


The Future of
Vehicular
Technology | 48



Densely Packed
ICs Blend
Components | 66



A Different
View of
Power Sensors | 70



microwaves&rf


JANUARY 2017

TRUSTED ENGINEERING RESOURCE FOR OVER 50 YEARS

www.mwrf.com

TOP TECH TO WATCH IN 2017

p|37



SEARCH
PARTS
FAST

 source**esb**

Parts

Enter part...

Enter List



\$10.00 Powered by **Penton***

Periodicals Postage Paid • USPS 100 Approved Poly

Your Trusted Source www.SourceESB.com



The Trusted Name in RF, Microwave & Millimeterwave ICs

Featured MACOM MMIC Devices

Application	Function	Part Number
SATCOM	Ka-Band Power Amplifier	MAAP-011289, 28 - 30.5 GHz
	Doubler Power Amplifier	MAFC-011009, 28 - 30 GHz
	L-Band Power Amplifier Module	MAAP-011060, 1616 - 1627 MHz
Test & Measurement	Wideband Power Amplifier	MAAP-011247, DC - 22 GHz
	Wideband Low Noise Amplifier	MAAL-011141, DC - 26.5 GHz
	Wideband DBL BAL Mixer	MAMX-011036, 8 - 43 GHz
Aerospace & Defense	Octave Band VCO	MAOC-415000, 10 - 20 GHz
	Power Amplifier	MAAP-011232, 0.1 - 3 GHz
Industrial, Scientific & Medical	Low Noise Amplifier	MAAL-011129, 18 - 32 GHz
	Gain Block	MAAM-011206, DC - 15 GHz
Wired Broadband	Variable Gain Amplifier	MAAM-011194, 45 - 1218 MHz
	Gain Block	MAAM-011220, 45 - 1218 MHz
	Very Low Noise Amplifier	MAAL-011136, 45 - 1218 MHz

Aerospace & Defense

Industrial, Scientific & Medical

Satellite Communications

Test & Measurement

Wired Broadband

MACOM delivers a leading portfolio of high-performance DC to 100 GHz MMICs


For over 60 years MACOM design and application experts have driven RF, Microwave and mmW innovation. Our engineers are delivering a new generation of wideband, high-performance MMICs for T&M, SATCOM, A&D, wired broadband and ISM applications.

Our 27 new MMIC products offer optimal performance, bandwidth, packaging and reliability to meet your most demanding requirements. New products include:

- › High Linearity SATCOM PAs
- › Wideband Amplifiers & Mixers
- › Single Bias LNAs & Gain Blocks
- › Broadband VCOs
- › V-, E- & W-Band Products
- › mmW Switches
- › Wideband Detectors
- › Broadband 75 ohm Amplifiers

Ka-Band 3 W Power Amplifier Ideal for Satellite Communications

Psat (dBm) and PAE (%) vs Frequency (GHz)



MACOM™

Partners from RF to Light

Learn more and get datasheet:

www.macom.com/mmics



Planar Monolithics Industries, Inc.

Monopulse Comparators

PMI designs and manufactures a variety of coaxial monopulse comparators for beamforming antenna applications up to 26.5 GHz. Form, fit and functional designs can also be replicated to specific requirements. Standard models with various options are available at PMI's website (Link below)

http://pmi-rf.com/Products/monopulse_comparators/features.htm

Model: MPC-20R2G21R2G-CD-LNF 8 Input Monopulse Comparator with Gain

Frequency	20.2 - 21.2 GHz
Gain	0 dB, 5 dB Nom. (Selectable)
Noise Temperature /Figure	100 K / 1.3 dB Noise Figure
Phase Balance	±3° Maximum
DC Supply	+12 VDC @ 700 mA, -12 VDC @ 100 mA
Temperature	-55 °C to +85 °C



Package Size:
6.25" x Ø4.80" x 2.00"
Connectors: SMA (F)

Model: PMC-3G3D5G-6D8-SFF 4 Input Monopulse Comparator

Frequency	3.0 to 3.5 GHz
Insertion Loss	0.8 dB Max. - Measured 0.4 dB
VSWR	1.25:1 Max. - Measured 1.25:1
Isolation	23 dB Min. - Measured 25.052 dB
Amplitude Balance	±0.4 dB Max. - Measured ±0.2681 dB
Phase Balance	±5° Maximum - Measured ±3.2°
RF Input Power	Average: 11 Watt Max. Peak: 0.1 kW Max.
Temperature	-55 °C to +85 °C



Package Size:
3.23" x 3.23" x 0.43"
Connectors: SMA (F)

Model: PD-CD-001-1, 4 Way Phase Shift Power Divider with 0°, 90°, 180°, 270° Outputs

Frequency	9.3 - 9.9 GHz
Insertion Loss	8.0 dB Max. - Measured 6.97 dB Max
VSWR	2.0:1 Max. - Measured 1.60:1 Max.
Amplitude Balance	±0.5 dB Max. - Measured ±0.2 dB Max.
Phase Balance	±7.0° Max. - Measured ±4° Max.
RF Input Power	28 W CW, 750 W Peak
Temperature	-32 °C to +77 °C Operating



Package Size:
2.35" x 1.7" x 0.5"
Connectors: SMA (F)

Amplifiers – Solid State
Attenuators – Variable/
Programmable
Couplers (Quadrature,
180° & Directional)
Detectors – RF/Microwave
DLVAs, ERLVAs
& SDLVAs
DTOs, VCOs, PLO, DROs,
& Frequency Synthesizers
Filters & Switched
Filter Banks
Form, Fit, Functional
Products & Services
Frequency Discriminators
& IFMs
Integrated MIC/MMIC
Assemblies (IMAs)
IQ Vector Modulators
Limiters – RF/Microwave
Log Amplifiers
Millimeter Wave
Components
(Up to 50 GHz)
Miscellaneous Products
Monopulse Comparators
Multifunction Integrated
Assemblies (MIAs)
Phase Shifters & Bi-Phase
Modulators
Power Dividers/Combiners
(Passive & Active)
Pulse Modulators (SPST)
Rack & Chassis Mount
Products
Receiver Front Ends
& Transceivers
SDLVAs, ERLVAs
& DLVAs
Single Side Band
Modulators
SMT & QFN Products
Switch Matrices
Switched Filter Banks
Switches – Solid State
Systems – Fly Eye Radars
Threshold Detectors
USB Products



Austin, Texas
October 30 – November 4, 2016
amta2016.org
Booth: L01

MILCOM2016

Baltimore, MD
November 1-3, 2016
www.milcom.org
Booth: 3004

West Coast Operation:

4921 Robert J. Mathews Pkwy, Suite 1
El Dorado Hills, CA 95762 USA
Tel: 916-542-1401, Fax: 916-265-2597


East Coast Operation:

7311-F Grove Road
Frederick, MD 21704 USA
Tel: 301-662-5019, Fax: 301-662-1731

sales@pmi-rf.com • www.pmi-rf.com

ISO9001-2008 REGISTERED

18 GHz THAT MOVES AT THE SPEED OF LIGHT



narda  **MITEQ**



Enclosures are available for multiple transmitter or receiver combinations.

18 GHz High-Reliability IF and RF Fiber-Optic Links

L3 Narda-MITEQ's hermetically sealed fiber-optic links are ideal for transmitting both IF and RF signals optically, making them the perfect choice for a variety of applications like antenna remoting and EMC/EMI. Models are available with instantaneous bandwidths of up to 18 GHz and offer a spurious-free dynamic range of 101 dB/Hz. These dynamic transmitters and receivers use standard wavelengths of 1550 nm and 1310 nm, performing in a wide temperature range of -40 °C to +85 °C with a typical low signal loss of 0.4 dB/km. So when your project demands the transmission of reliable IF and RF data optically, count on L3 Narda-MITEQ – *your best resource for innovative fiber-optic solutions.*

Learn more about our product line by visiting us at nardamiteq.com, or call us at (631) 231-1700.

ONE PLATFORM, ZERO BARRIERS

SIMPLY SMARTER


NI AWR DESIGN ENVIRONMENT

NI AWR Design Environment is a single platform that integrates system, circuit, and EM analysis for the design of today's advanced wireless products, from base stations to cellphones to satellite communications. Its intuitive use model, proven simulation technologies, and open architecture supporting third-party solutions translates to zero barriers for your design success.

Simply smarter design.



Learn more at ni.com/awr



In This Issue

FEATURES

37 COVER STORY:

5 TECHNOLOGY AREAS TO WATCH IN 2017

This year, expect to see the RF/microwave industry produce solutions that push technological boundaries to meet new and emerging requirements.

44 HARVESTING ENERGY FROM RF SOURCES

Excess energy from transmitted communications signals can be captured and transformed to dc power, perfect for a wide range of low-power electronic devices.

48 DRIVING THE FUTURE OF VEHICULAR TECHNOLOGY

Electronic technologies, from basic temperature sensors to millimeter-wave radars, are playing more prominent roles in new car models.

52 UWB PRINTED ANTENNA BLOCKS SATELLITE AND WLAN SIGNALS


This novel monopole monopole UWB antenna provides two notched bands for rejecting interference from 5-GHz WLAN signals and 8-GHz X-band satellite signals.

58 HOW BENDING AFFECTS A FLEXIBLE UWB ANTENNA


A compact antenna maintains high gain and an omnidirectional radiation pattern, even with flexing across frequency ranges complying with UWB frequency allocations in the U.S. and Europe.

80 NYU WIRELESS DRIVES NEXT-GENERATION TECHNOLOGY


Students and faculty at NYU WIRELESS are fervently working to create the wireless technology of the future.




58



37



48



52

PRODUCT TECHNOLOGY

- 66** Component-Packed Receiver ICs
- 70** Power Sensor Trends
- 73** High-Power LDMOS Transistors
- 74** Wideband Signal Analyzer
- 77** Switch Matrix for Multichannel Testing
- 78** 1/f Noise Characterization System

NEWS & COLUMNS

- 10** ON MWRF.COM
- 13** EDITORIAL
- 18** FEEDBACK
- 20** NEWS
- 28** R&D ROUNDUP
- 32** INSIDE TRACK
with James Kimery,
National Instruments
- 64** APPLICATION NOTES
- 84** NEW PRODUCTS
- 88** ADVERTISERS INDEX



JOIN US ONLINE



follow us @MicrowavesRF



become a fan at
facebook.com/microwavesRF




80



Enabling Wireless Connectivity for the Internet of Things

New Front-end Modules for IoT Applications



| Consumer Electronics

High-performance 5.0 GHz WLAN Front-end Module: SKY85712-21

For 802.11ac networking and personal computing systems, PC cards and WLAN-enabled wireless video systems

2.4 GHz, 64 QAM WLAN Front-end Modules: SKY85314-11, SKY85325-11

For 802.11b / g / n networking, set-top boxes, and personal computing systems

2.4 GHz, 256 QAM WLAN / Bluetooth® Front-end Module: SKY85303-21

For WiFi-enabled smartphones, tablets, and mobile / portable devices



| Connected Home and Wearables

Low-power Bluetooth® Low Energy Front-end Module: SKY66111-11

For fitness trackers, smartwatches, wireless headphones and in-home appliances

2.4 GHz ZigBee® / Thread / Bluetooth® 5 / 802.15.4 Smart Front-end Module: SKY66112-11

For home automation, alarms and industrial sensors

Ultra-low Power 2.4 GHz ZigBee® / Thread / Bluetooth® 5 / 802.15.4 Front-end Module: SKY66113-11

For smart thermostats and alarms, security, lighting, wireless headphones and fitness trackers

2.4 GHz ZigBee® / Thread / Bluetooth® 5 Low Energy / 802.15.4 Front-end Module: SKY66114-11

For in-home appliances, smart thermostats, lighting, alarms and industrial sensors



| Machine-to-Machine (M2M)

LTE Dual-band Front-end Module: SKY68000-21

For 4G / LTE devices, cellular modem devices, and low-power, wide area networks (LPWAN)

LTE Universal Multi-band Front-end Module: SKY68001-21


For 4G / LTE devices, cellular modem low- and mid-band devices, and low-power, wide area networks (LPWAN)

LTE Multi-band Front-end Module: SKY68011-21

For 4G / LTE devices, cellular modem devices, and low-power, wide area networks (LPWAN)

***For more information about all of our wireless solutions,
please visit us at www.skyworksinc.com***

BETTER COMMUNICATION SOLUTIONS



Low PIM Couplers



Low PIM Attenuators


4.3/10.0



Low PIM Terminations



Power Divider/Combiner



Directional Couplers
MIL-DTL-15370 Available



Tower Top & D.A.S Equipment



Public Safety



Satcom, mmWave
& Military



Aeronautical/Space
Transportation



AMER, EMEA,
& D.A.S



Millimeter-Wave

MECA 5G Products & Equipment

MECA Electronics designs and manufactures an extensive line of RF/Microwave Equipment and Components with industry leading performance including D.A.S. Equipment, Low PIM Products, supports 5G & Millimeter-Wave, Power Dividers & Combiners, Directional & Hybrid Couplers, Fixed & Variable Attenuators, RF Terminations, Circulators/Isolators, DC Blocks & Bias Tees, Adapters & Jumpers. Models available in industry common connector styles: N, SMA, 2.92mm, TNC, BNC, 7/16, 4.1/9.5 & 4.3/10.0 DIN as well as QMA, Reverse Polarity SMA, TNC and

various mounting solutions. Since 1961 MECA Electronics (Microwave Equipment & Components of America) has served the RF/Microwave industry with equipment and passive components covering Hz to 40 GHz. MECA is a privately held ISO9001:2008 Certified, global designer and manufacturer for the communications industry with products manufactured in the United States of America. We stock products so that you do not need to.

Buy Online

Products in STOCK when you need it!



RFPartsOnDemand.com



e-MECA.com
Since 1961

MECA Electronics, Inc.
Microwave Equipment & Components of America

459 E. Main St., Denville, NJ 07834

Tel: 973-625-0661 • Fax: 973-625-9277 • Sales@e-MECA.com




World's Only High-Performance Solid-State RF Power Amplifiers Up To 350 kW

WEB | www.111rfpower.com
EMAIL | sales@111rfpower.com
TEL | (951) 343-4005
 6690 Doolittle Avenue
 Riverside, CA 92503



Example of conservatively-rated 150 to 218 MHz, 1 kW CW module for AM, FM, CW, or pulse applications in a ruggedized 4.1 x 2.7 x 1.2 in., 17 oz. package. Rated for altitudes to 30,000 ft. and MIL-STD-810F Method 516.5 shock and vibration.



This amplifier delivers 16 kW at a 20% duty cycle from 3.5 to 450 MHz with transmit and receive switching less than 1.5 μ s with 60-dB isolation in a 24 x 19.25 x 18 in. enclosure.

Delta-Sigma, Inc., is a world leader in the design and manufacture of high-performance solid-state RF power amplifier modules, subsystems, and systems up to 350 kW for defense, commercial, and scientific applications. Our modular designs elegantly scale from 1-kW subsystems to the industry's highest-power, solid-state turnkey systems for fast turn-around, low system cost, reduced complexity, and exceptional reliability. And we specialize in helping our customers transition from legacy vacuum-tube amplifiers to modern solid-state designs.

OUR AMPLIFIERS SERVE APPLICATIONS INCLUDING:

- Electronic warfare
- Commercial and military communications
- Industrial RF heating
- EMC testing
- Synthetic aperture radar (SAR)
- Wind profiler radars to at least 60,000 ft.
- Particle accelerators
- Satellite communications

EXCEPTIONAL PERFORMANCE:

- Compact and lightweight
- Exceptionally reliable and rugged
- Highest efficiency: DC-to-RF greater than 70% and system AC-to-RF greater than 50%
- High linearity: Proprietary linearization circuitry delivers system-level third-order IMD as low as -91 dBc
- Rated for CW and pulsed operation
- Pulse width to 30 ns with zero droop and ringing
- Noise in receive mode near the thermal limit
- Switching speed typically less than 1 μ s and isolation of 60 dB.

YOUR RF AMPLIFIER PARTNER SINCE 1995

For more than two decades, Delta-Sigma, Inc., has worked together with our customers to create some of the world's most impressive synergistic RF power amplifier systems. So please contact us with your requirements!



350 kW CW Spoken Here

At Delta-Sigma, Inc., home of the world's most powerful solid-state RF power amplifiers since 1995



Delta-Sigma, Inc. has been building state-of-the-art high-power RF amplifiers since 1995 and has been setting new benchmarks along the way. Today we offer complete compact turnkey systems from 1 kW to 350 kW CW or pulse (the highest in the industry) with exceptional linearity, efficiency, and ruggedness.

For example, NASA's new 250-kW, 48-MHz Doppler radar wind profiler at Kennedy Space Center provides critical pre-launch wind data up to 60,000 ft. and was designed and built by Delta-Sigma, Inc. It's the only such system in the world to be powered by RF power transistors.

Delivering capability like this requires teamwork and partnership, something Delta-Sigma, Inc. is proud of and offers every customer, large or small. So whether you're making the transition from vacuum tubes to solid-state, need 1-kW solid-state amplifiers for battlefield radios, or a complete high-power system for radar, EW, scientific, or industrial applications, Delta-Sigma, Inc., can build a custom solution that meets or exceeds your requirements.


PLEASE CONTACT US TODAY
WITH YOUR DESIGN REQUIREMENTS!
(951) 343-4005 or sales@111rfpower.com

This Centurion 250-kW solid-state system powers NASA's new Doppler Radar Wind Profiler at Cape Canaveral's launch facility.



DELTA-SIGMA, INC., 6690 DOOLITTLE AVE., RIVERSIDE, CA 92503 | **(951) 343-4005**


www.111rfpower.com



FIERCELY INDEPENDENT IN MAKING MEASUREMENTS

<http://mwrf.com/blog/fiercely-independent-making-measurements>

Every editor covering electronics technology dreams about having their own test laboratory—a station to provide our observations on the “published specifications” provided to us when writing stories about RF/microwave hardware. But be careful what you wish for.



TRACKING EFFECTS OF TEMPERATURE

<http://mwrf.com/software/tracking-effects-temperature>

Thermal modeling is becoming a more important part of the electronic design process, especially with increasing efforts to pack more power into smaller electronic devices. Quite simply, power = heat. Where power is generated or transferred, any form of loss will result in the production of heat. For the preservation of an electronic design, the heat must be efficiently removed.



ARE YOU BEING AFFECTED BY PHASE COHERENCE?

<http://mwrf.com/blog/are-you-being-affected-phase-coherence>

Phase coherence can be an ambiguous topic, yet one that's important for RF, electrical, and design engineers to understand. This article will set out and build upon some basic definitions, ultimately enabling you to determine if and why phase coherence is affecting your various designs and applications.

CRITICAL TALKING POINTS IN TEST & MEASUREMENT

<http://mwrf.com/test-measurement-analyzers/critical-talking-points-test-measurement>

As wireless technology continues to invade our lives, suppliers of test-and-measurement equipment must keep up by offering the proper test solutions to meet today's needs. And the same suppliers must also think in terms of the future, with 5G obviously being on the minds of many.



join us online  

twitter.com/MicrowavesRF facebook.com/microwavesrf



ULTRACMOS®

Breaking MORE Barriers in RF SOI

Peregrine Semiconductor has been breaking barriers in RF silicon on insulator (SOI) for nearly three decades.

Our UltraCMOS® technology has enabled us to set a new record for high linearity, introduce the first high frequency RF SOI mixer, announce the world's fastest GaN FET driver and take RF SOI to new heights with the first 60 GHz RF SOI switches. And that was just last year. In 2017 and beyond, Peregrine will break even MORE barriers in RF SOI. Discover the many benefits of UltraCMOS technology—high performance, monolithic integration, low power consumption, flexibility, a small footprint and high reliability.


To find out if UltraCMOS technology could be the answer to your design challenges, visit www.psemi.com or contact sales@psemi.com.

A Murata Company



MMIC AMPLIFIERS

50 MHz to 26.5 GHz



PHA-1+ \$**1**99
0.05-6 GHz ea. (qty. 20)
Gain 13.5 dB
P_{out} 22 dBm

AVA-183A+ \$**7**95
5-18 GHz ea. (qty. 20)
Gain 14.0 dB
P_{out} 19 dBm

AVM-273HPK+ \$**36**90
13-26.5 GHz ea. (qty. 10)
Gain 13.0 dB
P_{out} 27 dBm



We've got you covered!

3 MMIC amplifiers support the whole gamut of applications from 50 MHz all the way up to 26.5 GHz!

Mini-Circuits' AVM-273HPK+ wideband microwave MMIC amplifier supports applications from 13 to 26.5 GHz with up to 0.5W output power, 13 dB gain, ± 1 dB gain flatness and 58 dB reverse isolation. The amplifier comes supplied with a voltage sequencing and DC control module providing reverse voltage protection in one tiny package to simplify your circuit design. This model is an ideal buffer amplifier for P2P radios, military EW and radar, DBS, VSAT and more!

The AVA-183A+ delivers 14 dB gain with excellent gain flatness (± 1.0 dB) from 5 to 18 GHz, 38 dB isolation, and 19 dBm power handling. It is unconditionally stable and an ideal LO driver amplifier. Internal DC blocks, bias tee, and microwave coupling capacitor simplify external circuits, minimizing your design time.

The PHA-1+ uses E-PHEMT technology to offer ultra-high dynamic range, low noise, and excellent IP3 performance, making it ideal for LTE, and TD-SCDMA. Good input and output return loss across almost 7 octaves extend its use to CATV, wireless LANs, and base station infrastructure.

Visit minicircuits.com for full specs, performance curves, and free data! These models are in stock and ready to ship today!

FREE X-Parameters-Based
Non-Linear Simulation Models for ADS



<http://www.modelithics.com/mvp/Mini-Circuits.asp>



Editorial

CHRIS DeMARTINO

Technical Editor

chris.demartino@penton.com



Will 2017 Be the Year of the Engineer?

All things considered, 2017 certainly looks to be a significant year for the RF/microwave industry. Of course, we will continue to hear about 5G as it inches closer to reality. We can also expect to hear all sorts of reports concerning the Internet of Things (IoT). Driverless cars are sure to make headlines, too. The list goes on.

Whether it's texting a friend or watching a YouTube video on an iPhone, wireless technology is now clearly entrenched in our lives. It is impossible to walk around here in New York City and not see people texting on the street or looking at something on their phone while waiting for the train. We can get so distracted by a text message conversation that we become unaware of what's happening around us (I have been guilty of this myself).

Although wireless technology is such a major part of our lives, does society appreciate the engineers who are responsible for it? Are engineers more or less appreciated than, say, teachers and health professionals? Teachers should be respected—their jobs can often be difficult and stressful. I have teacher friends who can certainly attest to that. The same can be said for the nursing profession. I also know several nurses who can relate to having stressful jobs. One can make the case that teachers and nurses are seriously underappreciated (but I won't get into that here).

What about engineers? Are they appreciated? I'm not sure, but it is clear that many people—and understandably so—have no idea of the concept of RF/microwave engineering. I am positive that many of you reading this right now have experienced telling someone that you work in the "microwave" industry—or for a "microwave" company—only to wind up explaining to that same person that you don't actually work with microwave ovens. This simply underscores how wireless technology is relied upon, but not really understood.

Whether you may or may not feel appreciated, you should nonetheless feel some satisfaction today if you are a part of this industry. After all, you are creating the technology that so many people depend on—whether they realize it or not. **mw**

JOIN US ONLINE twitter.com/MicrowavesRF
become a fan at facebook.com/MicrowavesRF



ZERO BIAS SCHOTTKY DETECTORS

For 0.01 - 50 GHz



Many Models Available in Stock



- > Single unit covers 0.01 - 50 GHz
- > Matched input for low VSWR
- > Flat frequency response
- > High sensitivity (0.5 mV/μW up to 50 GHz)
- > Optional output connectors (SMA, BNC, SMC)
- > Great for instrumentation and laboratory use

MODEL	FREQ. RANGE	MAX. VSWR	MAXIMUM FLATNESS (± dB)	LOW LEVEL SENSITIVITY (mV / μW)
DZR50024A	10 MHz-50 GHz	1.3:1 (to 18 GHz)	± 0.3 (to 18 GHz)	0.5
DZR50024B	10 MHz-50 GHz	1.6:1 (to 26 GHz): 1.8:1 (to 40 GHz): 2:1 (to 50 GHz)	± 0.6 (to 26 GHz): ± 0.8 (to 40 GHz): ± 1.0 (to 50 GHz)	0.5
DZR50024C	10 MHz-50 GHz	1.8:1 (to 40 GHz): 2:1 (to 50 GHz)	± 0.8 (to 40 GHz): ± 1.0 (to 50 GHz)	0.5

*All models have 2.4 mm (M) input connector
*Standard output polarity is negative.
Add letter "P" to end of model number for positive output.

Custom Designs - Write / Call for Quote

Other Products:

Amplifiers, Comb Generators, Limiters,
Switches, Integrated Subsystems




155 BAYTECH DRIVE, SAN JOSE, CA. 95134-2303

PH: 408-941-8399 . FAX: 408-941-8388

E-Mail: Info@Herotek.com

Web Site: <http://www.herotek.com>

Visa/MasterCard Accepted





POWER SPLITTERS/ COMBINERS

from **2 kHz to 40 GHz** as low as **94¢** ea. (qty. 1000)

NEW!

**THE WIDEST BANDWIDTH IN THE INDUSTRY
IN A SINGLE MODEL!**

EP2K1+ 2 to 26.5 GHz

EP2W1+ 0.5 to 9.5 GHz

EP2C+ 1.8 to 12.5 GHz


The industry's largest selection includes THOUSANDS of models from 2 kHz to 40 GHz, with up to 300W power handling, in coaxial, flat-pack, surface mount and rack mount housings for 50 and 75Ω systems.

From 2-way through 48-way designs, with 0°, 90°, or 180° phase configurations, Mini-Circuits' power splitter/combiners offer a vast selection of features and capabilities to meet your needs from high power and low insertion loss to ultra-tiny LTCC units and much more.

Need to find the right models fast? Visit minicircuits.com and use Yoni2®!

It's our patented search engine that searches actual test data for the models that meet your specific requirements! You'll find test data, S-parameters, PCB layouts, pricing, real-time availability, and everything you need to make a smart decision fast!

All Mini-Circuits' catalog models are available off the shelf for immediate shipment, so check out our website today for delivery as soon as tomorrow!

 **RoHS Compliant**
Product availability is listed on our website.

 **Mini-Circuits®**

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

448 rev S

PIN DIODE CONTROL DEVICES

PIN DIODE

ATTENUATORS

- 0.1–20GHz
- Broad & narrow band models
- Wide dynamic range
- Custom designs



Attenuator types offered are: Current Controlled, Voltage Controlled, Linearized Voltage Controlled, Digitally Controlled and Digital Diode Attenuators.

PIN DIODE

SWITCHES

- Broad & narrow band models
- 0.1–20GHz
- Small size
- Custom designs



SPST thru SP8T and Transfer type models are offered and all switches are low loss with isolation up to 100dB. Reflective and non-reflective models are available along with TTL compatible logic inputs. Switching speeds are 1μsec.—30nsec. and SMA connectors are standard. Custom designs including special logic inputs, voltages, connectors and package styles are available. All switches meet MIL-E-5400

PIN DIODE

PHASE SHIFTERS

- 0.5–20GHz
- Switched Line
- Varactor Controlled
- Vector Modulators
- Bi-Phase Modulators
- QPSK Modulators
- Custom Designs



SUBASSEMBLIES

Passive Components and Control Devices can be integrated into subassemblies to fit your special requirements. Call for more information and technical assistance.



Custom Designs

CALL OR WRITE

waveline[®]
SOLID STATE INC

P.O. Box 718, West Caldwell, NJ 07006
(973) 226-9100 Fax: 973-226-1565
E-mail: wavelineinc.com

JANUARY | 2017

microwaves&rf

Powered by Penton[®]

EDITORIAL

CONTENT DIRECTOR: **NANCY K. FRIEDRICH** nancy.friedrich@penton.com
TECHNICAL CONTRIBUTOR: **JACK BROWNE** jack.browne@penton.com
TECHNICAL ENGINEERING EDITOR: **CHRIS DeMARTINO** chris.demartino@penton.com
CONTENT PRODUCTION DIRECTOR: **MICHAEL BROWNE** michael.browne@penton.com
PRODUCTION EDITOR: **JEREMY COHEN** jeremy.cohen@penton.com
CONTENT PRODUCTION SPECIALIST: **ROGER ENGELKE** roger.engelke@penton.com
CONTENT OPTIMIZATION SPECIALIST: **WES SHOCKLEY** wes.shockley@penton.com
ASSOCIATE CONTENT PRODUCER: **LEAH SCULLY** leah.scully@penton.com
ASSOCIATE CONTENT PRODUCER: **JAMES MORRA** james.morra@penton.com

ART DEPARTMENT

GROUP DESIGN DIRECTOR: **ANTHONY VITOLO** tony.vitolo@penton.com
SENIOR ARTIST: **JIM MILLER** jim.miller@penton.com
CONTENT DESIGN SPECIALIST: **JOCELYN HARTZOG** jocelyn.hartzog@penton.com
CONTENT DESIGN SPECIALIST: **TIM DRIVER** tim.driver@penton.com
CONTENT & DESIGN PRODUCTION MANAGER: **JULIE JANTZER-WARD** julie.jantzer-ward@penton.com

PRODUCTION

GROUP PRODUCTION MANAGER: **CAREY SWEETEN** carey.sweeten@penton.com
PRODUCTION MANAGER: **VICKI MCCARTY** vicki.mccarty@penton.com
CLASSIFIED PRODUCTION COORDINATOR: **LINDA SARGENT** linda.sargent@penton.com

AUDIENCE MARKETING

USER MARKETING DIRECTOR: **BRENDA ROODE** brenda.roode@penton.com
USER MARKETING MANAGER: **DEBBIE BRADY** debbie.brady@penton.com
FREE SUBSCRIPTION/STATUS OF SUBSCRIPTION/ADDRESS CHANGE/MISSING BACK ISSUES
OMEDA T | 847.513.6022 TOLL FREE | 866.505.7173

SALES & MARKETING

MANAGING DIRECTOR: **TRACY SMITH** T | 913.967.1324 F | 913.514.6881 tracy.smith@penton.com
REGIONAL SALES REPRESENTATIVES
AZ, NM, TX: **GREGORY MONTGOMERY** T | 480.254.5540 gregory.montgomery@penton.com
AK, CA, CO, ID, MT, ND, NV, OR, SD, UT, WA, WI, WY, W/CANADA: **JAMIE ALLEN** T | 415.608.1959
F | 913.514.3667 jamie.allen@penton.com
AL, AR, IA, IL, IN, KS, KY, LA, MI, MN, MO, MS, NE, OH, OK, TN: **PAUL MILNAMOW** T | 312.840.8462
paul.milnamow@penton.com
CT, DE, FL, GA, MA, MD, ME, NC, NH, NJ, NY, RI, PA, SC, VA, VT, WV, EASTERN CANADA:
SHANNON ALO-MENDOSA T | 978.501.7303 shannon.alo-mendoza@penton.com
INTERNATIONAL SALES
GERMANY, AUSTRIA, SWITZERLAND: **CHRISTIAN HOELSCHER** T | 011.49.89.95002778
christian.hoelscher@husonmedia.com
BELGIUM, NETHERLANDS, LUXEMBURG UNITED KINGDOM, SCANDINAVIA, FRANCE, SPAIN, PORTUGAL:
JAMES RHOADES-BROWN T | +011 44 1932 564999 M | +011 44 1932 564998
james.rhoadesbrown@husonmedia.com
PAN-ASIA: **HELEN LAI** T | 886 2-2727 7799 helen@twoway.com.com

PLEASE SEND INSERTION ORDERS TO: orders@penton.com
PENTON REPRINTS: **WRIGHT'S MEDIA** T | 877.652.5295 penton@wrightsmedia.com
LIST RENTALS:
SMARTREACH CLIENT SERVICES MANAGER: **JAMES ADDISON** T | 212.204.4318 james.addison@penton.com

ONLINE

PRODUCT DEVELOPMENT DIRECTOR: **RYAN MALEC** ryan.malec@penton.com

DESIGN ENGINEERING & SOURCING GROUP

EXECUTIVE DIRECTOR OF CONTENT AND USER ENGAGEMENT: **NANCY K. FRIEDRICH**
GROUP DIRECTOR OF OPERATIONS: **CHRISTINA CAVANO**
GROUP DIRECTOR OF MARKETING: **JANE COOPER**

PENTON

1166 AVENUE OF THE AMERICAS, 10TH FLOOR, NEW YORK, NY 10036 T | 212.204.4200

Penton

Electronic Design | Machine Design | Microwaves & RF | Source ESB | Hydraulics & Pneumatics |
Global Purchasing | Distribution Resource | Power Electronics | Defense Electronics


PENTON IS AN INFORMA BUSINESS

RF Amplifiers and Sub-Assemblies for Every Application

Delivery from Stock to 2 Weeks ARO from the catalog or built to your specifications!

- Competitive Pricing & Fast Delivery
- Military Reliability & Qualification
- Various Options: Temperature Compensation, Input Limiter Protection, Detectors/TTL & More
- Unconditionally Stable (100% tested)

ISO 9001:2000
and AS9100B
CERTIFIED



OCTAVE BAND LOW NOISE AMPLIFIERS

Model No.	Freq (GHz)	Gain (dB) MIN	Noise Figure (dB)	Power-out @ P1dB	3rd Order ICP	VSWR
CA01-2110	0.5-1.0	28	1.0 MAX, 0.7 TYP	+10 MIN	+20 dBm	2.0:1
CA12-2110	1.0-2.0	30	1.0 MAX, 0.7 TYP	+10 MIN	+20 dBm	2.0:1
CA24-2111	2.0-4.0	29	1.1 MAX, 0.95 TYP	+10 MIN	+20 dBm	2.0:1
CA48-2111	4.0-8.0	29	1.3 MAX, 1.0 TYP	+10 MIN	+20 dBm	2.0:1
CA812-3111	8.0-12.0	27	1.6 MAX, 1.4 TYP	+10 MIN	+20 dBm	2.0:1
CA1218-4111	12.0-18.0	25	1.9 MAX, 1.7 TYP	+10 MIN	+20 dBm	2.0:1
CA1826-2110	18.0-26.5	32	3.0 MAX, 2.5 TYP	+10 MIN	+20 dBm	2.0:1

NARROW BAND LOW NOISE AND MEDIUM POWER AMPLIFIERS

CA01-2111	0.4 - 0.5	28	0.6 MAX, 0.4 TYP	+10 MIN	+20 dBm	2.0:1
CA01-2113	0.8 - 1.0	28	0.6 MAX, 0.4 TYP	+10 MIN	+20 dBm	2.0:1
CA12-3117	1.2 - 1.6	25	0.6 MAX, 0.4 TYP	+10 MIN	+20 dBm	2.0:1
CA23-3111	2.2 - 2.4	30	0.6 MAX, 0.45 TYP	+10 MIN	+20 dBm	2.0:1
CA23-3116	2.7 - 2.9	29	0.7 MAX, 0.5 TYP	+10 MIN	+20 dBm	2.0:1
CA34-2110	3.7 - 4.2	28	1.0 MAX, 0.5 TYP	+10 MIN	+20 dBm	2.0:1
CA56-3110	5.4 - 5.9	40	1.0 MAX, 0.5 TYP	+10 MIN	+20 dBm	2.0:1
CA78-4110	7.25 - 7.75	32	1.2 MAX, 1.0 TYP	+10 MIN	+20 dBm	2.0:1
CA910-3110	9.0 - 10.6	25	1.4 MAX, 1.2 TYP	+10 MIN	+20 dBm	2.0:1
CA1315-3110	13.75 - 15.4	25	1.6 MAX, 1.4 TYP	+10 MIN	+20 dBm	2.0:1
CA12-3114	1.35 - 1.85	30	4.0 MAX, 3.0 TYP	+33 MIN	+41 dBm	2.0:1
CA34-6116	3.1 - 3.5	40	4.5 MAX, 3.5 TYP	+35 MIN	+43 dBm	2.0:1
CA56-5114	5.9 - 6.4	30	5.0 MAX, 4.0 TYP	+30 MIN	+40 dBm	2.0:1
CA812-6115	8.0 - 12.0	30	4.5 MAX, 3.5 TYP	+30 MIN	+40 dBm	2.0:1
CA812-6116	8.0 - 12.0	30	5.0 MAX, 4.0 TYP	+33 MIN	+41 dBm	2.0:1
CA1213-7110	12.2 - 13.25	28	6.0 MAX, 5.5 TYP	+33 MIN	+42 dBm	2.0:1
CA1415-7110	14.0 - 15.0	30	5.0 MAX, 4.0 TYP	+30 MIN	+40 dBm	2.0:1
CA1722-4110	17.0 - 22.0	25	3.5 MAX, 2.8 TYP	+21 MIN	+31 dBm	2.0:1

ULTRA-BROADBAND & MULTI-OCTAVE BAND AMPLIFIERS

Model No.	Freq (GHz)	Gain (dB) MIN	Noise Figure (dB)	Power-out @ P1dB	3rd Order ICP	VSWR
CA0102-3111	0.1-2.0	28	1.6 Max, 1.2 TYP	+10 MIN	+20 dBm	2.0:1
CA0106-3111	0.1-6.0	28	1.9 Max, 1.5 TYP	+10 MIN	+20 dBm	2.0:1
CA0108-3110	0.1-8.0	26	2.2 Max, 1.8 TYP	+10 MIN	+20 dBm	2.0:1
CA0108-4112	0.1-8.0	32	3.0 MAX, 1.8 TYP	+22 MIN	+32 dBm	2.0:1
CA02-3112	0.5-2.0	36	4.5 MAX, 2.5 TYP	+30 MIN	+40 dBm	2.0:1
CA26-3110	2.0-6.0	26	2.0 MAX, 1.5 TYP	+10 MIN	+20 dBm	2.0:1
CA26-4114	2.0-6.0	22	5.0 MAX, 3.5 TYP	+30 MIN	+40 dBm	2.0:1
CA618-4112	6.0-18.0	25	5.0 MAX, 3.5 TYP	+23 MIN	+33 dBm	2.0:1
CA618-6114	6.0-18.0	35	5.0 MAX, 3.5 TYP	+30 MIN	+40 dBm	2.0:1
CA218-4116	2.0-18.0	30	3.5 MAX, 2.8 TYP	+10 MIN	+20 dBm	2.0:1
CA218-4110	2.0-18.0	30	5.0 MAX, 3.5 TYP	+20 MIN	+30 dBm	2.0:1
CA218-4112	2.0-18.0	29	5.0 MAX, 3.5 TYP	+24 MIN	+34 dBm	2.0:1

LIMITING AMPLIFIERS

Model No.	Freq (GHz)	Input Dynamic Range	Output Power Range Psat	Power Flatness dB	VSWR
CLA24-4001	2.0 - 4.0	-28 to +10 dBm	+7 to +11 dBm	+/- 1.5 MAX	2.0:1
CLA26-8001	2.0 - 6.0	-50 to +20 dBm	+14 to +18 dBm	+/- 1.5 MAX	2.0:1
CLA712-5001	7.0 - 12.4	-21 to +10 dBm	+14 to +19 dBm	+/- 1.5 MAX	2.0:1
CLA618-1201	6.0 - 18.0	-50 to +20 dBm	+14 to +19 dBm	+/- 1.5 MAX	2.0:1

AMPLIFIERS WITH INTEGRATED GAIN ATTENUATION

Model No.	Freq (GHz)	Gain (dB) MIN	Noise Figure (dB)	Power-out @ P1dB	Gain Attenuation Range	VSWR
CA001-2511A	0.025-0.150	21	5.0 MAX, 3.5 TYP	+12 MIN	30 dB MIN	2.0:1
CA05-3110A	0.5-5.5	23	2.5 MAX, 1.5 TYP	+18 MIN	20 dB MIN	2.0:1
CA56-3110A	5.85-6.425	28	2.5 MAX, 1.5 TYP	+16 MIN	22 dB MIN	1.8:1
CA612-4110A	6.0-12.0	24	2.5 MAX, 1.5 TYP	+12 MIN	15 dB MIN	1.9:1
CA1315-4110A	13.75-15.4	25	2.2 MAX, 1.6 TYP	+16 MIN	20 dB MIN	1.8:1
CA1518-4110A	15.0-18.0	30	3.0 MAX, 2.0 TYP	+18 MIN	20 dB MIN	1.85:1

LOW FREQUENCY AMPLIFIERS

Model No.	Freq (GHz)	Gain (dB) MIN	Noise Figure dB	Power-out @ P1dB	3rd Order ICP	VSWR
CA001-2110	0.01-0.10	18	4.0 MAX, 2.2 TYP	+10 MIN	+20 dBm	2.0:1
CA001-2211	0.04-0.15	24	3.5 MAX, 2.2 TYP	+13 MIN	+23 dBm	2.0:1
CA001-2215	0.04-0.15	23	4.0 MAX, 2.2 TYP	+23 MIN	+33 dBm	2.0:1
CA001-3113	0.01-1.0	28	4.0 MAX, 2.8 TYP	+17 MIN	+27 dBm	2.0:1
CA002-3114	0.01-2.0	27	4.0 MAX, 2.8 TYP	+20 MIN	+30 dBm	2.0:1
CA003-3116	0.01-3.0	18	4.0 MAX, 2.8 TYP	+25 MIN	+35 dBm	2.0:1
CA004-3112	0.01-4.0	32	4.0 MAX, 2.8 TYP	+15 MIN	+25 dBm	2.0:1

CIAO Wireless can easily modify any of its standard models to meet your "exact" requirements at the Catalog Pricing.

Visit our web site at www.ciaowireless.com for our complete product offering.

Ciao Wireless, Inc. 4000 Via Pescador, Camarillo, CA 93012

Tel (805) 389-3224 Fax (805) 389-3629 sales@ciaowireless.com



Feedback

ANOTHER PATH TO INDEPENDENCE?

I really enjoyed reading your article titled "Fiercely Independent in Making Measurements" just now (available on mwr.com). Your quest to "set up a test station to provide observations on published specifications" reminded me of someone else I know: me.

I launched JitterLabs (www.jitterlabs.com) last year as an independent test lab for characterizing clock sources for timing noise—primarily phase noise and jitter, which as you know are hotly contested and important specifications for their manufacturers and customers. It took me years to design and create a laboratory, in which I obsessed about providing the

most accurate data. I even obtained several patents, including one to remove spurs introduced by an oscilloscope. I also developed techniques to reduce artifacts introduced by baluns when measuring phase noise, something which the industry had not been aware of.

The lab's boundaries extend online, where all the test data is hosted for clock-device vendors, who use custom software to explore the data, run analyses, export results, etc. Additionally, it allows their customers to input custom specifications for clock performance (phase noise masks, jitter limits, custom filtering, etc.), and apply them to test data to create compliance statements. This way, customers can compare the performance of competing vendors' products, apples-to-apples. Any company can share their data with any other company they choose, to facilitate business. It's quite a novel business plan, which attempts to streamline traditional business processes by moving them online for greater efficiencies and cost savings.

While I can't loan you test equipment, I can provide perhaps something better— independent test data (which might be all you wanted, anyway), along with detailed documentation about how it's obtained, and software that runs in your favorite web browser to analyze the data in accordance with its intended end application.

Thanks for letting me share my experience. Please keep me in mind if I can ever help you out.

GARY GIUST, PH.D., JITTERLABS

EDITOR'S NOTE

Thanks for reading, and thanks for replying. JitterLabs sounds like it could provide an invaluable "second look" at a clock, especially since the clock is so critical to the performance of so many systems—whether commercial comms or military EW. We appreciate your offer to take a look at stuff for us. Perhaps we'll be able to take you up on it down the road. For now, at least, we can help spread the word that you and JitterLabs are out there and ready.

JACK BROWNE,
TECHNICAL CONTRIBUTOR

Powerful Multipath/Link Emulator


Multipath Rayleigh & Rician Fading
Unmanned Aerial Vehicle (UAV) testing
Sophisticated Satellite link emulation
Mobile Comm's on the move testing

**250 MHz
bandwidth**

Test solutions for

- WIN-T** - warfare information networks, tactical
- MUOS** - mobile user objective system
- JTRS** - Joint Tactical Radio System
- IRIS** - Internet routing in space

Software showing mobile link setup




dbm Corp, Inc
32A Spruce Street ♦ Oakland, NJ 07436
Tel (201) 677-0008 ♦ Fax (201) 677-9444

www.dbmcorp.com



Upgrade Your Mixer

2GHz–14GHz, 0dBm LO Drive




The LTC5549 microwave mixer upgrades your transmitter and receiver performance with a +22.8dBm IIP3 at 12GHz. Its 0dBm LO drive and an on-chip frequency doubler eliminate the need for an external LO power amplifier and allow use of commonly available low frequency PLL/synthesizers, reducing power consumption and solution costs — all in a tiny 3mm x 2mm package that keeps your solution size small.

▼ Features

- +22.8dBm IIP3 at 12GHz
- 0dBm LO Drive
- Upconversion or Downconversion
- –30dBm LO Leakage
- Tiny 3mm x 2mm Package

Demo Board



▼ Info & Free Samples

www.linear.com/product/LTC5549

1-800-4-LINEAR

LT, LT, LTC, LTM, Linear Technology and the Linear logo are registered trademarks of Linear Technology Corporation. All other trademarks are the property of their respective owners.

News

TAKING WIRELESS SENSOR Networks out of Factories and Putting Them in Cars

Inside its Silicon Valley wafer factory, Linear Technology has installed wireless sensors to monitor gas cylinders used in the manufacturing process and alert managers when to replace them. The chipmaker had little trouble selecting which sensors to buy—it designed them.

The sensors, equipped with wireless technology called SmartMesh IP, have found early success in the industrial Internet of Things, which aims to increase manufacturing efficiency by using sensor data and sharing it between machines. Linear Technology says that over 50,000 SmartMesh networks have been installed in places like GlaxoSmithKline's factory in Cork, Ireland, where they observe the drug company's water storage tanks.

But the company's engineers have a vision of pushing SmartMesh out of its industrial nest. Linear Technology recently said that it helped build a battery-management system for electric vehicles using SmartMesh chips and battery monitors. The idea was to cut out the complex and costly wiring that normally connects auto electronics.

The system paired the wireless SmartMesh devices with battery-monitoring circuits capable of tolerating lots of electrical noise and wide operating temperatures inside the battery cells of a BMW i3 electric vehicle. The devices reported the charge of each battery using a wireless technology called mesh networking, which shares wireless signals within a small community of the chips.



There are many potential stumbling blocks to using wireless technologies inside cars, including metal parts that could prove difficult for wireless signals to get through.

The battery-management system was built by Lion Smart using components from Linear Technology, which showed the BMW test vehicle at the electronica trade show in Munich, Germany in November. It stands out for using technology that was originally developed to cut costs and make it easier to add cheap sensors inside high-voltage factory environments.

The results were similar in new battery-management systems, said Erik Soule, Linear Technology's vice president of signal conditioning products, in a recent interview. The wireless chips eliminate the wires that normally deliver battery readings to a central computer, improving reliability and simplifying designs. There is a constant threat that the wires will shake loose or fail while driving.

The power required to drive electric cars is not usually contained in a single large battery. In the BMW i3, for example, two separate battery packs are located in the front and back of

the vehicle. Reporting their status to a central point normally falls to wires, like the popular CAN Bus cable or a proprietary technology like Linear Technology's isoSPI cable.

SmartMesh takes the cables out of the equation, allowing engineers to install the battery packs and sensors where wiring harnesses can't fit, said Soule. Getting more data about the batteries, like current and temperature, is as simple as adding more sensors. The wireless chips are also cheaper than the cabling, he said.

There are many potential stumbling blocks to using wireless technologies inside cars, said Soule. Electric cars are not safe environments for wireless signals. There are many metal parts that could prove difficult for wireless signals to get through and the high-voltage electronics create tons of electromagnetic noise.

But SmartMesh uses both path and frequency diversity, which routes the messages around obstacles as well as dampen interference. It is also constantly watching the network so that it can hop between channels when one gets too crowded. Linear Technology boasts that SmartMesh networks are "99.999% reliable."

The system has its limitations, though. Soule cautioned that SmartMesh doesn't have the response times to stream data

from critical sensors like radar or cameras that could help a vehicle automatically avoid a collision. The devices, which can synchronize their clocks to within several microseconds, were originally developed for factories and environmental sensing, prioritizing reliability and low power consumption over speed.

The concept of using wireless sensors inside cars also has history working against it. In 2010, researchers found that hackers could hijack the wireless pressure sensors built into the tires of some luxury vehicles. The researchers warned that criminals could exploit the vulnerability to track a vehicle or force its electronic control system to malfunction.

Soule pointed to SmartMesh's AES128 encryption as a thick insulation against hackers, but he also admits that the system is still a proof-of-concept. He said that he talked with representatives from several German automakers at the electronica demonstration. "There is huge interest," he noted.

Linear Technology acquired SmartMesh through its acquisition of Dust Networks in 2011, on the premise that its sensor networking chips could provide a wider audience for the power-management chips for which it is known. The technology has kept a low profile in the \$14.7 billion deal that Linear Tech signed in May to be acquired by Analog Devices, which is increasingly courting factories and cars with its chips. ■


MODULES EXTEND FREQUENCY Range of Testers into Millimeter-Wave Territory

MILLITECH RECENTLY RELEASED a pair of wireless modules that bolt onto test equipment and extend their frequency range into millimeter waves. It represents a part of the wireless spectrum that is being plumbed for transmitting a much larger volume of information than today's low frequencies.

The Spartan Test Modules, as they are called, extend a vector network analyzer into the 69-GHz range, also known as the V-band, and the 90-GHz or E-band range. The modules link to existing testers using standard connectors, saving engineers money that would otherwise be spent on custom test setups, the company said.

Millitech, which is based in Northampton, Mass., and is a subsidiary of Smiths Interconnect, said that the modules were designed to test radar components, like switches and filters, which must be tested over a wide frequency range. The receiver part of the module can also double as a downconverter for extending the range of spectrum analyzers.

The modules represent one of the latest attempts to make regular test equipment compatible with millimeter frequencies, which are challenging to generate and often require multiple devices. Another effort came from National Instruments, which in February 2016 revealed a radio platform to better understand the behavior



Millitech wireless modules link to existing testers using standard connectors, saving engineers money that would otherwise be spent on custom test setups.

and capabilities of millimeter waves, which have already been opened for communications.

In July, the Federal Communications Commission ruled to open new bands of unlicensed spectrum between 64 and 71 GHz. Many companies have already started pilots of next-generation wireless gear. Intel is testing millimeter-wave equipment at its headquarters in Austin, Texas. The company is trying out the 15- and 28-GHz bands, which like all millimeter waves, have trouble traveling far and penetrating obstacles. ■

TELEDYNE ACQUIRES e2v Technologies in \$789 Million Deal

TELEDYNE TECHNOLOGIES RECENTLY SIGNED a deal to acquire e2v Technologies, a maker of radio-frequency parts and machine-vision systems, for \$789 million. Teledyne said that e2v's technology would mesh with the mixed-signal and imaging products it sells to aerospace and defense firms.

The deal is the latest evidence of Teledyne's sensitive trigger finger for acquiring new technologies and the engineers behind them to enhance growth. Teledyne, which acts like a holding company for around 70 different divisions, has focused in recently years on systems engineering, machine vision, and instrumentation in aerospace, defense, healthcare, and other markets.

e2v Technologies, which is based in Chelmsford, UK, is known for making image sensors and power components for radio-frequency applications in healthcare, factories, and wireless communications. It offers microprocessors and other chips for commercial airplanes, as well as assembly and packaging services for semiconductors. It also builds satellite parts hardened against dangerous radiation.

In September 2016, e2v released a new phase-locked loop (PLL) that can be used in satellite control systems. The PLL is based on novel silicon-on-insulator technology. In December, it claimed to have built the first digital-to-analog converter that can generate K-band signals, which are harnessed for radar and satellite communications, without a mixer.


Teledyne said that these types of parts complement its microwave electronics and assemblies. "While we both provide microwave devices, e2v's largest product and market are magnetrons for cancer radiotherapy," said Robert Mehrabian, Teledyne's chief executive, in a statement. "Teledyne supplies solid-state and vacuum microwave systems, but no magnetrons, and we primarily serve defense markets such as electronic warfare, radar, and communications."

e2v has also built radio systems for specific customers like law-enforcement agencies. In 2013, the company disclosed that it was working on a system that projects radio pulses to remotely shut down the electronics in motorcycle and car engines. It creates a similar effect to an electromagnetic pulse at a distance up to 50 meters.

Neil Johnson, e2v's chairman, said in a statement that the company would benefit from "being part of a larger, complementary group with enhanced scale and a wider range of capabilities to service its key customers and management." e2v's board of directors, he said, had approved the deal.

With previous deals, Teledyne has acted like a holding company, forming subsidiaries like Teledyne LeCroy, a maker of electronic test equipment, to operate independently. Neither company said whether e2v, which employs around 1,700, would become a subsidiary or be absorbed by other Teledyne units, like its Microwave or Micro-electronic Technologies divisions. Over the last year, e2v had sales of around \$340 million and netted about \$60 million in profit.

The deal is expected to be completed in the first half of 2017. ■



Teledyne said that e2v's technology would mesh with the mixed-signal and imaging products it sells to aerospace and defense firms.

(Image courtesy of NASA Goddard Space Flight Center, Creative Commons)

UP TO 100 Watt AMPLIFIERS

NOW! 100 kHz to 26.5 GHz



\$995
from ea. qty. (1-9)

High-powered performance across wide frequency ranges.

Mini-Circuits' class A/AB linear amplifiers have set a standard for wideband high-power performance throughout the RF and microwave industry. Rugged and reliable, they feature over-voltage and over-temperature protections and can withstand opens and shorts at the output! Available with or without heat sinks, they're perfect for demanding test lab environments and for integrating directly into customer assemblies. With standard models covering frequencies from 100 kHz up to 26.5 GHz, chances are we have a solution for your needs in stock. Place your order on minicircuits.com today for delivery as soon as tomorrow! Need a custom model? Give us a call and talk to our engineers about your special requirements!

Model	Frequency (MHz)	Gain (dB)	Pout @ Comp.		S Price* (Qty. 1-9)
			1 dB (W)	3 dB (W)	
ZVM-273HP+	13000-26500	14.5	0.5	0.5	2195
ZVE-3W-83+	2000-8000	35	2	3	1295
ZVE-3W-183+	5900-18000	35	2	3	1295
ZHL-4W-422+	500-4200	25	3	4	1160
ZHL-5W-422+	500-4200	25	3	5	1670
ZHL-5W-2G+	800-2000	45	5	5	995
ZHL-10W-2G+	800-2000	43	10	12	1295
• ZHL-16W-43+	1800-4000	45	12	16	1595
• ZHL-20W-13+	20-1000	50	13	20	1395
• ZHL-20W-13SW+	20-1000	50	13	20	1445
LZY-22+	0.1-200	43	16	30	1495
ZHL-30W-262+	2300-2550	50	20	32	1995
ZHL-30W-252+	700-2500	50	25	40	2995
LZY-2+	500-1000	47	32	38	2195
LZY-1+	20-512	42	50	50	1995
• ZHL-50W-52+	50-500	50	63	63	1395
• ZHL-100W-52+	50-500	50	63	79	1995
• ZHL-100W-GAN+	20-500	42	79	100	2395
NEW! ZHL-100W-272+	700-2700	48	79	100	7995
ZHL-100W-13+	800-1000	50	79	100	2195
ZHL-100W-352+	3000-3500	50	100	100	3595
ZHL-100W-43+	3500-4000	50	100	100	3595

Listed performance data typical, see minicircuits.com for more details.

• Protected under U.S. Patent 7,348,854

*Price Includes Heatsink



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

Broadest Selection of In-Stock RF Switches



PIN Diode




Waveguide



USB Controlled



Electromechanical



Surface Mount

- Coaxial, Waveguide and Surface Mount options available
- SPST thru SP12T and Transfer configurations
- Frequencies from 10 MHz to 110 GHz
- All in-stock and ship same-day



Fairview Microwave
RF COMPONENTS ON DEMAND. *Done!*

News

COMPOUND SEMICONDUCTOR Maker II-VI Expands Factory

II-VI INC. is expanding a factory for compound semiconductors used in displays, laser sensors, and radio-frequency devices. The company, based in Saxonburg, Pa., expects four times the number of chips will leave the new plant by 2020.

The factory under renovation is located in Champaign, Ill., and is operated by EpiWorks, a chip-maker that II-VI purchased for an undisclosed sum in February 2016. EpiWorks is known for manufacturing epitaxial chips out of extremely thin layers of semiconductors like indium phosphide and gallium arsenide. Both are critical building blocks for optical as well as wireless chips.


Before it acquired EpiWorks, II-VI built other semiconductors in the arcane field of electrical materials, including silicon carbide and zinc sulfide. Vincent Mattera, II-VI's CEO since September, has followed his predecessor Francis Kramer in laying ambitious plans for new technology.

The company is building clean rooms in Illinois for new manufacturing tools, but also a special laboratory for testing wafers. And renovating a chip factory is not to be taken lightly. The facility must be designed to be extremely clean, free of even a single speck of dust that can corrupt a chip's circuits.

After the EpiWorks deal closed, the company ordered three new specialized semiconductor machines that filled the available space in the Illinois plant, according to Quesnell Hartmann, one of the co-founders of EpiWorks, in a recent statement. "These systems have already been installed and we have now moved into the next phase of growth," he added.

The renovations are scheduled to be finished in mid-2017. In the meantime, II-VI is hiring engineers and plant manag-

ers to help run the bigger facility. The new hires will oversee the production of devices based on indium phosphide (InP) and gallium arsenide (GaAs). The products will include optoelectronic parts for data centers, semiconductor lasers, and specialized chips for 5G wireless infrastructure.




Before acquiring EpiWorks, II-VI built other semiconductors in the arcane field of electrical materials, including silicon carbide and zinc sulfide. (Image courtesy of UCL Engineering, Creative Commons)

While most chipmakers contract foundries to manufacture chip designs, II-VI has expanded its manufacturing operations in recent years. Before it signed the deal with EpiWorks, it also bought Anadigics, a maker of compound semiconductors for wireless chips, for \$78.2 million. The deal ended a surprise bidding war between an unidentified Chinese firm and GaAs Labs, the holding company for Macom.

II-VI disclosed in a recent government filing that it had sold some of Anadigics' radio-frequency technology for around \$45 million. But the company kept Anadigics' manufacturing plant in New Jersey, which had produced GaAs wafers measuring six inches. II-VI plans to build optical components known as vertical-cavity surface-emitting lasers with the old equipment. ■

The Right RF Parts. Right Away.



We're RF On Demand, with over one million RF and microwave components in stock and ready to ship. You can count on us to stock the RF parts you need and reliably ship them when you need them. Add Fairview Microwave to your team and consider it done.

fairviewmicrowave.com
1.800.715.4396

Fairview Microwave
RF COMPONENTS ON DEMAND. *Done!*

QUANTENNA FOLLOWS UP with Second 802.11ax Chip

BACK IN OCTOBER, Quantenna revealed the first known chip to support an embryonic form of Wi-Fi, which will not be released until around 2019. At the Consumer Electronics Show (CES) in Las Vegas earlier this month, the company previewed its second chip based on the standard, called 802.11ax.

The new chip, QSR5G-AX, supports an early draft of the stan-

dard, which technology analysts and industry executives have painted as a significant upgrade to the latest 802.11ac version of Wi-Fi. It will not increase download speeds explicitly, but instead will improve how Wi-Fi networks share the available airwaves to reduce traffic.

The Wi-Fi Alliance has said that 802.11ax will coordinate multiple antennas to send multiple streams of data to devices. Each stream

is split again with orthogonal frequency-division multiple access, or OFDMA, a variation on the technology used in modern cellular networks, creating a bigger pipeline for data. In contrast, earlier forms of Wi-Fi created multiple streams but assigned only one to each device.

The new standard aims to provide better coverage in places bursting with mobile devices and connected sensors, like apartment buildings and offices. Wi-Fi networks in your neighbor's apartment or the office below yours can cause interference. It will also provide download speeds to over 10 Gb/s.

"802.11ax is the future of Wi-Fi," said Sam Heidari, Quantenna's CEO, in a statement. The company has jumped out ahead of major rivals like Broadcom, which last year completed its \$37 billion merger with Avago to form Broadcom Incorporated. And that has given Quantenna clout with investors, who gave it around \$160 million in funding before it went public late last year.

The QSR5G-AX supports eight total streams for routers and set-top boxes. Four of the streams occupy the 5-GHz band and four are in the 2.4-GHz band. The 5-GHz spectrum holds more room for wireless traffic than 2.4-GHz, which is at varying degrees by earlier standards.

The new chip is a slightly lighter version than the first 802.11ax chip released by Quantenna in October, the QSR10G-AX, which supports 12 streams of data. That device is a drop-in replacement for older chips based on the company's 802.11ac chip architecture.

Both chips will be compatible with 802.11ax devices, like smartphones or computers, said the company. They will also be compatible with existing standards, like 802.11ac and 802.11n. Quantenna plans to begin sampling both the QSR10G-AX and QSR5G-AX chips in early 2017. It did not say when either chip would enter production. ■

FASTER, QUIETER, SMALLER SIGNAL SOURCES QUICKSYN SYNTHESIZERS

Design smaller and more efficiently with National Instruments QuickSyn synthesizers. The revolutionary phase-refining technology used in QuickSyn synthesizers enables blazing fast switching speeds, very low spurious and phase noise performance, wide frequency range, and small footprint.

ni-microwavecomponents.com/quicksyn



QuickSyn Lite Synthesizer



© 2016 National Instruments. All rights reserved.

the accuracy of *Rubidium*...

PRS10 Rubidium Oscillator (10 MHz)

- Less than 5×10^{-11} aging per month
- Ultra low phase noise (-130 dBc/Hz @ 10 Hz)
- 20 year lamp life
- 1 pps input and output
- RS-232 computer interface

\$1495 (U.S. list)



FS725 Benchtop Rubidium Frequency Standard

- 5 MHz and 10 MHz outputs
- 0.005 ppm aging over 20 years
- Built-in distribution amplifier (up to 22 outputs)
- 1 pps input and output
- RS-232 computer interface

\$2695 (U.S. list)

SRS rubidium frequency standards have excellent aging characteristics, extremely low phase noise and outstanding reliability.

The PRS10 component rubidium oscillator is designed for easy system integration. It has a 1 pps input for phase-locking to an external reference (like GPS) and provides 72 hour Stratum 1 level holdover.

The FS725 benchtop instrument is ideal for the metrology laboratory as well as the R&D facility – anywhere precision frequency is required. It generates 5 MHz and 10 MHz signals and has a built-in distribution amplifier with up to 22 outputs.



Stanford Research Systems

1290-D Reamwood Ave. Sunnyvale, CA 94089 · email: info@thinkSRS.com
Phone (408) 744-9040 · Fax (408) 744-9049 · www.thinkSRS.com

BOOSTING POWER WITH SILICON CMOS

SILICON CMOS SEMICONDUCTOR technology has been the basis for a wide range of analog, digital, and mixed-signal semiconductor devices. Traditionally, though, it does not fare well in high-frequency amplification applications. A different semiconductor technology, such as gallium arsenide (GaAs), is typically recruited to raise the amplitude of high-frequency signals.

In hopes of gaining more power at higher frequencies from Si CMOS, Jie Cui from the School of Electrical and Optical Engineering, Nanjing University of Science and Technology (Nanjing, China) and Purdue University (West Lafayette, Ind.), working with Sultan Helmi, Yingheng Tang, and Saeed Mohammadi from Purdue Univ., reviewed a great deal of the work already performed on increasing the operating frequencies of Si CMOS processes. In concert, they stacked on-chip transistors in different configurations to achieve higher levels of output power.

The team reviewed the performance levels of a number of different stacked CMOS PAs, operating from RF through millimeter-wave frequencies, including a number of PAs developed at Purdue. As with other researchers, they discovered that various limitations in Si CMOS must first be overcome for higher performance. For example, output power is limited by the low breakdown voltages of CMOS. In addition, limitations in frequency, efficiency, and bandwidth are caused by the parasitic elements of active and passive components in CMOS technology, including on-chip passive components with high loss (e.g., inductors, transformers, and transmission lines).

Some of the parasitic limitations can be overcome by using a substrate material with high thermal conductivity, such as aluminum nitride (AlN), in place of the standard Si-based substrates. In addition, the use of an enhanced silicon-on-sapphire (SOS) CMOS process can also minimize parasitic elements when fabricating PA circuitry for improved higher-frequency performance.

Employing an innovative interconnection scheme, the three transistors of a triple-cascode cell were fabricated and stacked using a combined layout cell with low parasitic elements. The researchers were able to achieve power outputs at frequencies approaching the performance levels of commercial GaAs PAs.

One of the designs features a stacked transistor configuration and switchable input matching network for optimizing wideband performance by dividing the total bandwidth into two portions. When the input matching switch is in the “on” state, the PA covers a bandwidth of 1.8 to 2.4 GHz; when the switch is in the “off” state, the PA operates across a bandwidth of 2.4 to 3.4 GHz. This particular design provides 6-dB gain with better than +13 dBm output power at 1-dB compression (P1dB) with better than 13% peak power-added efficiency (PAE). Fabricated with a 0.25- μ m SOS CMOS process, it is a good example of the higher-frequency PA performance achievable with Si CMOS.

See “Stacking the Deck for Efficiency,” *IEEE Microwave Magazine*, Vol. 17, No. 12, December 2016, p. 55.

REGISTERING HIGH RFID ISOLATION

RADIO-FREQUENCY-IDENTIFICATION (RFID) TECHNOLOGY

continues to spread as a reliable means of wireless security for many systems. These include readers that transmit signals to remotely power transceivers without batteries, which return signals to the reader at the same frequency. Effective operation requires adequate isolation between the two signals and the transmit and receive paths, which is typically achieved by two separate bistatic antennas or a single, switchable monostatic antenna.


Because both approaches can suffer from leakage of transmit power into the RFID reader, researchers Alirio Boaventura, Joao Santos, Arnaldo Oliveira, and Nuno Borges Carvalho of the Instituto de Telecomunicações, Departamento de Eletrônica, Telecomunicações e Informática, Universidade de Aveiro, Portugal, explored various self-jamming cancellation techniques for commercial RFID integrated circuits (ICs), including methods currently used in radar systems.

Such factors as signal reflections; RFID tag movement and resulting modulation from RFID tag antennas; lack of isolation from passive couplers in RFID antenna connections; and interference from nearby radio systems can result in jamming of RFID systems. Without sufficient isolation, power from these different sources can leak into the RFID receiver section and cause an overload of the receiver front end.

One proven method for cancelling self-jamming signals is to use a sample of the self-jamming signal to create an out-of-phase version of the signal to cancel the interference. This classical approach involves amplitude and phase control to create a reliable self-jamming cancellation signal, leaving only the RFID information signal.

Through experimentation using baseband approaches, the researchers developed several approaches suitable for passive RFID designs based on algorithms that form lowpass filters (LPFs) and highpass filters (HPFs) for the removal of self-jamming interference in RFID systems. The approaches are meant to extend the range of passive RFID systems and, as the researchers explain, have already been adopted in a number of commercial RFID ICs. The techniques have proved effective in minimizing self-jamming effects for RFID systems even under transient operating conditions.

See “Perfect Isolation,” *IEEE Microwave Magazine*, Vol. 17, No. 11, November 2016, p. 20.



TINY Wideband Transformers & Baluns!

NOW!
4 kHz - 18 GHz From **99¢** ea. (qty. 20)

To support an even wider range of applications, Mini-Circuits tiny surface-mount transformers and baluns now cover frequencies from 4 kHz up to 18 GHz! Our latest designs achieve consistent performance across very wide frequency bands, and our baluns have demonstrated great utility for use with chipsets. With over 250 trusted models in stock representing a wide selection of circuit topologies and impedance ratios, chances are, we have a solution for your needs!

Our Low Temperature Co-Fired Ceramic (LTCC) models provide reliable performance in tough operating conditions, tiny size – as small as 0805 – and very low cost. All core-and-wire models are available with our exclusive Top Hat® feature, improving pick-and-place accuracy and throughput. We even manufacture our own transmission wire under rigorous control and use all-welded connections to ensure reliability and repeatability you can count on.

Visit minicircuits.com and use **Yoni2®**, our patented search engine to search our entire model database by performance criteria and find the models that meet your requirements. Order today and have them in hand as soon as tomorrow! Cost-effective custom designs and simulations with fast turnarounds are just a phone call away!




TC
0.15" x 0.15"



NC
0.08 x 0.05"
Ceramic



NCR2
0.08 x 0.10"
Ceramic

 **RoHS compliant.**



Directional / Bi-Directional COUPLERS



5 kHz to 18 GHz up to 250W from **95¢** ea. (qty. 1000)

Now! 475,326 Looking for couplers or power taps? Mini-Circuits has 326 models in stock, and we're adding even more! Our versatile, low-cost solutions include surface-mount models down to 1 MHz, and highly evolved LTCC designs as small as 0.12 x 0.06", with minimal insertion loss and high directivity. Other SMT models are designed for up to 100W RF power, and selected core-and-wire models feature our exclusive Top Hat™ for faster, more accurate pick-and-place.

At the other end of the scale, our new connectorized air-line couplers can handle up to 250W RF input power, with low insertion loss and exceptional coupling flatness! All of our couplers are RoHS compliant. So if you need a 50 or 75Ω, directional or bi-directional, DC pass or DC block coupler, for military, industrial, or commercial applications, you can probably find it at minicircuits.com, and have it shipped today!



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

SUPER ULTRA WIDEBAND AMPLIFIERS


up to +27 dBm output... **0.1 to 21 GHz**

Ultra wide coverage and super flat gain make our ZVA family ideal for ECM, instrumentation, and test systems. With output power up to 0.5 Watts, they're simply some of the most usable amplifiers you'll find, for a wide range of applications and architectures!

All of our ZVA models are unconditionally stable, ruggedly constructed, and able to withstand open or short circuits at full output. For more details, from data sheets to environmental ratings, pricing, and real-time availability, just go to minicircuits.com!

All models IN STOCK!

 RoHS compliant




from **\$845** ea.

Electrical Specifications (-55 to +85°C base plate temperature)

Model	Frequency (GHz)	Gain (dB)	P1dB (dBm)	IP3 (dBm)	NF (dB)	Price \$ * (Qty. 1-9)
ZVA-183WX+	0.1-18	28±2	27	35	3.0	1345.00
ZVA-183X+	0.7-18	26±1	24	33	3.0	935.00
ZVA-213X+	0.8-21	26±2	24	33	3.0	945.00

* Heat sink must be provided to limit base plate temperature. To order with heat sink, remove "X" from model number and add \$50 to price.

Wideband Performance



 **Mini-Circuits®**

Inside TRACK

with
James Kimery,

for RF Communications and Software-Defined Radio (SDR), National Instruments

Interview by CHRIS DeMARTINO, Technology Editor

JAMES KIMERY is the director of marketing for RF, communications, and software-defined radio (SDR) initiatives at National Instruments (NI). He is responsible for the company's communication system design and SDR strategies. Kimery also manages NI's advanced research RF/Communications Lead User program.

5G is obviously receiving lots of attention. In your own words, can you tell us why we need 5G?

There are several reasons, but I believe that there are two primary drivers. First, we all know and have experienced the transformational impact of the smartphone. Our mobile smart devices have become an indispensable part of our lives and drive our collective demand for mobile broadband data, resulting in an exponential increase in broadband data. Unfortunately, industry analysts predict the growing demand for mobile data will outstrip capacity in the not-so-distant future. To keep up with rising demand, new capacity is needed. That's where 5G comes in—5G promises significant increases in data rates as well as capacity.

Second, the concept of a network encompassing increased capacity, increased bandwidth, and perhaps even lower latency will inevitably give rise to a wealth of new applications and services that could transform our lives, once again spawning new businesses and unlocking enormous economic potential. Service operators are motivated to move 5G forward to increase revenue by offering new



services for businesses and consumers beyond broadband data and voice, igniting an ecosystem of suppliers primed to deliver solutions that capitalize on these new capabilities.

To conclude, there are two primary drivers for 5G—one based on our need for faster data and more capacity than our current 4G networks, and the other rooted in the

nascent wireless broadband movement but augmented by new 5G capabilities. The 5G network will enable entrepreneurs to create applications, services, and solutions that take full advantage of the network's new functionality and hopefully create tremendous business opportunities.

Millimeter-wave frequencies are clearly tied to 5G. Where do you see that going?

On July 14, 2016, the FCC moved forward with reclassifying the following spectrum bands as mixed-use, including mobile access: 28-GHz (27.5 to 28.35 GHz), 37-GHz (37 to 38.6 GHz), and 39-GHz (38.6 to 40 GHz) bands, and a new unlicensed band at 64 to 71 GHz. In total, the FCC essentially allocated almost 14 GHz of licensed and unlicensed spectrum for 5G. As such, the United States became the first country in the world to designate spectrum for 5G operation and more aggressively designated specific centimeter- and millimeter-wave spectrum as potential spectrum targets.

Although these centimeter- and millimeter-wave frequencies have been designated for 5G by the U.S., global harmonization is a challenge. The WRC—the ITU group responsible for global spectrum harmonization—noted in 2015 that the 28-GHz band cannot be allocated globally, meaning the U.S. and other countries that have available spectrum around 28 GHz may likely join together to move asynchronously forward. Without global agreement on spectrum for 5G, worldwide acceptance and adoption of 5G technologies may be challenged.

In addition, the smartphone industry today enjoys tremendous benefits from economies of scale with the harmonization of the standard and spectrum bands regionally (and also technology with few vendors dominating the global market). 5G will need this type of harmonization to maximize the impact.

Furthermore, Verizon announced a “5G Specification” and plans for fixed wireless deployment intended for “last mile access” to residential homes. Although not technically 5G, Verizon has seen the opportunity and vision to move forward with millimeter-wave technologies to address a near-term opportunity. And this move could potentially pave the way for a broader 5G millimeter-wave deployment for mobile access.

When we met at NIWeek, you mentioned how you think 5G's modulation scheme may simply be orthogonal frequency-division multiplexing (OFDM). Do you still feel that's the case?

Yes. In fact, since NIWeek, the 3GPP has kicked off several study items related to Release 15, otherwise known as the 5G release. Because the 3GPP is a consensus-building organization, OFDM seems to be the strongest candidate

for Phase 1 5G standardization. Although competing waveforms are technically still alive and viable, OFDM seems to have the broadest support—and in a consensus organization, popularity matters. Other flavors of filtered OFDM are still being considered, but the path for inclusion is not quite as straightforward or clear.

Massive multiple-input, multiple-output (MIMO) technology is something that is linked to 5G. Can you tell us a little about it?

Unlike 3G or 4G systems, massive MIMO employs hundreds of antennas at the base station to exploit the numerous degrees of freedom that these many antennas can deliver. Lund University and the University of Bristol were able to demonstrate last spring the vast potential of massive MIMO by prototyping a 128-antenna system with 22 UEs. These researchers achieved a spectrum efficiency of over 145 b/s/Hz, which is over 15× the current LTE systems. Spectrum below 6 GHz is scarce, and by using massive MIMO rather than conventional LTE, networks could increase capacity by over 15× using relatively low-cost technology.

The 3GPP is still considering massive MIMO for inclusion in Release 15, and many aspects to massive MIMO must be worked out at a system level. However, there seems to be genuine interest and motivation to work through these issues and build consensus before June 2018, which is the current scheduled date for finalization of Phase 1 of 5G.

What challenges are associated with 5G testing?

5G offers tremendous potential benefits over our current networks, and in the end, new technologies are needed to realize these systems. In order for millimeter-wave systems to be viable, it is almost certain that high-gain, phased-array antennas will be needed at the base station and at the UE to overcome the path loss at these frequencies.

These antenna beams are highly directional at such frequencies and may be packaged with the silicon, producing a module that includes the transceivers, low-noise amplifiers (LNAs), power amplifiers (PAs), and the antenna. With this type of packaging, instrument access with a cable is not possible and the specter of over-the-air testing of these modules must be considered. Over-the-air testing introduces many variables not encountered with cabled testing, and this is a research area for test-and-measurement companies.

Massive MIMO also presents challenges in that massive-MIMO base stations feature hundreds of transceiver chains and MIMO processing, and these systems differ dramatically from current 4G implementations. With massive MIMO, each individual transceiver chain can be tested

individually, but a test capable of testing all transceiver chains in aggregate is surely needed to obtain error-vector-magnitude (EVM) measurements—a common method to assess the performance characteristics of a transceiver. Testing one receiver or one transmit path is not sufficient to measure EVM of the system.

To address the massive-MIMO test challenge, one could envision a signal generator with 128 or more outputs and a vector signal analyzer (VSA) with the same number. Cost-effectively delivering this type of instrument requires test-and-measurement companies to be creative.

What developments do you think will occur in 2017 that will bring 5G closer to reality?

Two really important events will happen in 2017. The work items for 3GPP Release 15 are expected to be set in March. So by March of 2017, we should have a good picture of the 5G Phase 1 specification, although there will be several months of work ahead for the 3GPP membership.

Second, I mentioned earlier the Verizon 5G specification. I believe there will be a big focus on what Verizon does in the 28-GHz band. Although Verizon may not deploy mo-

bile access equipment, and perhaps the specification may be short of a comprehensive 5G mobile access network, the Verizon work will be the first commercial widespread deployment of centimeter-/millimeter-wave technology in the world. In some ways, the Verizon progress may be an early indicator of the success of 5G mobile access networks. In other words, if Verizon is successful with their field trials and deployments, this will bode well for future 5G millimeter-wave deployments.

Lastly, when do you expect to see the first 5G deployments?

The Korean government is pushing very hard to have 5G trial deployments in time for the 2018 Winter Olympics in Pyeoungchang, and these deployments are widely expected to be at 28 GHz. Given the timing of the specification finalization—June 2018—it is unclear whether these trial deployments will be standard-compliant. However, if both Verizon and the Korean operators such as Korea Telecom and South Korea Telecom are successful with their initial millimeter-wave deployment goals, then we may all see and experience 5G much sooner than 2020. **mw**

AUTOMATED RF TEST SYSTEMS

from

JFW

**Attenuator Assemblies
Transceiver Testing
RF Switch Assemblies
RF Matrix Switches
Handover Test Systems**



JFW Industries, Inc.

317-887-1340

877-887-4539


www.jfwindustries.com

sales@jfwindustries.com



HIGH PERFORMANCE PASSIVE FREQUENCY DOUBLERS

Up to
**15.0
GHz**



Features

- | Low Conversion Loss
- | Good Harmonic & Sub-Harmonic Rejection
- | Small Size

Talk To Us About Your Custom Requirements.




Phone: (973) 881-8800 | Fax: (973) 881-8361

E-mail: sales@synergymw.com

Web: WWW.SYNERGYMWAVE.COM

Mail: 201 McLean Boulevard, Paterson, NJ 07504

***All Available for
Same-Day Shipping***



RF Solutions From RF Engineers

866.727.8376
visit pasternack.com today!



5 Technology Areas to Watch in 2017

This year, expect to see the RF/microwave industry produce solutions that push technological boundaries to meet new and emerging requirements.

When forecasting what 2017 has in store for the RF/microwave landscape, it led to one concrete conclusion: The industry is primed to continue delivering its share of innovative technology solutions. Both commercial and military applications demand cutting-edge devices, components, and systems as well as the latest design software and test-and-measurement equipment. And with companies focused on making 5G a reality, the industry shows no signs of slowing down.

Speaking with those throughout the industry revealed a number of predictions for 2017. For one, size, weight, and power (SWaP) constraints will be ever-more stringent for aerospace and defense systems. Radar applications will take advantage of emerging technology to offer performance that surpasses the capabilities of older systems. Of course, gallium-nitride (GaN) technology will play a key role in all of these developments.

Moreover, mobile communication demands will lead to challenging filter requirements. Proper antenna solutions are needed, too, as more people drop cable service. In addition, providers of design software tools and test-and-measurement equipment must deliver solutions to satisfy rapidly changing needs.

With these prognostications setting the stage, here are five industry sectors to keep a close eye on this year:

1. SEMICONDUCTOR TECHNOLOGY


By now, GaN technology's huge impact on RF/microwave technology should be apparent to all in the industry. In 2017, we can surely expect


to see GaN in heavy doses. One well-documented benefit of GaN lies in the realization of smaller form factors, making it vital when it comes to meeting today's SWaP requirements.

"In 2017, we expect to see a continued push toward more stringent SWaP requirements for upgraded and next-generation aerospace and defense systems—particularly for radar applications," says Kevin Harrington, director of strategic marketing, discrete products group, Microsemi (www.microsemi.com). "New power lineups based on GaN-on-silicon carbide (GaN-on-SiC) provide higher power-added efficiencies (PAEs) and smaller form factors that were not possible in older radar systems. Combining GaN-on-SiC with continued advances in thermal design packages and smart chip design for peak RF and thermal performance will help continue to push the limits of SWaP requirements.

"Monolithic microwave integrated circuits (MMICs) will continue to have a critical role in advanced electronic-warfare (EW) solutions," continues Harrington. "Mixed technology, gallium arsenide (GaAs), GaN, and silicon germanium (SiGe) each offer critical performance advantages. GaN MMICs have pushed higher power capability over wide bandwidths, while GaAs MMICs maintain higher linearity and low noise figure at lower power levels. Added functionality to standard building blocks will help system-level designers optimize the various lineups needed in EW and electronic-countermeasure (ECM) systems."

Harrington believes there will be an ongoing move to more integrated solutions. He notes, "Higher levels of integration will also be a continued trend in 2017. This will happen either through multi-chip modules (MCMs) for higher power applications using GaN, GaAs, and silicon-diode technologies, or through SiGe BiCMOS for lower power, highly integrated RF integrated circuits (RFICs). This trend is seen in many market applications, including military communications, smart munitions, avionics, and radios."





2. FILTER REQUIREMENTS

Intensifying demands of mobile communications have created a need for more advanced RF filter solutions. Firms such as Qorvo (www.qorvo.com) and Broadcom (www.broadcom.com) represent two of the major players in this space.

However, newer companies like Resonant (www.resonant.com) and Akoustis (www.akoustis.com) are now making their presence felt, too.

“For 2017, band proliferation, higher data rates, and minimizing the number of smartphone models continue to drive the growth and complexity of filters,” says Mike Eddy, vice president of marketing at Resonant. “Hence, the expectation is that the number of filters sold will increase to more than 45 billion in 2017, according to [market research firm] Navian.”

Eddy adds, “These are the trends for filters in mobile devices, which are the largest filter market:

- **Increasing number of filters per device:** More RF paths within the device from multiple antennas and spectrum proliferation will continue to grow and require more filters. Thus, filter size and cost must continue to decrease.
- **Increasing integration:** RF front-end performance is

crucial. Maximizing power-amplifier (PA) efficiency on the uplink and receiver sensitivity on the downlink will require optimization of the entire RF chain. As complexity increases, understanding the RF chain and any interactions between elements becomes crucial. For filters, optimizing the interface to the PA and the low-noise amplifier (LNA) will be required in the filter design process.

- **Complex multiplexing:** Carrier aggregation (CA) for higher data rates will drive more complex multiplexing, which in turn drives more complex filters.
- **More demanding specifications:** Isolation, loss, and power-handling requirements continue to create new challenges. Filters in the RF chain are a major contributor to loss, which is critical for total transmit (Tx) efficiency (and ultimately for the PA current draw and for battery life) as well as the total noise figure in the receive (Rx) path (and ultimately for the signal-to-noise ratio and the data rate).”

3. ANTENNA SOLUTIONS

Another key technology area that bears watching in 2017 is the antenna. Interestingly enough, the large number of people who are dropping cable service, or “cord-cutting,” has




led to greater demands for

adequate antenna performance, according to one company. Jeff Shamblin, chief scientist at Ethertronics (www.ethertronics.com), explains, “Adoption of video streaming is accelerating and the move is on to cancel cable subscriptions. The main drawback is that the local TV channels provided as part of a cable subscription are no longer available to the consumer. In 2017, we can expect around 24 million non-paying TV households.”

Shamblin is quick to point out how dropped cable service requires proper antenna technology. He explains, “The relevant problem to solve for cord-cutting systems is antenna selection and placement. A lot of neighborhoods with single-family homes have restrictions on placement of TV antennas outdoors. Additionally, for consumers living in apartments and condos, there are restrictions on roof access that add to the antenna siting task. The popular approach is to use a small antenna

THE IDEAL SYNTHESIZER FAMILY FOR ANY APPLICATION

- Benchtop / Handheld / Modular Platforms
- Lowest Phase Noise
- USB, SPI, LAN programmable, SCPI compliant, COM Interface
- <10 Watt Power Consumption
- <100 Microseconds switching speed
- Programming transferrable between models



pronghorn-solutions.com | +1 (720) 808-9832 | sales@prong-hornsolutions.com

indoors to connect to the TV tuner to access over-the-air (OTA) signals.

"This current approach of placing a passive antenna at a location in a room in a home provides you the ability to sample the signal at that one location," he notes. "Since this is an indoor environment, there will be reflected signals bouncing around the room. The antenna will in reality be picking up multiple signals and coupling them into the OTA receiver. The shape of the radiation pattern and polarization of the passive antenna is fixed, i.e., one radiation pattern only per channel and a fixed polarization state of the antenna. This fixed radiation pattern will not be optimized for reception of the multiple reflected signals in the room across all of the TV channels."

According to Shamblin, utilizing an LNA in these scenarios is not the proper solution: "Attempting to improve a passive antenna by adding an LNA typically fails since the LNA will amplify noise along with the TV signal received by the antenna. As a result, the signal-to-noise ratio (SNR) is slightly lower than it is without the amplifier since the LNA has losses. LNAs are recommended when using an outdoor antenna and a long cable run, with the LNA providing the capability of boosting the signal at the antenna prior to the losses associated with the long coaxial cable leading to the TV."

Ethertronics has developed technology that can help overcome those problems. "Our Active Steering technology provides the capability of generating four or more radiation patterns from a single antenna and to dynamically change the polarization state. This dynamic 'radiation mode' capability, when coupled to an Ethertronics-supplied algorithm, allows for these multiple radiation patterns and polarization states to be sampled. The technology allows for the optimal radiation mode to be selected for use when acquiring an OTA channel for viewing. This will result in receiving a stronger TV signal in-home from an Active Steering antenna when compared to a passive antenna of equivalent size."

4. DESIGN TOOLS

Soon, 5G may transform the way that products are designed and built, with simulation software playing a key role. "In 2017, emerging 5G technologies and the increasing power of low-cost software-defined radios (SDRs) will





KRYTAR®

Microwave Components & Instruments
DC to 67 GHz



Directional Couplers
to 67 GHz



3 dB 90° Hybrid Couplers
to 40 GHz



Directional Detectors
to 50 GHz



Double Arrow 3 dB 180° Hybrid Couplers
to 26.5 GHz



Detectors
Zero Bias
Schottky
Planar Doped
Barrier Planar
Tunnel Diode
Threshold Detectors
to 40 GHz



**MLDD Power Divider/
Combiner** to 45 GHz



**RF & Microwave
Power Meter**
100 KHz to 40 GHz



Adapters: DC to 67 GHz
In Series: SMA, 2.92 mm, 2.4 mm
Between Series: 2.29 mm to 2.4 mm



**Coaxial
Terminations**
to 67 GHz



Broadband Limiters
Pin-Pin Diode
Pin-Schottky Diode to 18 GHz

MIL Qualified Components Available

 **KRYTAR®** 1288 Anvilwood Ave. Sunnyvale, CA 94089

Toll Free: (877) 734-5999 • Fax: (408) 734-3017 • sales@krytar.com

www.krytar.com lists complete specifications



change the way that engineers research, design, and build wireless products,” says Ken Karnofsky, senior strategist, signal processing applications, at MathWorks (www.mathworks.com). “These technologies are driving deep integration of RF and digital technologies to implement millimeter-wave radios, massive multiple-input, multiple-output (MIMO) antenna arrays, and flexible multi-function radios for commercial, military, and public safety systems.

“Specifically, radios operating at millimeter-wave frequencies will employ extremely compact MIMO array designs, with the RFIC integrated with the antenna elements,” continues Karnofsky. “Similarly, 5G systems are expected to achieve high throughput at relatively low power by using hybrid beamforming techniques. These techniques partition the processing between RF and digital components to optimize SNR and efficiently focus transmitted signals on a specific location.”

According to Karnofsky, simulation tools that support multiple domains offer a tremendous advantage. “Highly integrated devices require engineers to design across traditional silos of expertise and use domain-specific tools,” he notes. “As a result, 5G and other advanced wireless-technology designers should rely on multi-domain simulation tools. By modeling the antenna, RF, and digital subsystems together, they can quickly explore alternative architectures and algorithms along with measuring the impact of design tradeoffs on system performance.”

Karnofsky also expects to see increased dependence on SDR technology for wireless applications. He elaborates, “We will also see expanded use of SDR technology to meet the need for hardware prototypes and testbeds for a range of wireless applications—including 5G. System designers and research and development engineers see an opportunity to use SDR hardware to speed development of these prototypes. But they often lack the field-programmable gate array (FPGA) or system-on-a-chip (SoC) programming expertise to implement their designs on that hardware.

“They will and should increasingly turn to a model-based design workflow that uses generation of portable HDL and C code from models,” says Karnofsky. “Using this workflow, they can design, prototype, and verify algorithms on a range of commercial SDR hardware and create production-ready IP for implementation on custom hardware.”

5. CHANGING TEST NEEDS

New advances in wireless communications will have a major impact on test-and-measurement requirements. Several different technologies can be considered driving factors. According to Adam Smith,

director of product marketing at LitePoint (www.litepoint.com), “Big changes are coming to wireless. There is an explosion in new wirelessly connected products and new use models will value improvements in range, battery life, latency, and number of connected devices. Three major technologies will play a key role in these new products: IEEE 802.11ax, low-power wide-area networks (LPWANs), and millimeter-wave frequencies.

“IEEE 802.11ax is not simply the next version of Wi-Fi,” explains Smith. “It represents a fundamental change in the way that Wi-Fi operates. ‘Simplistically speaking, Wi-Fi is borrowing from cellular by adopting techniques used in LTE. Unlike LTE, which operates in a managed, licensed spectrum, Wi-Fi operates in the unlicensed spectrum on an ad hoc, on-demand basis. A successful launch of this technology will require products to manage the chaos of the unlicensed spectrum. Verifying that these devices play by the IEEE 802.11ax rules requires smarter test equipment. Equipment needs to be ‘packet aware’ and support near real-time power control. New test methodologies are needed to achieve the required manufacturing economics without sacrificing product quality.”

LitePoint is also offering test solutions to support LPWAN technologies. Smith notes, “LPWAN technologies, such as Sigfox, LoRa, and LTE Cat-NB1, seek to meet the emerging requirements for the Industrial Internet of Things (IIoT) market. These technologies address range, battery life, security, and quality-of-service. One challenge device makers will face is getting their products to market quickly with high quality. To make this easier, we provide ‘reference designs’ for test, delivering pre-validated chipset-specific solutions that accelerate product validation.”

The third factor that Smith believes will impact the test-and-measurement arena is millimeter-wave technology. He says, “Millimeter-wave technology represents the next frontier of wireless with nearly 20 GHz of pristine spectrum. The physics of this spectrum drives antenna beamforming technology, which in turn drives new ways of measuring these types of signals. Test equipment needs to be able to address OTA measurements of a variety of antenna arrays, ensuring that these arrays can efficiently ‘steer’ the energy to the end-user.”

Taking all of these potential advances into consideration, 2017 looks to be an eventful year for the RF/microwave industry. As 5G and other new technologies loom on the horizon, companies are focused on delivering the next generation of design and test solutions. Cutting-edge performance in terms of semiconductor technology will likely create headlines this year. And filter and antenna solutions will play key roles across many wireless fields in 2017. Stay tuned to *Microwaves & RF*, as we report on these unfolding developments. **mtw**





CERAMIC FILTERS

The Industry's Widest Selection!

Over 200 Models Comprising Over 7 Million Units in Stock!

from **99¢** qty. 3000

From DC to 15 GHz — Mini-Circuits' LTCC filters give you the industry's widest selection of high pass, band pass, low pass, and diplexer models, supporting a vast range of applications. These tiny ceramic filters utilize Low Temperature Co-fired Ceramic (LTCC) technology to achieve high reliability in extreme environments, superior thermal stability, and excellent repeatability in packages as small as 0.06 x 0.03"! They're even available in quantities as small as 20 pieces in a reel, and designer kits to help you find the right model for your system for low cost.

Visit minicircuits.com today for comprehensive test data, advanced simulation models, PCB layouts, everything you need to make an informed choice. Place your order online and have them in hand as soon as tomorrow!

Free, High-Accuracy Simulation
Models for ADS



www.modelithics.com/mvp/Mini-Circuits.asp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

555 rev org

ARE YOU 5G-READY?

**LET US BE YOUR ONE-STOP SHOP
FOR MMWAVE COMPONENTS & SUBASSEMBLIES.**



 **SAGE**
Millimeter, Inc.

WWW.SAGEMILLIMETER.COM



MADE IN USA

www.sagemillimeter.com | 3043 Kashiwa Street, Torrance, CA 90505
T: 424-757-0168 | F: 424-757-0188 | sales@sagemillimeter.com

... ALSO INTRODUCING THE NEW SAGE STOCKROOM

IN STOCK



WG to Coax Adapters

IN STOCK



Balanced Mixers

IN STOCK



Orthomode Transducers

IN STOCK



Bulkhead Adapters

IN STOCK



Sector Antennas

IN STOCK



Faraday Isolators

IN STOCK



Harmonic Mixers

IN STOCK



Power Dividers

IN STOCK



Horn Antennas

IN STOCK



Magic Tees

IN STOCK



Omni Directional Antennas

IN STOCK



Waveguide Terminations

IN STOCK



Directional Couplers

IN STOCK



Full-Band Attenuators

IN STOCK



Taper Transitions

visit us
online
for more!

WWW.SAGEMILLIMETER.COM/STOCKROOM

Over 250 millimeterwave
components off-the-shelf,
in stock, and ready to ship
guaranteed in only 1-3 days.

 **SAGE**
STOCKROOM

Harvesting Energy from RF Sources

Excess energy from transmitted communications signals can be captured and transformed to dc power, perfect for a wide range of low-power electronic devices.

CONSERVATION OF ENERGY starts by reusing energy that has already been expended. That energy is readily available in electromagnetic (EM) form, from broadcast AM and FM radio waves to the many wireless devices that transmit signals around us, such as cellular base stations and short-distance wireless local-area networks (WLANs). The key to harvesting or scavenging this “used” energy starts with a dedicated receiver capable of receiving the available wireless signals, along with some means of converting the received signal power into a supply of electrical power.


Many leading suppliers of wireless communications products are well aware of the eventual need to conserve battery power as users became more dependent on those devices. The evolution of the cellular telephone into a personal messaging and entertainment center has meant that these portable radios can do more, but it also means that they require more power to do so. If limited to batteries as power sources, the increased current drain from the added functionality will result in less operating time per battery charge (and less billable hours for service providers).

For a while now, developers of mobile communications devices have sought to ease the load on the batteries in those devices via some form of energy recovery system. With the growing popularity of Internet of Things (IoT) and machine-

to-machine (M2M) devices for automated remote control of electronic devices, IoT applications are being envisioned—for homes and factories alike—that could potentially remain powered for years awaiting a trigger. With energy-harvesting capability, such devices can literally pull energy out of the air to recharge their own batteries or harvest enough energy from the environment so that a battery may not even be required for power.

Such devices are now typically referred to as “zero-power” wireless sensors for their capability of providing sensor data directly on a wireless channel or by means of the internet, using a wireless gateway with no apparent source of energy. The “batteryless” approach has been commonly used with radio-frequency-identification (RFID) tags that transmit an identifying signal based on received power from an RFID reader’s transmitted signals (as the source of power).

By harvesting power from available RF energy sources, a new generation of ultra-low-power (ULP) wireless devices, such as IoT sensors, can be developed for low-maintenance applications like remote monitoring. Energy harvesting is considered very much a “companion” technology to wireless communications, since it can enable extended battery lifetime for mobile devices and possibly battery-free operation for some electronic devices.



This is a simplified functional diagram of how RF energy can be harnessed from the environment and converted into dc power for another application. The diagram is based on a patented concept of using a cellular telephone’s surface as an energy-harvesting antenna, thus reusing the electromagnetic (EM) energy from the very same cellular phone. (Courtesy of Radiant micro-tech Corp.)

100W POWER AMPLIFIERS

700-2700 MHz



48 dB Gain, ± 1.7 dB Flatness **\$8,995_{each}**

High power over wide frequency range with unprecedented reliability for a fraction of the cost of competitive products! Mini-Circuits' HPA-272+ high-power rack mount amplifier has been life test qualified for 10,000 hours at 100W output without failure, so you know it's made to last under heavy use in your lab. Extensive built-in safety features include over-temperature protection and the ability to withstand opens and shorts at the output.* It's ideal for a wide variety of high power test applications including EMI, reliability testing, power stress testing, and burn-in of multiple units at once. This model provides 48 dB gain with ± 1.7 dB gain flatness over its entire frequency range and 89 dB reverse isolation. Housed in a rugged, 19-inch rack-mountable chassis, the amplifier operates on a self-contained 110/220V power supply and includes internal cooling, making it easy to use in most lab environments. They're available off the shelf for an outstanding value, so place your order on minicircuits.com today for delivery as soon as tomorrow!

*at 3 dB compression point.



The basic concept for harvesting energy from an RF source typically involves an extra antenna to receive the desired wireless signals via a wireless product's primary receiver.

CREATING ENERGY

Energy can be harvested from a number of different sources, including light, heat, vibration, motion, pressure, magnetic fields, and RF/microwave signals. Some methods of producing energy are quite creative but practical. EnOcean (www.enocean.com), for example, makes wireless light-emitting-diode (LED) lamp switches that use the pressure of a user's hand on the switch as the source of energy. Pressing on the switch generates the dc power needed to transmit wireless on/off signals to an LED lamp within line of sight of the switch.

The basic concept for harvesting energy from an RF source typically involves an extra antenna to receive the desired wireless signals via a wireless product's primary receiver. Alternately, a secondary receiver may be dedicated to energy harvesting that covers the frequency range of interest (*see figure*). Received signals are applied to some form of rectifying circuitry to convert the wireless energy to dc power.

In some cases, an antenna that incorporates the rectifying circuitry, known as a rectenna, may be used to save space. The antenna portion of a rectenna can be almost any form of antenna suitable for the frequency band of interest. Options include a monopole, dipole, or microstrip patch fabricated on printed-circuit board (PCB), along with rectifying circuitry based on nonlinear rectifying devices (such as Schottky or IMPATT diodes). The antenna will be joined to the rectifying circuitry by means of impedance-matching circuitry and filters, such as lowpass filters, to block any harmonics generated by the diodes.

Conversion efficiency is critical to any energy-harvesting solution. The antenna and receiver will determine the amount of RF signal power available for rectification, while the diodes and diode-rectifying circuitry will determine the RF-to-dc conversion efficiency. Energy-harvesting circuits have historically taken advantage of plentiful sources of RF energy, such as FM radio signals, which can be collected with simple stick antennas and basic diode-rectifying circuits.

Voltage regulation is an important part of any energy-harvesting solution, as it ensures that a stable supply of electricity is being provided to the load. For that purpose, a number of IC suppliers offer various forms of voltage converters with built-in regulation to maintain consistent voltage and current for the intended load. Linear Technology

(www.linear.com/energyharvesting), for example, has developed a family of energy-harvesting power supplies with capabilities that target different forms of initial energy sources.

The ICs, which integrate a full-wave bridge rectifier with a buck converter, are designed for lower current operation with lower-energy sources (like thermoelectric generators and piezoelectric sources) and higher currents with higher-power sources (e.g., solar and RF energy). In fact, many IC suppliers with energy-harvesting power supplies, such as Silicon Labs (www.silabs.com) and Texas Instruments (www.ti.com), offer reference designs to show their ICs in typical applications.

These ICs are not simple power-supply circuits, but sophisticated means of (in some cases) controlling trickle charges to a battery from a low-power energy supply. A device such as the LTC3588-1 from Linear Technology is a nanopower energy-harvesting power supply for use with high-output-impedance energy sources such as piezoelectric, solar, or magnetic transducers. It allows charge to accumulate on an input capacitor until the IC's buck converter can efficiently transfer a portion of the stored charge to a load (like a battery) at the output.

It provides four pin-selectable output voltages of 1.8, 2.5, 3.3, and 3.6 V with as much as 100 mA continuous output current to accommodate many different load or battery requirements. A larger output capacitor can be used with the IC when higher output current bursts are needed. This IC, with an input voltage range of 2.7 to 20.0 V dc, is part of a total energy-harvesting solution, along with an antenna, receiver, and rectifying element. Depending on the amount of energy available from a source, the designer of an energy-harvesting solution would select the power-supply circuitry according to the expected voltage and current range to be fed to the load.

Energy sources are all around, and RF/microwave signals are just one type of those sources. Military equipment suppliers, for example, have already experimented with circuits that extract energy from motion, such as using a soldier's walking motion to generate the power supply for recharging a portable radio system. In the medical world, where implantable devices must be powered by external power supplies, ICs are being developed with on-chip antennas and the capability to draw power from radio waves in a patient's environment. The rapid growth of IoT devices and applications will be creating increasing demand for energy-harvesting solutions that can free many future wireless devices from their dependences on batteries. **mtw**

HIGH PERFORMANCE VOLTAGE CONTROLLED OSCILLATORS

**Up to
18.0
GHz**



Features

- > **Exeptional Phase Noise**
- > **Optimized Bands Up-to 3:1 Bandwidth**
- > **Planar, Ceramic & SAW Resonator Construction**
- > **REL-PRO Patented Technology**
- > **Miniature & Small Size, Surface Mount**
- > **RoHS Compliant**



Talk To Us About Your Custom Requirements.



Phone: (973) 881-8800 | Fax: (973) 881-8361

E-mail: sales@synergymw.com

Web: WWW.SYNERGYMWAVE.COM

Mail: 201 McLean Boulevard, Paterson, NJ 07504

Driving the Future of Vehicular Technology

Electronic technologies, from basic temperature sensors to millimeter-wave radars, are playing more prominent roles in new car models.


AUTOMOBILES ARE BEING made smarter with each model year. Electronic technologies are playing major roles in enhancing vehicular safety, and that trend will continue. Cameras and millimeter-wave radar systems in newer car models, for example, can detect objects in front and rear and send warning and trigger signals to other subsystems within a car, such as the automatic braking system (ABS), to prevent an accident.

The interest of automotive manufacturers in producing fully autonomous vehicles has been well publicized, and the overall growth of electronic content within new-model automobiles represents a heartily growing market for electronic devices such as microprocessors and wireless transceivers, as well as software that can help build the road to the “driverless” vehicle of the future. But before we can all take our hands off the wheel, a better understanding of the industry’s growing electronic needs is needed.

Cars are smarter due to their growing electronics content, starting with their computer networks—among them, those based on the controller area network (CAN), local interconnect network (LIN), and FlexRay protocols. The CAN protocol, for example, allows all electronic devices in an automobile to communicate. A vehicle’s electronic control unit (ECU) can communicate by means of a single CAN interface, as opposed to utilizing separate analog and digital interfaces for different electronic components to save weight and complexity. The CAN protocol was first developed for automotive applications, but has been adopted by other industries (e.g., medical electronic equipment manufacturers) because of its reliability and effectiveness.

As vehicles gain more electronic content, an efficient communications and control protocol such as CAN is essential for orchestrating the sequences of messages among the networked devices. All devices on a CAN system first receive all transmitted messages from the ECU, then decide whether a message is relevant or should be filtered. Every message has a priority, and the device node with the higher priority has the opportunity to respond first. A CAN system includes cyclic redundancy code (CRC) that is used for error checking.

In addition to this communication of electronic devices within a vehicle’s own network, future vehicles will also communicate



1. The concept of vehicle-to-vehicle (V2V) communications involves a sharing of vehicular speed and location information among vehicles with V2V wireless technology, to avoid accidents as well as traffic backups. (Courtesy of Car Talk)

with each other by means of wireless vehicle-to-vehicle (V2V) communications. A recent proposal by the U.S. Department of Transportation (DoT) outlined the benefits of V2V communications and a timeframe for its implementation in new model cars (by 2023). The proposal is under review by a number of other organizations, including the U.S. Federal Highway Administration and the Alliance of Automobile Manufacturers.

By having all vehicles communicating their locations, speeds, directions, and other parameters 10 times per second to other vehicles, all vehicles will have a 360-deg. situational awareness of the traffic volume and conditions around them (*Fig. 1*), both to avoid accidents and minimize traffic congestion. Existing vehicular electronic technologies, such as collision-avoidance systems, are seen as complementary to V2V systems and networks.

The DoT’s proposal suggests that V2V technology can provide significant decreases in the number of accidents and significant decreases in the number of lives lost due to vehicular accidents. The 392-page proposal is aligned with the automotive industry’s efforts to develop autonomous, “self-driving” vehicles that would employ GPS satellite receivers for position information and V2V networks for cars to “talk” to each other by means of various electronic components and devices. As a consequence, roads are made safer even with less local control exerted by human drivers.

SWITCH-N-SAVE


NEW!

RF Switches

by

CEL

SWAP THEM WITH OTHER
SUPPLIER SWITCHES FOR
BIG SAVINGS



LOWER COST SOLUTIONS

Cost Savings for New and Existing Customers













HIGHER RF PERFORMANCE

Better RF Performance than other RF Switches



HIGH JAPANESE QUALITY

Manufactured in Japan with High Quality, Packaging and Testing

CEL Part Numbers	Switch Type	MAX Freq. (GHz)	Insertion Loss (dB)		Isolation (dB)		Compression point @ 3V (dBm)		Package Type (mm)
			2.5 GHz	6.0 GHz	2.5 GHz	6.0 GHz	2.5 GHz	6.0 GHz	
CG2163X3	SPDT	6.0	0.40	0.50	40	31	+33 @ P1.0dB	+32 @ P1.0dB	 (1.5 x 1.5 x 0.37)
JUST ADDED CG2164X3	DPDT	6.0	0.50	0.65	25	17	+32 @ P0.5dB	+30 @ P0.5dB	 (1.5 x 1.5 x 0.37)
CG2176X3	Absorptive SPDT	6.0	0.45	0.55	30	22	+37.5 @ P0.5dB	+37.5 @ P0.5dB	 (1.5 x 1.5 x 0.37)
CG2179M2	SPDT	3.0	0.45	N/A	26	N/A	+30 @ P0.1dB	NA	 (2.0 x 1.25 x 0.9)
CG2185X2	SPDT	6.0	0.35	0.40	28	26	+29 @ P0.1dB	+29 @ P0.1dB	 (1.0 x 1.0 x 0.37)
CG2214M6	SPDT	3.0	0.35	N/A	25	N/A	+30 @ P0.1dB	NA	 (1.5 x 1.1 x 0.55)
JUST ADDED CG2409M2	SPDT	3.8	0.45	N/A	27	N/A	+37.5 @ P0.1dB	NA	 (2.0 x 1.25 x 0.9)
JUST ADDED CG2409X3	SPDT	6.0	0.40	N/A	26	N/A	+37.5 @ P0.1dB		 (1.5 x 1.5 x 0.37)
CG2415M6	SPDT	6.0	0.35	0.45	32	26	+31 @ P0.1dB	+31 @ P0.1dB	 (1.5 x 1.1 x 0.55)
CG2430X1	SP3T	6.0	0.50	0.60	28	25	+28 @ P0.1dB	+28 @ P0.1dB	 (1.5 x 1.5 x 0.37)

CEL

WWW.CEL.COM/SWITCHES

Wireless communications within a single vehicle has traditionally been conducted within the Industrial-Scientific-Medical (ISM) frequency band, typically from 315 to 915 MHz, although much higher frequencies are used for automotive radar systems and will be used for V2V technology. For example, in the U.S., the FCC has allocated the frequency range normally associated with wireless local area network (WLAN) equipment for V2V applications: 5.850 to 5.925 GHz. While

internet providers and other wireless users are hoping to gain the use of some of this bandwidth, the automotive industry is well aware of the need for bandwidth if it is to achieve the challenging goals set for future V2V networks.

Depending upon geographic regions, the V2V standards and frequencies will vary. The U.S. V2V standard is commonly known as the wireless access for vehicular environments (WAVE) standard. Europe has the vehicular ad hoc network (VANET) standard,

which is a variation on the mobile ad hoc network (MANET) standard. While the FCC that governs frequency bandwidth in the U.S., it is the European Telecommunications Standards Institute (ETSI) in Europe that sets the requirements for V2V technology. The latter governing body has created a standard known as ITS-G5, which is based on the IEEE's 802.11p wireless networking standard.

DRIVING MORE CHIPS

Semiconductor manufacturers have been long at work developing and supplying wireless transceivers, sensors, and other forms of integrated circuits (ICs) for automotive electronics prior to the coming of V2V technologies. The list of well-established IC suppliers for automotive electronics is long, and includes Analog Devices (www.analog.com), Broadcom (www.broadcom.com), NXP Semiconductors (www.nxp.com), and Infineon Technologies (www.infineon.com). Not only are electronic sensors helping to meet stricter emissions standards for vehicles with internal combustion engines, but they are also being used to achieve low-emissions power trains in hybrid electric vehicles (HEVs).

The operating environment for automotive ICs is not unlike the specifications set for military electronic devices, with high reliability required over wide operating temperature ranges. To be considered "automotive-grade" electronic devices, such ICs must endure stress testing according to guidelines established by the Automotive Electronics Council (AEC) in the AEC Q100 specifications. Electronic devices for automotive use are qualified according to how rigorous the conditions of their particular applications and locations within the vehicle, with grades

KOAXIS, Inc. Coaxial RF Cable Assemblies

Semi-rigid Design Guide

download at koaxis.com



**Quicker and more
cost-effective assemblies
are as easy as 1-2-3-4-5-6**

or, as always

Build It visually build a cable assembly
See It get a specification instantly
Buy It online using eCommerce




Made in the USA

+1 (610) 222-0154

0 through 4 assigned for different ambient operating temperature ranges: -40 to +150°C (Grade 0), -40 to +125°C (Grade 1), -40 to +105°C (Grade 2), -40 to +85°C (Grade 3), and -40 to +70°C (Grade 4).

Through its merger with Freescale Semiconductor, NXP (which is in turn about to be acquired by Qualcomm) fortified its already strong semiconductor design and fabrication capabilities to produce some of the industry's smallest 77-GHz radar ICs (Fig. 2). Based on a high-frequency silicon germanium (SiGe) semiconductor process, the single-chip, multiple-channel, 77-GHz radar transceiver measures just 7.5×7.5 mm² and provides high-resolution radar performance for automotive advanced driver assistance systems (ADASs). The small size of the radar IC makes it easier to integrate into multiple locations within a vehicle. The IC provides the accurate, high-resolution radar returns needed for self-driving autonomous vehicles in addition to its support of collision-avoidance systems and adaptive cruise control systems.

Infineon, a long-time supplier of automotive electronic solutions, also relies on a SiGe semiconductor process for its radar system IC (RASIC) series of 77-GHz automotive radar devices that are fully qualified to AEC-Q100 requirements. The highly integrated devices require few, if any, additional external components.



2. The high level of integration used in a SiGe semiconductor process has enabled the production of this miniature 77-GHz automotive radar chip. (Courtesy of NXP Semiconductors)

NXP, which supports all three automotive network protocols, also makes a number of RF-based solutions for automotive electronics applications at ISM band frequencies, including a single-chip transceiver with programmable fractional-N phased-lock loop (PLL) frequency synthesizer. These lower-frequency devices are typically used for such applications as communicating data from tire pressure monitoring systems (TPMSs) and for keyless remote entry and other telemetry applications. The firm supplies a range of sensors for such functions as monitoring gas emissions and fluid temperature monitoring (such as for anti-freeze and motor oil).

All automotive radar systems are not at millimeter-wave frequencies, as Analog Devices offers a frequency-modulated-continuous-wave (FMCW) radar chip for use at 24 GHz, along with a number of different sensors based on MEMS technology. The radar chipset

includes a two-channel transmitter, a four-channel receiver, and a 13-GHz fractional-N PLL frequency synthesizer. The firm recently bolstered its position as an electronics component supplier for automotive safety systems by acquiring solid-state laser-beam steering technology from the privately held Vescent Photonics, Inc. of Golden, Colo. The nonmechanical technology is a good fit for automotive LIDAR systems with higher reliability than mechanical solutions.

Between the self-contained networks within each vehicle, such as a CAN system, and the expectations of widespread V2V wireless communications capabilities in future vehicles, modern wireless communications technologies will ensure that vehicles are as well connected as their owners. Whether a driver's hands are on or off the steering wheel, hopefully the end result is a safer driving experience for all. **mw**

EXIT OUT OF ORDINARY

EXODUS

ADVANCED COMMUNICATIONS



High Power SSPA
 : Chip & Wire, Assemblies, Modules & Systems
 : Broadband, CW, Pulse & Linear Applications
 : 1MHz to 47GHz, 3KW CW, 10KW Pulse
Block Up Converters
Low Noise Amplifiers



Exodus Advanced Communications, Corp.
 3674 E. Sunset Road, Suite 100
 Las Vegas, Nevada 89120 USA
 Tel : 1-702-534-6564
 Fax : 1-702-441-7016
 Email : sales@exoduscomm.com
 Web : www.exoduscomm.com

Sales contacts
 Inside Sales : Christy Strahan Anderson
 Domestic/International Sales : Bill Liebman
 Technical Sales : Effi Bainvol



EXODUS ADVANCED COMMUNICATIONS

Design Feature

JUNDING ZHAO | Microwave Engineer,
Nanjing Changfeng Aerospace Electronic Technology Co. Ltd., Nanjing 210094, China

HAO ZHANG | Microwave Engineer,
Nanjing Changfeng Aerospace Electronic Technology Co. Ltd., Nanjing 210094, China

UWB Printed Antenna Blocks Satellite and WLAN Signals

This novel monopole UWB antenna provides two notched bands for rejecting interference from 5-GHz WLAN signals and 8-GHz X-band satellite signals.


Ultrawideband (UWB) communications systems provide many times the bandwidth needed for standard communications services, such as cellular wireless communications or wireless local area networks (WLANs). One of the main benefits of an UWB component like an antenna or amplifier is that a single component can be used in a system that provides multiple communications services.

As an example, a novel printed UWB monopole antenna was developed with dual-notched frequency bands, for use in both the 5.2-GHz WLAN band and the 8.0-GHz X-band satellite communications (satcom) band. The design couples an E-shaped structure with microstrip feedline to achieve UWB performance with band-rejection capability. The UWB antenna demonstrates omnidirectional radiation patterns across its wide bandwidth.



UWB radio technology has attracted a great deal of attention ever since the U.S. Federal Communications Commission (FCC) allocated 7.5 GHz of bandwidth (3.1 to 10.6 GHz) for unlicensed radio applications. Many applications have been developed based on UWB technology, such as short-range broadband communications, radar sensing, and body-area networks (BANs) for medical and health-care use.¹ In terms of antennas for UWB systems, planar monopole antennas present attractive features: simple structure, small size, low cost, stable radiation patterns, and constant gain over wide operating bands. Owing to these characteristics, research is increasingly being focused on planar monopoles for UWB use.²⁻⁶

Potential problems for UWB communications systems stem from interference from existing systems within that

wide frequency range, such as 5.8-GHz signals from WLAN systems and 8-GHz signals from X-band satellite communications systems (XSCSs). As a result, a compact UWB monopole antenna with multiple reject bands can provide a practical solution to reject these unwanted interference signals.⁷⁻¹³



1. These diagrams show the layout of the UWB antenna with two notches: (a) the overall view of the antenna layout, (b) a front view of the layout, and (c) a rear view of the layout.



2. This layout and equivalent circuit represent the coupled E-shaped resonator used in the UWB antenna.

with radius, R_1 , of 8.5 mm, which is fed by 50- Ω microstrip line of width $w_0 = 3.5$ mm. To improve impedance-matching performance, a rectangular slit is embedded in the ground plane, located under the microstrip feed line. The final opti-

To achieve the desired band-notched performance, different-shaped slots (such as U- or V-) are usually inserted into the initial UWB monopole antenna structure. In refs. 8 and 9, however, only one notch band was created. In refs. 10 and 11, two notched bands can be achieved by means of a defected ground structure (DGS) approach. However, all these notched UWB antenna design strategies are based on the use of multilayer circuit structures that would increase fabrication costs and not be compatible with existing integrated-circuit (IC) radio devices.

To provide a practical solution for limiting the effects of interference in UWB systems, a compact UWB monopole antenna with two notch bands was developed. To start, the resonant properties of an E-shaped resonator were explored. Analysis of the resonator structure reveals that dual bandstop performance was possible based on the dual-mode resonant properties of the E-shaped resonator. By placing the E-shaped resonator structure close to the feed-line of the UWB antenna, it should be possible to achieve the two notched bands within the total UWB frequency range.

To validate the design concept, a novel planar UWB antenna with two sharply rejected notch bands centered at 5.8 and 8.0 GHz, respectively, was designed and fabricated. Computer simulations and prototype measurements show that the antenna achieves an ultrawide bandwidth ranging from 2.0 to 11.0 GHz while avoiding interference from WLAN/XSCS signals. The antenna offers an omnidirectional radiation pattern in the H-plane across its full bandwidth.

Figure 1 presents the geometry of the proposed UWB antenna with two sharp notch bands. The antenna consists of a dual bandstop filter and a conventional planar circular monopole antenna. It is fabricated on 0.508-mm-thick RO4350B circuit material from Rogers Corp. (www.rogerscorp.com). The circuit material exhibits a dielectric constant (relative permittivity) of 3.48 at 10 GHz in the z-axis (thickness) of the substrate. The bandstop filter (i.e., the two notch bands) is realized by coupling the E-shaped resonator to 50- Ω microstrip feedlines for the antenna.

The proposed planar UWB antenna has a circular patch

mized parameters of the planar UWB antenna are as follows: $w_1=20$ mm, $w_2=8.05$ mm, $w_3=4.6$ mm, $w_4=0.3$ mm, $l_1=35$ mm, $l_2=16$ mm, and $l_3=3.8$ mm.

The proposed E-shaped resonator is composed of a stepped-impedance hairpin resonator with a centrally loaded short-ended stub. Figure 2 shows the layout of the E-shaped resonator coupled to a section of main transmission line and its corresponding equivalent circuit. The properties of the E-shaped resonator can be analyzed by the even-odd-mode analysis method. Under mode excitation, the electrical field distribution of the resonator exhibits either an even- or an odd-mode distribution property. Thus, the even- and odd-mode resonant frequencies (f_{even} and f_{odd} , respectively) can be deduced by means of Eqs. 1 and 2, respectively:


$$f_{\text{even}} = \frac{c}{\lambda_{\text{even}} \sqrt{\epsilon_{\text{eff}}}} = \frac{c}{4(l_{e1} + l_{e2} + l_{e3}) \sqrt{\epsilon_{\text{eff}}}} \quad (1)$$

$$f_{\text{odd}} = \frac{c}{\lambda_{\text{odd}} \sqrt{\epsilon_{\text{eff}}}} = \frac{c}{4(l_{e1} + l_{e2}) \sqrt{\epsilon_{\text{eff}}}} \quad (2)$$

where f is the center frequency of the E-shaped resonator; ϵ_{eff} denotes the effective dielectric constant of the substrate; and c is the speed of light in free space.

The dual-mode stepped-impedance resonator (SIR) can achieve dual-stopband (i.e., the two notch bands) performance when placed next to the microstrip feedline. It can be functionally equivalent to two shunt-connected series resonance circuits, as shown in Fig. 2b. The section l_{e1} , l_{e2} of the dual-mode SIR can be seen as the capacitance C while the section l_{e3} of the dual-mode SIR can be seen as inductance L . The dimensions of the E-shaped resonator were selected as follows: $w_{e1} = 0.2$ mm, $w_{e2} = 0.2$ mm, $l_{e1} = 3$ mm, $l_{e2} = 4.6$ mm, $l_{e3} = 0.8$ mm, and $r_e = 0.2$ mm.

Transfer characteristics of the coupled E-shaped resonator with various dimensions were studied to validate its two-mode resonant properties (Fig. 3). The frequencies of the two notch bands move down simultaneously with



3. These S-parameters were simulated for various dimensions of the coupled E-shaped resonator: (a) l_{e2} and (b) l_{e3} .

increases in the length l_{e1} . This is because the electrical fields are distributed on these two sections for both the even and odd modes.

When l_{e3} is decreased, only the frequency of the first notch band moves higher. This is because there are no electrical fields distributed on the area of l_{e3} for the odd mode. Therefore, by appropriately adjusting the resonator dimensions, two notch bands can be achieved at desired frequencies.


Based on the two bandstop filters previously described, a novel planar UWB monopole antenna with two high-rejection notch bands was designed as shown in Fig. 4. All simulations were carried out using Version 11.0 of the commercial Ansoft HFSS finite-element EM simulation software from Ansys (www.ansys.com).

Figure 5 compares the simulated and measured VSWR for the UWB antenna. The antenna exhibits an impedance


bandwidth of 2.0 to 11.0 GHz for a VSWR of less than 2.0:1, except for the notch bands of 5.5 to 6.5 GHz and 7.6 to 9.1 GHz. The center frequencies of these two notch bands are about 5.8 and 8.0 GHz, respectively.

These notch bands are well suited for rejecting 5.8-GHz WLAN signals and 8.0-GHz satellite signals. The normalized radiation patterns in the E- and H-planes were simulated at 2.5, 5.0, 7.5, and 10.0 GHz (Fig. 6). As the patterns show, the antenna achieves good omnidirectional radiation patterns in the H-plane. Figure 7 plots the measured peak gain in the E-plane. The radiation patterns in the E-plane are in symmetry. Even with its dual notches, this antenna behaves very much like a typical printed-circuit-board (PCB) monopole antenna.

By controlling the parameters of the E-shaped resonator, the two notch bands can be easily tuned to the desirable




4. This is a photograph of the fabricated prototype of the UWB antenna with dual notches.



5. The measured and simulated VSWRs of the UWB antenna are plotted here.

NOW! Revolutionary **ABSORPTIVE/REFLECTIONLESS FILTERS**

DC to 21 GHz!



Stop Signal Reflections Dead in Their Tracks!

Mini-Circuits is proud to bring the industry a revolutionary breakthrough in the longstanding problem of signal reflections when embedding filters in RF systems. Whereas conventional filters are fully reflective in the stopband, our new X-series reflectionless filters are matched to 50Ω in the passband, stopband and transition band, eliminating intermods, ripples and other problems caused by reflections in the signal chain. They're perfect for pairing with non-linear devices such as mixers and multipliers, significantly reducing unwanted signals generated due to non-linearity and increasing system dynamic range by eliminating matching attenuators². They'll change the way you think about using filters in your design!

Jump on the bandwagon, and place your order online today for delivery as soon as tomorrow. Need a custom design? Call us to talk to our engineers about a reflectionless filter for your system requirements.



X-Series

\$6⁹⁵¹
ea. (qty. 1000)

- ✓ High pass, low pass and band pass models
- ✓ Patented design eliminates in-band spurs
- ✓ Absorbs stopband signal power rather than reflecting it
- ✓ Good impedance match in passband stopband and transition
- ✓ Intrinsically Cascadable³
- ✓ Passbands from DC – to 21GHz⁴
- ✓ Stopbands up to 35 GHz

 ***Tiny 3x3mm QFN***

¹ Small quantity samples available, \$9.95 ea. (qty. 20)

² See application note AN-75-007 on our website

³ See application note AN-75-008 on our website

⁴ Defined to 3 dB cutoff point


Protected by U.S. Patent No. 8,392,495 and Chinese Patent No. ZL201080014266.1.
Patent applications 14/724976 (U.S.) and PCT/USIS/33118 (PCT) pending.



By controlling the parameters of the E-shaped resonator, the two notch bands can be easily tuned to the desirable frequency locations.

frequency locations. The antenna covers the frequency range for UWB systems, between 2.0 and 11.0 GHz, with rejection bands centered around WLAN/SCS services. With the benefit of small size, outstanding performance can be realized for broadband antennas—widely needed for UWB applications.

The measured results show good performance in terms of reflection coefficient, antenna gain, and radiation patterns. The antenna design represents a practical approach for modern UWB wireless communication



6. The measured and simulated radiation patterns for the UWB antenna are shown for the following frequencies: (a) 2.5 GHz, (b) 5.0 GHz, (c) 7.5 GHz, and (d) 10.0 GHz.


HAPPY NEW YEAR!

HSX
SERIES
SIGNAL GENERATORS



RESOLVE TO GET MAXIMUM PERFORMANCE


- ▶ 1GHz Phase Noise: -142dBc/Hz (10kHz offset)
- ▶ 10MHz to 3, 6, 12, and 20GHz (1mHz resolution)
- ▶ Spurious Response: $< -80\text{dBc}$
- ▶ Dynamic Range: $+20\text{dBm}$ to -110dBm
- ▶ Channel-Channel Isolation: $< -110\text{dB}$
- ▶ 4x Independent, PHASE COHERENT Channels



holzworth
instrumentation


phone: +1.303.325.3473

www.holzworth.com



7. The measured peak gain of the UWB antenna is plotted as a function of frequency for the UWB frequency range.

systems owing to its simple topology, compact size, and excellent performance.

Editor's Note: The authors' design approach was also demonstrated in the construction of an UWB bandpass filter, using parallel U-shaped slots to achieve dual frequency notches within the full FCC-approved UWB frequency range of 3.1 to 10.6 GHz. (See <http://mwrfl.com/passive-components/ufw-bandpass-filter-features-dual-notches>). 

REFERENCES

1. Revision of Part 15 of the Commission's Rules Regarding Ultra-Wideband Transmission Systems, First Note and Order, Federal Communications Commission, ET-Docket 98-153, 2002.
2. M. Naghshvarian-Jahromi, "Novel wideband planar fractal monopole antenna," *IEEE Transactions on Antennas & Propagation*, Vol. 56, No. 12, 2008, pp. 3,844-3,849.
3. M. Naser-Moghadasi, H. Roustaei, and B.S. Virdee, "Compact UWB planar monopole antenna," *IEEE Antennas and Wireless Propagation Letters*, Vol. 8, 2009, pp. 1,382-1,385.
4. S.M. Mazinani and H.R. Hassani, "A novel broadband plate-loaded planar monopole antenna," *IEEE Antennas and Wireless Propagation Letters*, Vol. 8, 2009, pp. 1,123-1,126.
5. M. Sun, Y.P. Zhang, and Y. Lu, "Miniaturization of planar monopole antenna for ultrawideband radios," *IEEE Transactions on Antennas & Propagation*, Vol. 58, No. 7, 2010, pp. 2,420-2,425, 2010.
6. Raj Kumar, and Ashish G. Kokate, "On the design of square shape fractal antenna with matching strip for UWB applications," *International Journal of Electronics*, Vol. 100, No. 7, 2013, pp. 881-889.
7. W.-S. Lee, D.-Z. Kim, K.-J. Kim, and J.-W. Yu, "Wideband planar monopole antennas with two band-notch characteristics," *IEEE Transactions on Microwave Theory & Techniques*, Vol. 54, 2006, pp. 2800-2806.
8. K. Chung, J. Kim, and J. Choi, "Wideband microstrip-fed monopole antenna having frequency band-notch function," *IEEE Microwave & Wireless Component Letters*, Vol. 15, 2005, pp. 766-768.
9. Y. Kim and D.H. Kwon, "CPW-fed planar ultra wideband antenna having a frequency band notch functions," *Electronic Letters*, Vol. 40, 2004, pp. 403-405.
10. K. Yin and J. P. Xu, "Compact ultra-wideband antenna with two bandstop characteristic," *Electronic Letters*, Vol. 44, 2008, pp. 453-454.
11. Dan-Hong Bi, Zhi-Yuan Yu, Shao-Guo Mo, and Xun-Cai Yin, "Two new ultra-wideband antennas with 3.4/5.5-GHz two band-notch characteristics," *Microwave & Optical Technology Letters*, Vol. 51, 2009, pp. 2,942-2,945.

Looking for just the right part, at just the right price...

Connect with over 200 distributors on the NEW SourceESB!



Find electronic parts fast - from the only
database that verifies part authorization.

Parts

▼

Enter part...

Enter List

Q

www.SourceESB.com

Design Feature

SHERIF R. ZAHARAN | Postgraduate Student; sherif.zahran.1991@ieee.org

A. GAAFAR | Associate Professor

Arab Academy for Science and Technology, Department of Electronics, Cairo, Egypt

MAHMOUD A. ABDALLA | Professor; maaabdalla@ieee.org

Electromagnetic Waves Group, Department of Electronic Engineering, Military Technical College, Cairo, Egypt

How Bending Affects a Flexible UWB Antenna

A compact antenna maintains high gain and an omnidirectional radiation pattern, even with flexing across frequency ranges complying with UWB frequency allocations in the U.S. and Europe.


Flexible antennas are important components in a growing number of wireless applications, including wearable electronics and sensor systems. However, flexing the antenna from its nominal straight configuration can impact performance, depending on the antenna design, substrate material, and other factors. To meet the need for flexibility, a robust yet compact ultrawide-band (UWB) antenna was designed based on microstrip feed approach.

The antenna design measures just $38 \times 22 \text{ mm}^2$ and is fabricated on flexible liquid crystalline polymer substrate material. It features a resonating structure, which plays a key role in the enhancement of gain across the lower part of the UWB spectrum. The design was simulated with commercial design software and a prototype was built and characterized, with good agreement between simulations and measurements for bent and straight cases.

The markets for flexible wireless devices are rapidly increasing, both with regard to wearable and implantable devices for health-monitoring systems and daily-life wireless devices (e.g., cell phones, tablets, and laptop computers). For this reason, the need for flexible printed antennas has increased in recent years, especially for biomedical applications,¹⁻³ wearable applications,^{4, 5} and body-mounted applications.⁶

A number of flexible antenna designs have been attempted on different mechanically flexible substrate materials. Some approaches involve

textile substrates,^{7, 8} others use paper substrates,^{9, 10} and still others employ thin, flexible dielectric substrates.¹¹⁻¹³ A tradeoff always exists between achieving functional conformability and low cost. In the case of circuits fabricated on flexible substrates, the circuit material must be robust and be able to endure wide temperature ranges without degradation in performance.



1. These 2D diagrams illustrate the basic geometry of the UWB antenna: (a) the top layer and (b) the bottom layer.

For flexible antennas, design goals include good radiation parameters in a compact size, with performance maintained throughout bending. In other words, it is very important requirement that they should perform effectively under various bending conditions.¹⁴

One application area in urgent need of flexible devices is UWB communications. The enormous bandwidth available, the capacity for high data rates, and the potential for small size and low processing power—along with low implementation costs—present a unique opportunity for UWB to become a widely adopted radio solution for future wireless home-networking technology.¹⁵

Such systems include wireless PC peripherals, multimedia connectivity, and wireless network access for mobile computing devices. One example of a flexible radio application is a body area network (BAN), which is becoming increasingly popular for health monitoring in medical applications.

From a frequency spectrum point of view, UWB technology employs bandwidths of greater than 500 MHz (or fractional bandwidths of greater than 20%¹⁵), such as 2,500 to 3,000 MHz. Depending on location, various frequency allocations have been made for UWB series.

In the United States, for example, there is 3.1 to 10.6 GHz by the Federal Communications Commission (FCC).¹⁶ Europe has multiband orthogonal frequency division multiplexing (MB-OFDM; 3.1 to 4.8 GHz) and direct-sequence UWB (DS-UWB; 6 to 8.5 GHz) by the European Conference for Postal and Telecommunication Administrations (CEPT) Electronic Communication Committee (ECC).¹⁷

Antennas designed for these applications should have reasonable and constant radiation properties (such as radiation pattern type, gain, and polarization) within their operating bandwidths.^{18,19} Different planar monopole antenna structures have been widely used as UWB antennas due to their ability to provide constant omnidirectional radiation patterns and controlled input impedance parameters over the UWB frequency band. Moreover, planar antennas have simple structures and small size, and can be printed on the very same PCB circuitry as the transmitter and receiver.²⁰⁻²⁶

Designing flexible antennas requires thin substrates to accommodate the flexing. As a consequence, the antenna's radiation pattern properties may be degraded due to the thinness of the substrate. Care must be taken in the design of an antenna with thin substrate material to achieve an omnidirectional radiation pattern with good gain across the target operating frequency range. Examples of UWB flexible antennas in planar configurations are presented in refs. 27-31. Success in achieving good performance parameters has made flexible UWB antennas valuable components for wearable, implantable, and body-centric applications.³²⁻³⁴


By using an extremely thin substrate material, it is possible to develop a compact flexible antenna for UWB applications. The

antenna is fed with a microstrip transmission line with modified monopole structure. The design was computer-simulated with a commercial full-wave electromagnetic (EM) simulation software program, with measurements of a prototype matching closely with the performance predictions made by the simulations.

The antenna design employs a microstrip-fed circular monopole with resonator at ground level, fabricated on Ultralam 3850 liquid-crystal-polymer (LCP) circuit material from Rogers Corp. (www.rogerscorp.com). The circuit material has dielectric constant (relative permittivity) of 3.14 in the z-axis (thickness) at 10 GHz with loss tangent of 0.0025. The substrate was 100 μm thick and the copper cladding was 18 μm thick.

Figures 1a and b show the top and bottom design geometry of the antenna, respectively. The top layer is designed as a circular monopole antenna. The monopole antenna is fed by a single 50- Ω transmission line with feed width, $W_f = 0.245$ mm. To compensate the low efficiency of an antenna fabricated on such a thin substrate, an incomplete half-disk resonator was added on the bottom of the circular patch antenna.

The additional resonator acts as an incomplete reflector, preserving moderate antenna gain without deforming the desired omnidirectional radiation pattern of the antenna. A stub was added to the resonator to compensate for any further added resonance that may affect the desired UWB bandwidth. Finally, the ground shape of the feeding microstrip transmission line was formed in the shape of a triangle to decrease the size of metal at the ends, which enhances bending functionality.



2. These photographs show the fabricated prototype antenna next to a British penny: (a) the bottom layer, (b) the top layer, and (c) the amount of bending possible with the flexible substrate.


Figure 2 compares the fabricated antenna prototype to a coin (a British penny) and in its bent form. Fabrication was performed by means of a carefully controlled photolithographic process, followed by a high-resolution chemical etching process. As can be seen in Fig. 2c, the antenna's thin structure and bending capabilities make it an excellent candidate for wearable wireless electronic products.

The initial design of the circular monopole diameter was set equal to the wavelength of the center frequency within the selected UWB bandwidth, which was designed as 7.5 GHz.


THE PROPOSED FLEXIBLE UWB ANTENNA AND ITS DIMENSIONS						
Parameters (in mm)						
Parameter	L	W	D _p	D ₁	D ₂	W _S
Dimension	38	22	21.2	10.2	20.2	6
Parameter	W _{g1}	W _{g2}	L _g	X	W _f	L _f
Dimension	8	18	14.8	1	0.245	15

The antenna was further optimized based on investigating the current flow through the antenna radiator over the full bandwidth of the UWB antenna requirements. The antenna’s dimensions are listed in the *table*; it has a total area of 38×22 mm².


To explain the role of the additional resonator at ground, the surface current distributions are shown in *Fig. 3* with and without the resonator. It shows the direction and distribution of surface currents at 4 GHz induced by the presence of a



3. These simulated plots show magnitude/vector surface current distributions over the top and bottom antenna surfaces for (a) the antenna geometry without the booster at 4 GHz, and (b) the novel UWB antenna design with the bottom booster resonator at 4 GHz.



4. This 2D radiation pattern was simulated for the normalized antenna XZ-plane gain, for different antenna configurations, at 4 GHz.




5. The flexible antenna design was simulated for its flexed performance when bent over an imaginary cylinder with radius R_x .

smaller-radius, ground-resonating structure, which forces the current to coexist more on the edges of the top radiating patch. This enhances the generation of less-deformed radiation patterns at this frequency.

The normalized two-dimensional (2D) gain pattern in the X-Y plane of *Fig. 4* demonstrates how the initial structure without the stub resonator improves the generation of radiation in the Z+ direction. It also shows how the addition of the stub results in further enhancements to the radiation pattern in that direction.

The antenna’s performance was simulated with the commercial Ansoft HFSS finite-element EM simulation software from Ansys (www.ansys.com). Two versions of the antenna were built and simulated: straight and bent forms. *Figure 5* shows the configuration of the bent version of the antenna, with the antenna simulated as being bent around an imaginary cylinder with radius of curvature R_x .



6. The photograph shows the measurement setup for the UWB antenna design, using a test fixture from Inter-Continental Microwave (www.icmicrowave.com).

The antenna’s resonant characteristics were confirmed by measurements of the fabricated antenna prototype. *Figure 6* shows the measurement setup for antenna matching. A test fixture was used to measure antenna impedance-matching properties, since soldering a 50-Ω SMA connector to the antenna for coaxial measurements proved quite difficult due to the narrow width of the antenna’s microstrip transmission lines.

Figure 7 compares the simulated reflection coefficients of the antenna for straight and bent ($R_x = 40$ mm) formats versus the measured reflection coefficient for the straight antenna.



Ultra Small 2x2mm

2W ATTENUATORS DC-20 GHz **\$1⁹⁹** from ea. (qty. 1000)


Save PC board space with our new tiny 2W fixed value absorptive attenuators, available in molded plastic or high-rel hermetic nitrogen-filled ceramic packages. They are perfect building blocks, reducing effects of mismatches, harmonics, and intermodulation, improving isolation, and meeting other circuit level requirements. These units will deliver the precise attenuation you need, and are stocked in 1-dB steps from 0 to 10 dB, and 12, 15, 20 and 30 dB.

The ceramic hermetic **RCAT** family is built to deliver reliable, repeatable performance from DC-20GHz under the harshest conditions. With prices starting at only

\$4.95 ea. (qty. 20), these units are qualified to meet MIL requirements including vibration, PIND, thermal shock, gross and fine leak and more, at up to 125°C!

The molded plastic **YAT** family uses an industry proven, high thermal conductivity case and has excellent electrical performance over the frequency range of DC to 18 GHz, for prices starting at \$2.99 ea. (qty. 20).

For more details, just go to minicircuits.com – place your order today, and you can have these products in your hands as soon as tomorrow!




Plastic

Ceramic

FREE Simulation Models! 

<http://www.modelithics.com/mvp/Mini-Circuits/>





7. Simulations provided the reflection coefficients for the straight and bent ($R_x = 40$ mm) versions of the UWB antenna, from 2 to 11 GHz, which can be compared to measurements of the straight version of the antenna.

Both simulated results have reflection coefficients lower than -10 dB from 4 to 10.7 GHz. Also, the reflection coefficient is lower than -6 dB within the frequency band of 3 to 4 GHz. Both simulated results display a deep resonance close to 7.5 GHz with small difference in amplitude. Furthermore, the measurements show similar values over most of the frequency band of interest.

The measured reflection coefficient indicates the strong resonance near 7.5 GHz, and is lower than -6 dB at frequencies starting from 3 GHz and higher. However, despite a decrease in the simulated reflection coefficient of less than -10 dB from 4 GHz and higher, the measured reflection coefficient has a

sudden increase to -4 dB in the frequency band of 4.0 to 5.3 GHz before it decreases to less than -10 dB, preserving a pattern close to that of the simulated curves.


This is caused by the difficulty in making measurements due to the thin feeding microstrip line width. However, it is still apparent that the measurement and simulated results are fairly close.

To validate the antenna's far-field characteristics, three-dimensional (3D) gain radiation patterns were simulated at certain frequencies (4, 6, 8, and 10 GHz), as shown in Fig. 8. To validate that bending the antenna does not affect its radiation patterns, the simulated radiation patterns for the straight antenna (Fig. 8a) are compared to the bent antenna with $R_x = 40$ mm for the same selected frequencies (Fig. 8b). In both cases, the 3D gain patterns preserve an omnidirectional pattern, as is quite apparent at 4, 6, and 8 GHz. A small deformation in the omnidirectional pattern is noticeable at 10 GHz.


By observing the color bar of the plotted pattern, the antenna has directive gain values that range around -40 dB for nulls at x axis (feeding axis) and 4 dB for boresight direction. For more antenna radiation pattern investigation, the simulated antenna gain at the Z axis is plotted in Fig. 9. As can be seen, the antenna gain reaches a maximum at 7 GHz, where it is 3.5 dB, and a minimum at -1 dB for the frequency band edges within the UWB spectrum.

To analyze the antenna radiation patterns within the UWB frequency range, the current distributions were measured and plotted for the same test frequencies at 4, 6, 8, and 10 GHz (Fig. 10). As can be seen, the radiation pattern degrades with increasing frequency. Also, the current distribution is homogeneous over the antenna's resonant band in ordered harmonics, which explains how the antenna preserves the omnidirectional pattern at these frequencies.


The antenna design provides near-stable performance with bending in terms of matching and radiation characteristics. The design appears suitable for use in wearable applications, although other issues must also be considered. These include the specific absorption rate (SAR), along with the thermal and dielectric properties of the substrate material when matched with human tissue for medical applications.



8. The 3D gain patterns of the UWB antenna were simulated at different target frequencies for the (a) straight and (b) bent versions of the antenna, bent over an imaginary cylinder with 4-cm radius.



9. The simulated gain of the straight version of the UWB antenna was plotted as a function of frequency.



10. The magnitude/vector surface current distributions for the UWB antenna design were simulated for different frequencies.

In short, the antenna design combines flexibility with a miniature footprint of only $38 \times 22 \text{ mm}^2$, making it a good fit (literally) for wearable wireless applications. It is designed for use in the upper UWB frequency range from 4 to 10.6 GHz, satisfying at least 82% of the FCC's UWB frequency regulation and 100% of the ECC's DS-UWB frequency-range requirements. The antenna maintains an omnidirectional radiation pattern in both straight and bent configurations except at higher frequencies, with high gain throughout. **MW**

REFERENCES

- Peter S. Hall and Yang Hao, *Antennas and Propagation for Body-Centric Wireless Communications*, Second Edition, Artech House, Norwood, MA, 2011.
- Haider R. Raad, Ayman I. Abbosh, Hussain M. Al-Rizzo, and Daniel G. Rucker, "Flexible and Compact AMC Based Antenna for Telemedicine Applications," *IEEE Transactions on Antennas and Propagation*, Vol. 61, No. 2, 2013, pp. 524-531.
- Maria Lucia Scarpello, Divya Kurup, Hendrik Rogier, Dries Vande Ginste, Fabrice Axi-sa, Jan Vanfleteren, Wout Joseph, Luc Martens, and Gunter Vermeeren, "Design of an Implantable Slot Dipole Conformal Flexible Antenna for Biomedical Applications," *IEEE Transactions on Antennas and Propagation*, Vol. 59, No. 10, 2011, pp. 3,556-3,564.
- Yei Hwan Jung, Yijie Qiu, Subin Lee, Ting-Yen Shih, and Yuehang Xu, "A Compact Polyethylene-Coated WLAN Flexible Antenna for Implantable Electronics," *IEEE Antennas and Wireless Propagation Letters*, Vol. 15, 2016, pp. 1,382-1,385.
- Haider Raad Khaleel, "Design and fabrication of compact inkjet printed antennas for integration within flexible and wearable electronics," *IEEE Transactions on Components, Packaging, and Manufacturing Technology*, Vol. 4, No. 10, 2014, pp. 1,722-1,728.
- Seungman Hong, Seok Hyon Kang, Youngsung Kim, and Chang Won Jung, "Transparent and Flexible Antenna for Wearable Glasses Applications," *IEEE Transactions on Antennas & Propagation*, Vol. 64, No. 7, 2016, pp. 2,797-2,804.
- William G. Whitrow, Alford Chauraya, J.C. Vardaxoglou, Yi Li, Russel Torah, Kai Yang, Steve Beeby, and John Tudor, "Inkjet-Printed Microstrip Patch Antennas Realized on Textile for Wearable Applications," *IEEE Antennas and Wireless Propagation Letters*, Vol. 13, 2014, pp. 71-74.
- Asimina Kiourti, Cedric Lee, and John L. Volakis, "Fabrication of Textile Antennas and Circuits with 0.1 mm Precision," *IEEE Antennas and Wireless Propagation Letters*, Vol. 15, 2016, pp. 151-153.
- Ting Leng, Xianjun Huang, KuoHsin Chang, JiaCing Chen, Mahmoud A. Abdalla, and Zhirun Hu, "Graphene Nanoflakes Printed Flexible Meandered-Line Dipole Antenna on Paper Substrate for Low-Cost RFID and Sensing Applications," *IEEE Antennas and Wireless Propagation Letters*, Vol. 15, 2016, pp. 1,565-1,568.
- Hattan F. Abutarboush, M.F. Farooqui, and A. Shamim, "Inkjet-Printed Wideband Antenna on Resin-Coated Paper Substrate for Curved Wireless Devices," *IEEE Antennas and Wireless Propagation Letters*, Vol. 15, 2016, pp. 20-23.
- Sana Ahmed, Farooq A. Tahir, A. Shamim, and Hammad M. Cheema, "A Compact Kapton-Based Inkjet-Printed Multiband Antenna for Flexible Wireless Devices," *IEEE Antennas and Wireless Propagation Letters*, Vol. 14, 2015, pp. 1,802-1,805.
- Z. Hamouda, J.-L. Wojcikiewicz, A.A. Pud, L. Kone, B. Belaabed, S. Berghel, and T. Lasri, "Dual-Band Elliptical Planar Conductive Polymer Antenna Printed on a Flexible Substrate," *IEEE Transactions on Antennas & Propagation*, Vol. 63, No. 12, 2015, pp. 5,864-5867.
- K. Janeczczek, M. Jakubowska, G. Koziol, A. Mlozniak, and A. Arzina, "Investigation of ultra-high-frequency antennas printed with polymer pastes on flexible substrates," *IET Microwaves, Antennas & Propagation*, Vol. 6, No. 5, 2012, pp. 594-554.
- Hsuan-Ling Kao, Cheng-Lin Cho, Xiu Yin Zhang, Li-Chun Chang, Bai-Hong Wei, Xin Dai, and Hsien-Chin Chiu, "Bending Effect of an Inkjet-Printed Series-Fed Two-Dipole Antenna on a Liquid Crystal Polymer Substrate," *IEEE Antennas and Wireless Propagation Letters*, Vol. 13, 2014, pp. 1,172-1,175.
- Homayoun Nikookar and Ramjee Prasad, *Introduction to UltraWideband for Wireless Communications*, Chapter 2, Springer Science & Business Media, New York, 2008.
- Federal Communications Commission, "Revision of Part 15 of the Commission's rules regarding ultra-wideband transmission system from 3.1 to 10.6 GHz," ET-Docket, Federal Communications Commission, FCC, 98-153, Washington, DC, 2002.
- Report from CEPT to the European Commission in response to the Fifth Mandate to CEPT on ultra-wideband technology to clarify the technical parameters in view of a potential update of Commission Decision 2007/131.
- Ian Oppermann, Matti Hämäläinen, and Jari Iinatti, *UWB: Theory and Applications*, John Wiley & Sons, New York, 2005.
- Zhi Ning Chen and Michael Yan Wah Chia, *Broad Band Planar Antennas: Design and Applications*, Chapter 2, John Wiley & Sons, New York, 2006.
- Y. Lu, Y. Huang, H.T. Chattha, and P. Cao, "Reducing ground-plane effects on UWB monopole antennas," *IEEE Antennas and Wireless Propagation Letters*, Vol. 10, 2011, pp. 147-150.
- Sherif R. Zahran, Omar H. El Sayed Ahmed, Ahmad T. El-Shalakany, Sherif S. Saleh, and Mahmoud A. Abdalla, "Ultra Wide Band Antenna with Enhancement Efficiency For High Speed Communications," *NRSC 2014*, Cairo, Egypt, pp. 65-72.
- Ahmed Abdelreheem and Mahmoud Abdalla, "Compact Curved Half Circular Disc-Monopole UWB Antenna," *International Journal of Microwave and Wireless Technologies*, Vol. 8, No. 2, 2016, pp. 283-290.
- Ahmed Adelraheem, Mahmoud Abdalla, Hesham Elregally, and Abdelazez Mitkees, "Experimental Evaluation of High-Fidelity High-Data-Rate UWB Antenna System," 2015 *IEEE AP-S International Antenna and Propagation Symposium Digest*, July 2015, Vancouver, Canada, pp. 522-523.
- Mohamed Nabil Sfrif, Symon K. Podilchak, Mohamed Essaaidi, and Yahia M.M. Antar, "Compact Disc Monopole Antennas for Current and Future Ultrawideband (UWB) Applications," *IEEE Transactions on Antennas and Propagation*, Vol. 59, No. 12, 2011, pp. 4,470-4,480.
- Mahmoud A. Abdalla, Ahmed A. Ibrahim, and Ahmed Boutejdar, "Resonator Switching Techniques for Notched UWB Antenna in Wireless Applications," *IET Microwaves, Antennas & Propagation*, Vol. 9, No. 13, 2015, pp. 1468-1477.
- Ahmed A. Ibrahim, Mahmoud A. Abdalla, and Ahmed Boutejdar, "Hybrid Technique Delivers Dual-Notch UWB antenna," *Microwaves & RF*, Vol. 55, No. 5, May 2016, pp. 56-60.
- A.C. Durgun, M.S. Reese, C.A. Balanis, C.R. Birtcher, D.R. Allee, and S. Venugopal, "Design, simulation, fabrication and testing of flexible bow-tie antennas," *IEEE Transactions on Antennas & Propagation*, Vol. 59, No. 12, December 2011, pp. 4,425-4,435.
- Haider R Khaleel., Hussain M. Al-Rizzo, Daniel G. Rucker, and Seshadri Mohan, "A compact polyimide-based UWB antenna for flexible electronics," *IEEE Antennas and Wireless Propagation Letters*, Vol. 11, 2012, pp. 564-567.
- Sherif R. Zahran and Mahmoud Abdalla, "Novel Flexible Antenna for UWB Applications," 2015 *IEEE AP-S International Antenna and Propagation Symposium Digest*, July 2015, Vancouver, Canada, pp. 147-148.
- H.K. Yoon, Y.J. Yoon, H. Kim, and C-H. Lee, "Flexible ultra-wideband polarisation diversity antenna with band-notch function," *IET Microwaves, Antennas & Propagation*, Vol. 5, No. 12, 2011, pp. 1,463-1,470.
- Qammer H. Abbasi, Masood Ur Rehman, Xiaodong Yang, Akram Alomainy, Khalid Qaraqe, and Erchin Serpedin, "Ultrawideband band-notched flexible antenna for wearable applications," *IEEE Antennas and Wireless Propagation Letters*, Vol. 12, 2013, pp. 1,606-1,609.
- Yijie Qiu, Yei Hwan Jung, Subin Lee, Ting-Yen Shih, Juhwan Lee, Yue Hang Xu, Ruimin Xu, Weigan Lin, Nader Behdad, and Zhenqiang Ma, "Compact polyene-coated flexible antenna for WLAN and upper-band UWB applications," *Electronics Letters*, Vol. 50, No. 24, 2014, pp. 1,782-1,784.
- Hadi Bahrami, S. Abdollah Mirbozorgi, Reza Ameli, Leslie A. Rusch, and Benoit Gosselin, "Flexible, Polarization-Diverse UWB Antennas for Implantable Neural Recording Systems," *IEEE Transactions on Biomedical Circuits & Systems*, Vol. 10, No. 1, 2016, pp. 38-48.
- Yiye Sun, Sing Wai Cheung, and Tung Ip Yuk, "Design of a textile ultra-wideband antenna with stable performance for body-centric wireless communications," *IET Microwaves, Antennas & Propagation*, Vol. 8, No. 15, 2014, pp. 1,363-1,375.

DIVE INTO LNA DESIGN

A LOW-NOISE AMPLIFIER (LNA) is a critical component in a receiver design, as its performance heavily determines the receiver's overall performance. Those involved with designing LNAs must ensure that noise figure is minimized while also being mindful of other parameters. In the application note, "Design of a 10 GHz Low-Noise Amplifier," National Instruments presents the design of an LNA that operates over a frequency range of 10.0 to 10.7 GHz. The NI AWR Design Environment is used to design and simulate the LNA.

The LNA is designed with the NE3515S02 heterojunction field-effect transistor (HJFET). At 10.4 GHz, this transistor has a minimum noise figure of approximately 0.3 dB along with roughly 12 dB of associated gain. Furthermore, a 12-mil-thick RO4003C

laminar from Rogers Corp. is used for the design.

A waveguide-to-microstrip adapter is incorporated into the input section of the LNA. This adapter was simulated with the Analyst 3D electromagnetic (EM) simulator. The next step of the design process involves the planar structures, which are the amplifier stages and bandpass filter. The LNA consists of two amplifier stages, enabling it to achieve greater than 20 dB of gain. The bandpass filter is placed at the output of the second amplifier stage to reduce out-of-band gain.

Initially, the Microwave Office software was used to simulate and optimize the amplifier stages and bandpass filter via closed-form distributed transmis-

sion-line models. Final adjustments and design verification were then achieved by using the AXIEM 3D planar EM simulator. The output transition is the final section of the overall RF design. This transition is realized with a coaxial connector that is placed perpendicular to the printed-circuit board (PCB).

The LNA's enclosure is then described in detail. A specific cover is designed to prevent potential spurious oscillations. Lastly, 10 prototypes were assembled and measured. The measurements demonstrated good agreement with the simulated results, proving that the LNA has a gain of approximately 21 dB at 10.37 GHz. In addition, noise figure is below 0.6 dB across the entire 700-MHz band.

National Instruments Corp.
11500 N. Mopac Expwy.
Austin, TX 78759-3504
(877) 388-1952
www.awrcorp.com

RECOGNIZE RF ARCHITECTURES FOR THE SMARTPHONE MARKET

THE SMARTPHONE MARKET consists of multiple categories, each having its own design goals and priorities. To meet these varying requirements, different approaches to RF front-end (RFFE) integration must be utilized. In the white paper, "RF Architecture Choices for Next-Generation Handset Designs," Qorvo discusses the differing RFFE integration requirements of two major smartphone categories: flagship and mid-tier phones. The white paper provides RFFE architecture examples of both.

Flagship phones and mid-tier (or entry level) handsets are decidedly different in terms of design priorities, price points, and development timelines. Flagship phones are premium designs that are intended for global use. They typically support six modes and more than 15 LTE bands, according to the white paper. Mid-tier handsets are intended for regional usage with some roaming capabilities. The white paper notes that a typical mid-tier phone supports five modes and between five and eight LTE bands.

Flagship phones demand a very high level of RFFE integration. To attract customers, manufacturers must pack high levels


of functionality and performance into an extremely slim handset. The RFFE must support a large number of bands to allow for global use. Another requirement involves support for multiple uplink and downlink carrier-aggregation (CA) combinations.

Qorvo's RF Fusion modules are designed for flagship phones. The RF Fusion portfolio consists of three different modules to cover the low-, mid-, and high-band spectrum regions. An illustration of the RF Fusion architecture is presented in the document.

Regional mid-tier handsets have different RFFE requirements in comparison to global premium handsets. Handset price is critical in this competitive market, meaning manufacturers generally aim to only include the RF components that are needed for each target region or operator. Design flexibility is also important, as handsets must be rapidly adapted for different regions. Qorvo's RF Flex portfolio of modules is intended for mid-tier smartphone manufacturers. These modules enable manufacturers to minimize handset costs. The white paper provides an illustration of the RF Flex architecture.

Qorvo Inc.
7628 Thorndike Road
Greensboro, NC 27409
(336) 664-1233
www.qorvo.com

Ultra-Wideband MMIC SPLITTER/COMBINERS



Single Unit Coverage as Wide as **2 to 26.5 GHz**

Models from **\$5⁵⁶**
ea. (qty. 1000)

THE WIDEST BANDWIDTH IN THE INDUSTRY IN A SINGLE MODEL!

Our new EP-series ultra-wideband MMIC splitter/combiners are perfect for wide-band systems like defense, instrumentation, and all cellular bands through LTE and WiFi. These models deliver consistent performance across the whole range, so you can reduce component counts on your bill of materials by using one part instead of many! They utilize GaAs IPD technology to achieve industry-leading performance, high power handling capability and efficient heat dissipation in a tiny device size, giving you a new level of capability and the flexibility to use them almost anywhere on your PCB! They're available off the shelf, so place your order on minicircuits.com today, and have them in hand as soon as tomorrow!

- Series coverage from 0.5 to 26.5 GHz
- Power handling up to 2.5W
- Insertion loss, 1.1 dB typ.
- Isolation, 20 dB typ.
- Low phase and amplitude unbalance
- DC passing up to 1.2A

 EP2K-Series, 4x4x1mm

 EP2W-Series, 5x5x1mm



Receiver ICs Blend Mixers, Synthesizers, and IF Amps

These densely packed integrated circuits surround mixer circuitry with many of the components that once had to be added to mixers in a typical receiver front end.

WIRELESS BASE STATIONS were once contained in large, climate-controlled spaces, but now they can be mounted anywhere. As wireless network service providers attempt to achieve coverage everywhere, the pressure is on base-station component suppliers to provide more functionality in smaller packages.

A pair of integrated circuits (ICs) from Analog Devices provides a solution by redefining the meaning of “mixer” in receiver front ends. Essentially, the ICs incorporate many of the components once added to a mixer in a receiver—such as local oscillators (LOs) and intermediate-frequency (IF) amplifiers—within the mixer IC itself. They make it possible to dramatically shrink a cellular base station while also providing software-defined-radio (SDR) flexibility to handle a number of different wireless standards.

The ICs in question are the models ADRF6612 and ADRF6614, both designed for RF ranges of 700 to 3,000 MHz, LO ranges of 200 to 2,700 MHz, and IF spans of 40 to 500 MHz. They work with low- or high-side LO injection and include an on-board phase-locked loop (PLL) and multiple low-noise voltage-controlled oscillators (VCOs), all packed within a 7- × 7-mm, 48-lead LFCSP housing. This level of integration and component density is enhanced by the diversity and programmability to support a number of different wireless standards in the small volumes required by modern microcells.

To appreciate the savings in space offered by these highly integrated mixer ICs, it may help to remember the front end of a cellular base-station receiver from around 2010 (Fig. 1). The dual-mixer architecture covered a bandwidth of approxi-


mately 1 GHz, requiring multiple components to handle the then cellular frequency range of 800 to 1,900 MHz. Frequency synthesis was provided by a separate PLL and narrowband VCO module that required a unique PLL loop filter for optimum performance. Dedicated VCO modules were used for each band of interest, adding to the required circuit-board area within the base station.

In addition, these discrete components were interconnected by low-impedance transmission lines, which contributed some signal loss. As a result, generous current was needed to drive the VCO output to a sufficient level for the mixer for low phase noise and noise figure under signal-blocking conditions.


Receiver ICs with integrated VCOs are not new. But achieving the wide bandwidths and low phase-noise levels required by multiple-carrier Global System for Mobile Communications (MC-GSM) wireless networks has been a challenge. The channel reuse scheme of GSM requires that receive LOs have extremely low phase noise, particularly at an alternate-channel offset frequency of 800 kHz (Fig. 2). If excessive phase noise at these alternate channels mixes with unwanted signals at the same 800-kHz offset, it can result in phase noise translated to the IF output, degrading system sensitivity.

Low VCO phase noise is typically achieved with a high-quality-factor (high-Q) tank and narrowband design. Frequency division can also reduce noise. By operating a VCO at an integer multiple of a receiver’s LO frequency, a 6-dB/octave reduction in phase noise is achieved by the subsequent division (Fig. 3). The phase-noise requirements for GSM in the 1,800- to 1,900-MHz band are extremely difficult—roughly twice as severe as those in the 800- to 900-MHz band.



In addition to low phase noise, modern base-station receiver designs must support the many modulation schemes currently used in wireless communications networks. In addition to GSM, other modulation schemes include wideband code-division-multiple-access (WCDMA) and Long Term Evolution (LTE) systems. Receiver designs often consist



1. The block diagram represents a typical cellular wireless base station from about 2010.




2. The channel reuse scheme requires the use of wide-bandwidth VCOs with low phase noise in GSM wireless systems to avoid performance degradation due to blocking.



3. Octave bandwidths are possible with this VCO circuit configuration.

of a number of different VCOs with moderate phase-noise performance levels configured so that they are combined to cover an octave bandwidth within the base station.

Once a number of VCOs have been configured to generate an octave bandwidth for the highest frequencies of operation, lower LO frequencies can be achieved by binary division. This approach was used in the ADRF6612 receiver mixer, where VCO fundamental frequencies span 2.7 to 5.6 GHz and two stages of frequency division realize LO frequencies from 200 to 2,700 MHz by dividing from 1 to 32. For applications that also include MC-GSM, the ADRF6614 receiver mixer includes two addi-



4. This LO signal chain is used in support of a wireless base-station receiver.

tional high-performance VCO cores to provide the LO frequencies needed for the 1,800- to 1,900-MHz GSM bands.

Since modern wireless microcells may not have the benefits of climate-controlled environments, components such as these receiver ICs must provide consistent, reliable performance over wide temperature extremes. To achieve specified performance over a wide operating temperature range, the PLLs and VCOs in the ADRF6612 and ADRF6614 ICs employ a number of calibration techniques.

For wide bandwidths with low noise, each VCO core employs an 8-b capacitive digital-to-analog converter (CDAC) that automatically selects the correct band (1 of 128) for a given LO frequency. Any variations in VCO tank amplitude are carefully monitored by the system, and the amplitude is adjusted using an automatic-level-control (ALC) system for optimum output amplitude. Each IC performs a calibration sequence any time the operating frequency is reprogrammed. This ensures that the selected band centers the tuning voltage for a VCO's tuning varactor diode in the optimum range to maintain the synthesizer in lock over the required operating temperature range.

The four VCO cores in each ADRF6612 and ADRF6614 ICs are positioned to ensure that their operating ranges provide suitable overlap for changing environmental conditions and device fabrication tolerances.

The cores will generally move frequency in the same direction for environmental and process variations, so there is enough overlap built in for the frequency synthesizer to always achieve locked conditions.

Once the calibration solution is determined, frequency should be maintained indefinitely; the tuning voltage range supports the required hold-in range. In time-division-duplex (TDD) systems, where the base station may change frequencies on a time-slot-to-time-slot basis, this operating time may be measured in microseconds. In frequency-division-duplex (FDD) systems, it might be necessary to maintain lock on a single frequency for years.

There is no allowable downtime at any point during the system operation of the ADRF6612 and ADRF6614 ICs. Thus, changes in temperature and component aging effects are covered by the varactor tuning-voltage range and frequency tuning sensitivity (Kv) of the VCO for potentially a 145°C temperature range. Each IC constantly monitors device temperature and adjusts the VCO bias as required.

The ADRF6612 and ADRF6614 ICs use a unique approach to minimize degradation of receiver sensitivity from spurious signal products. Using the synthesizer's integer mode with a tight loop filter results in low reference spurious products of less than -100 dBc. Minimal spurious signals are critical for modulation schemes such as MC-GSM. For LTE and other modulation schemes, or where fine frequency steps are required, the synthesizer can be operated in fractional-N division mode. The reference path incorporates a 13-b divider, and the integer and fractional paths each incorporate 16-b dividers for flexibility.

For applications where co-located, phase-tracked receive channels are required, such as in multiple-input, multiple-output (MIMO) systems, multiple ADRF6612 and ADRF6614 ICs can be cascaded in a daisy-chain manner to permit one unit acting as a master synthesizer to supply additional slave receivers through their external LO output and input ports, respectively. In this way, additional LO distribution amplifiers and their associated increases in phase noise can be minimized.

To support both high- and low-side LO injection, each IC's LO chain provides flexible signal processing (Fig. 4). Using integer division ratios of 1 to 32, low-side injection is possible even for the 700-MHz band with a high IF. The LO stages also provide a square-wave drive to the passive mixer cores over the full LO range from 200 to 2,700 MHz.¹

Modern wireless base-station receivers must operate in typically hostile signal environments. For example, any other in-band signals close in frequency to low-level input signals to the cellular receiver can act as blocking signals. In such a case, phase noise from the LO amplifier in the vicinity of the blocking signal is mixed into the IF output band directly on top of the desired signal. This increases the noise floor and reduces the signal-to-noise ratio (SNR) of the receiver—sometimes dramatically.

Since the blocking signal may be large (high power), it is important that both the VCO phase noise be extremely low, and the LO chain does not degrade the noise floor at the blocker offset. At these very high blocking levels, the receiver noise figure will eventually become dominated by the blocking signal and degrade according to the power level of the blocker.

In discrete implementations of the receive chain, it would be possible to introduce some filtering into the LO path to minimize the phase noise at the blocker offset coming from the VCO and LO distribution amplifiers. However, in an integrated front end, care must be taken to avoid additive phase noise in the LO chain.

The ADRF6612 and ADRF6614 ICs employ a high-gain LO chain and hard-limiting amplifiers to drive the LO chain into limiting. As each stage enters hard limiting, the small-signal gain of the LO chain that would otherwise increase phase noise is substantially reduced, minimizing noise-figure degradation under blocking conditions.

The noise fold-over from the blocking signal degrades the output noise spectrum of the receiver, and hence the receiver noise figure, by raising the output noise floor. The ADRF6612 and ADRF6614 receiver ICs are designed to withstand significant blocking signals with minimal degradation of receiver noise figure. Even with a +10-dBm input blocking level, the receiver's noise figure is only degraded by 3.2 dB at 10 MHz offset from the carrier, even though the conversion gain is compressed by 1 dB at that extreme blocking level.

The high level of integration in these receiver ICs has enabled significant performance improvements and savings in dc power for modern wireless base-station designers. The ICs feature a technique that simultaneously optimizes the RF and IF stages surrounding the on-chip mixer.²⁻⁴ **mw**

Editor's Note: This is an abbreviated version of the full article, available with additional performance data, at [mwrf.com](http://www.mwrf.com).

ANALOG DEVICES Inc., 804 Woburn St., Wilmington, MA 01887; (781) 329-4700, www.analog.com

ACKNOWLEDGMENTS


With the increased level of integration inherent in complete receiver chains comes a much larger development team. While it isn't possible to list all of the people that contributed to this work, the authors take great pleasure in acknowledging the efforts of the following industry experts: Kurt Fletcher and Dominic Mai spent many hours implementing an excellent layout while maintaining symmetry and avoiding unwanted couplings. Vincent Bu worked to develop the necessary packaging with our vendors. Susan Stevens maintained the excellent working relationship with our external foundry partner. Craig Levy and Rachana Kaza developed the production test capability for these parts. Wendy Dutile, Ed Gorzynski, and Chris Norcross all participated in the extensive prototyping of the test circuitry. Mark Hyslip coordinated the business aspects of successfully bringing this project together. The authors would like to dedicate this work in the memory of our colleague, Edward J. Gorzynski.

REFERENCES

1. M. Goldfarb, R. Martin, and E. Balboni, "Novel Topology Supports Wideband Passive Mixers," *Microwaves & RF*, October 2011, pp. 90.
2. "Apparatus and Method for a Wideband RF Mixer," US Patent 8,571,511 (A Technique for Optimizing the Performance of a Wideband Passive RF Mixer through the Employment of a Unique Multi-frequency Tuning Topology).
3. ADRF6612 datasheet, Analog Devices Inc. © 2014-2016, <http://www.analog.com/media/en/technical-documentation/data-sheets/ADRF6612.pdf>
4. ADRF6614 datasheet, Analog Devices Inc. © 2016, <http://www.analog.com/media/en/technical-documentation/data-sheets/ADRF6614.pdf>

ULTRA-REL™ CERAMIC MMIC AMPLIFIERS

10 MHz to 7 GHz



Low NF from 0.5 dB High IP3 up to +42 dBm Low DC current 65 mA **\$7⁴⁵**
from ea. (qty 20)

When failure is not an option! Our CMA family of ceramic MMIC amplifiers is expanding to meet your needs for more critical applications. Designed into a nitrogen-filled, hermetic LTCC package just 0.045" high, these rugged models have been qualified and are capable of meeting MIL standards for a whole battery of harsh environmental conditions:

Qualified for: (see website for complete list and details)

Gross and Fine Leak	HTOL (1700 hours @ +105°C)
Mechanical Shock	Steam Aging
Vibration	Solder Heat Resistance
Acceleration	Autoclave
PIND	And More!

*Gross leak only

Robust performance across wide bandwidths makes them ideal for military and defense applications, hi-rel instrumentation, and anywhere long-term reliability adds bottom-line value. Go to minicircuits.com for all the details today, and have them in your hands as soon as tomorrow!

Electrical Specifications (-55 to +105°C)



3 x 3 x 1.14 mm

Model	Freq. (GHz)	Gain (dB)	P _{out} (dBm)	IP3 (dBm)	NF (dB)	DC (V)	Price \$ ea. (qty 20)
CMA-81+	DC-6	10	19.5	38	7.5	5	8.95
CMA-82+	DC-7	15	20	42	6.8	5	8.95
CMA-84+	DC-7	24	21	38	5.5	5	8.95
CMA-62+	0.01-6	15	19	33	5	5	7.45
CMA-63+	0.01-6	20	18	32	4	5	7.45
CMA-545+	0.05-6	15	20	37	1	3	7.45
CMA-5043+	0.05-4	18	20	33	0.8	5	7.45
CMA-545G1+	0.4-2.2	32	23	36	0.9	5	7.95
CMA-162LN+	0.7-1.6	23	19	30	0.5	4	7.45
CMA-252LN+	1.5-2.5	17	18	30	1	4	7.45

RoHS compliant



Design, Spectrum Challenges Create Different View of Power Sensors

As higher frequencies become more common, power sensors must also provide the necessary measurement capabilities for current and future applications.

ENGINEERS SELECT POWER sensors based on their specific application and how the various sensor designs—thermal or diode—fit their measurement needs. That evaluation process is changing as more designs utilize higher frequencies due to RF spectrum overcrowding, high-bandwidth services, 5G backhaul, IEEE 802.11ad, WirelessHD, and other technologies.

To understand where power sensor trends are going, it is important to realize the pros and cons of each sensor type. A thermocouple sensor has a very good linear relationship between the changes in voltage and power, making it possible to achieve highly accurate power readings. Another benefit is that the thermocouple elements typically have a good resistance to electrostatic discharge (ESD) or other transient burnout. Finally, thermocouple detectors measure root-mean-square (RMS) power and are therefore modulation-independent. They will provide accurate average power readings of almost any signal type.

These accurate readings come with some drawbacks—chief among them, much slower measurement speeds. They also have rise times in the millisecond range, so they are not suitable for measuring peak or pulse power. Thermocouple sensors also have a higher noise floor, which limits the dynamic range to only around -30 or -35 dBm to $+20$ dBm in typical implementations.

Engineers who need to make true-RMS measurements across a wider dynamic range often select diode sensors (Fig. 1). The measurement speed of diode sensors is limited by their ability to process the data. With today's sensors having better processing technologies, diode sensors now feature measurement speeds in the thousands and tens of thousands of readings per second. They typically can measure power down to -40 or -50 dBm.

RADIO RECEIVERS

To measure signals of lower power, many engineers will use radio receivers (mostly in spectrum analyzers), which have much lower noise compared to thermal or diode sensors. These receivers can have noise floors well below -100 dBm, so engineers will be able to find and measure many signals that would never register on a thermal or diode sensor.

The major disadvantage is a high price tag. Most radio receivers are only available in spectrum analyzers, so they are usually restricted to the lab, which adds to the budget, and a wider breadth of measurements is required. Radio receivers also will not have the same amplitude accuracy as traditional power meters, generally achieving around ± 2 dB.



1. Diode sensors are commonly used to perform measurements.

HIGHER-FREQUENCY CHALLENGES

Just as the rollout of LTE and increasing use of modulated signals factored in the power sensor's evolution, so will current designs at higher frequencies. At millimeter-wave bands, power tends to fade due to propagation and transmission losses. For most current power sensors, conducting accurate power measurements at these higher frequencies and lower power levels are problematic.

USB &
Ethernet

POWER SENSORS

Turn Smart Power Sensors into Low-Cost RF Power Meters!



1 to 8000 MHz -45 to +20 dBm from **\$745** ea. qty. (1-4)

Mini-Circuits' smart RF power sensors turn almost any Windows® or Linux® based computer into a low-cost testing platform for all kinds of RF components and systems. To give you even more capabilities, our lineup now features models for high-sensitivity measurement of CW, multi-tone and modulated signals at levels as low as -45 dBm!

With 8 different models in stock offering USB and Ethernet control options, measurement speeds as fast as 10 ms*, dynamic range options from -45 to +20 dBm, and measurement capability for continuous wave and modulated signals, chances are, we have a power sensor to meet your needs and fit your budget!

Our user-friendly GUI provides a full range of measurement tools including measurement averaging, time-scheduled measurements, multi-sensor support, and measurement applications supporting RF testing of couplers, filters, amplifiers and more! View data and graphs on-screen or export to Excel® for reporting and data analysis.

All Mini-Circuits power sensors fit in your pocket and come supplied with all the accessories you need for immediate use right out of the box. Visit minicircuits.com and place your order today for delivery as soon as tomorrow.

RoHS compliant

Model	Power Measurement	Frequency MHz	Dynamic Range (dBm)	Control Interface	Price \$ ea. (Qty1-4)
NEW! PWR-6LRMS-RC	True RMS	50 to 6000	-45 to +10	USB & Ethernet	1595.00
NEW! PWR-6LGHS	CW	50 to 6000	-45 to +10	USB	895.00
NEW! PWR-6RMS-RC	True RMS	50 to 6000	-35 to +20	USB & Ethernet	1595.00
PWR-4RMS	True RMS	50 to 4000	-35 to +20	USB	1169.00
PWR-2.5GHS-75 (75Ω)	CW	0.1 to 2500	-30 to +20	USB	795.00
PWR-4GHS	CW	0.009 to 4000	-30 to +20	USB	795.00
PWR-6GHS	CW	1 to 6000	-30 to +20	USB	745.00
PWR-8GHS	CW	1 to 8000	-30 to +20	USB	869.00
PWR-8GHS-RC	CW	1 to 8000	-30 to +20	USB & Ethernet	969.00
PWR-8FS	CW	1 to 8000	-30 to +20	USB	969.00

*Measurement speed as fast as 10 ms for model PWR-8-FS. All other models as fast as 30 ms.

Excel is a registered trademark of Microsoft Corporation in the US and other countries.

Neither Mini-Circuits nor Mini-Circuits Power Sensors are affiliated with or endorsed by the owners of the above-referenced trademarks.




With Power Master, a field technician can define the frequency channel in which to measure power, focusing on the signals of interest or identifying specific interference in nearby channels.

Being able to measure power down to a level such as -90 dBm will result in greater product/system performance verification of high-frequency devices in production environments. For example, chipmakers will verify designs during research and development using a radio receiver or spectrum analyzer to obtain measurements down to -100 dBm. These instruments are too costly to use during manufacturing, which means power sensors measuring down to -40 dBm maximum are used. New cost-effective solutions are being developed that can measure power down to -90 dBm while conducting the necessary on/off measurements associated with manufacturing.

FREQUENCY SELECTABILITY

When it comes to field testing, power sensors that are not frequency-dependent and have limited dynamic range are not as effective, owing to the overcrowded RF spectrum where unintended signals such as spurs, harmonics, and interference can impact power readings. Power sensors that let users zero in on their signal of interest enable measurements such as channel power, adjacent channel power (ACP), and spur/harmonic suppression to be conducted with greater efficiency and confidence.

One example of this new wave of instrument is the MA24507A Power Master millimeter-wave power analyzer from Anritsu (www.anritsu.com) (Fig. 2). Utilizing Anritsu's ShockLine nonlinear-transmission-line (NLTL) technology, this USB-powered, frequency-selectable RF power sensor combines a power measurement range of -100 to $+10$ dBm with fast measurement speeds in a compact, lightweight housing.



2. This power analyzer covers a frequency range of 9 kHz to 70 GHz.

Unlike thermal and diode-based sensors, Power Master also gives users the ability to define the frequency of the signal to measure. For example, when field testing signal strength for wireless backhaul networks, a diode or thermal power sensor will not differentiate the intended RF signal from the other signals present at the input, which could potentially spoil the measurement.

With Power Master, a field technician can define the frequency channel in which to measure power, focusing on the signals of interest or identifying specific interference in nearby channels. In the lab, an engineer verifying RF circuit designs can use Power Master to troubleshoot unexpected signal behavior caused by a dirty local oscillator (LO), bad components, or outside signal interference. With the ability to measure power below -90 dBm, Power Master enables more over-the-air (OTA) testing that would otherwise be difficult to do with a bulky spectrum analyzer or power meter with limited power range.

CONCLUSION

The ability to conduct power measurements will become increasingly important as more designs climb to high frequencies to accommodate bandwidth. To address many of these applications—including millimeter-wave designs, IEEE 802.11ad, WirelessHD, and 5G backhaul—power sensors will need to be able to efficiently conduct the necessary tests at lower power levels. New design architectures will continue to be developed to meet these needs. **mtw**

RF LDMOS Transistors Power Smaller Base Stations

These high-power transistors boast a 30% savings in board space compared to their LDMOS predecessors.

SMALLER IS OFTEN better, but miniaturizing circuits that handle high power levels poses serious challenges for some engineers, such as designers of RF/microwave power amplifiers (PAs). Wireless service providers want better coverage for their customers by way of smaller (yet more powerful) base stations. Circuit designers are challenged, in turn, to create PAs with increased performance, but smaller footprints, cost, and power consumption than previous models.

Fortunately, advances at the device level, based on silicon LDMOS semiconductor technology, along with enhanced packaging and other improvements, make it possible to create smaller and better PAs for the ever-smaller cells of wireless communications networks.

Reducing operating expenses has always been one of the most important challenges for wireless carriers, and it has become increasingly important as large numbers of small cells complement traditional macrocells, increasing their overall infrastructure overhead. Consequently, carriers today must consider every possible cost-reduction solution, including the efficiency of all elements of the transmission path, and especially RF power transistors and amplifiers.

For example, increasing transistor and amplifier efficiency reduces costs by requiring less current consumption to deliver a specific RF output level. This can potentially reduce the number of transistors—and thus, board space devices—required to achieve it.

The third generation of the Airfast LDMOS device family (see figure) from NXP Semiconductors is tailored to meet this challenge by providing high efficiency and gain when employed in asymmetrical Doherty amplifiers. Compared to second-generation Airfast 2 devices, these newest power transistors deliver as much as 4% higher efficiency (53% final-stage efficiency and as much as 50% lineup efficiency). The devices also feature a 20% improvement in thermal performance, up to 90-MHz full-signal bandwidth, and as much as 30% space savings compared to earlier Airfast power transistors.

The first members of the third-generation Airfast LDMOS RF power transistors collectively span 1,805 to 2,690 MHz, making it possible to cover an entire cellular band with a single device. They are also the first Airfast products to be housed in



The A3T18H360W23S Airfast 3 LDMOS RF power transistor delivers peak RF output power of +55.9 dBm, gain of 17.5 dB, and PAE of 52% efficiency.

air-cavity plastic packages. These housings combine excellent electrical performance with low thermal resistance for effective dissipation of heat.

The initial third-generation device members include four transistors covering a frequency range of 1,805 to 2,690 MHz in bands with as much as 89 W output power. The lower-frequency devices, models A3T18H450W23S and A3T18H360W23S, are suitable for use from 1,805 to 1,880 MHz, frequencies popular for Fourth-Generation (4G) Long Term Evolution (LTE) cellular base-station deployment. The A3T18H450W23S delivers 89 W average output power with 17.2-dB gain and 51% power-added efficiency (PAE). The A3T18H360W23S has average output power of 56 W with 17.5-dB gain and 53% PAE.

One design goal in developing these new transistors was to reduce the “solution size” resulting from the use of the device, or the number of transistors required (in an amplifier) for specific levels of output power, efficiency, and instantaneous bandwidth. In the past, carriers could use only about 40 MHz of the full frequency range of a device, but the new transistors make it possible to cover their full signal bandwidth without sacrificing efficiency and power.

Earlier cellular base-station amplifier solutions may have required two or three transistors to achieve required performance levels for a wide bandwidth, but this can now be accomplished with these smaller devices. The reduction in size, without sacrificing power or thermal efficiency, was accomplished through advances in packaging, the use of an envelope termination inside the package, changes to device design, and improvements to internal package components. **mw**

NXP SEMICONDUCTORS, 1300 Alma School Rd., Chandler, AZ 85224; www.nxp.com/RF.

Wideband Signal Analyzer Captures 16 kHz to 26.5 GHz

For applications requiring long periods of wideband signal capture, this analyzer can grab 800 MHz at a time—from audio frequencies through high microwave signals.

COMMUNICATIONS SIGNAL BANDWIDTHS are growing wider with time, as users find needs for sending more voice, video, and data through wired and wireless systems. On the military side, radar and electronic-warfare (EW) systems also employing wider bandwidths. One of the challenges for system developers in these areas is to perform wideband signal capture, often for long time periods, in search of transient events.

Fortunately, a test solution was recently introduced by Tektronix (www.tek.com): the RSA7100A wideband signal analyzer. It offers a standard real-time capture bandwidth of 320 MHz, which can be optionally extended to as wide as 800 MHz, across a wide frequency range of 16 kHz to 26.5 GHz. The analyzer, with its companion controller and supporting software, is well-suited for wideband communications design, spectrum management, and advanced radar and EW system testing.

For those who don't need the wide frequency range, the RSA7100A also comes in a version covering 16 kHz to 14 GHz, with the same options for real-time analysis bandwidth. Both lower- and higher-frequency versions tune with 0.001-Hz resolution and are available with a front-end preamplifier for increased signal sensitivity from 10 MHz to 3.6 GHz.

The RSA7100A operates both by displaying measured spectrum in real time and by analyzing data from measurements taken over time. It is actually a measurement system (see figure), teamed with the CTRL7100A controller specially designed for the signal analyzer. Separating the analyzer from the computing engine allows sophisticated signal record, playback, and graphical visualization of signal data.

The controller enables real-time DPX operation with simultaneous streaming of measured data to RAID (redundant array of independent disks) memory. It runs on a Windows-based OS, including generous RAM and removable hard-disk storage for flexibility.

The broadband real-time analyzer employs a stable 10-MHz reference oscillator to deliver stable performance and high-frequency accuracy. Included with the instrument is a BNC connector for hooking up an external frequency reference source. The single-sideband (SSB) phase noise with the internal reference offers a quite respectable -128 dBc/Hz offset 1 kHz from 1-GHz carrier, -134 dBc/Hz offset 10 kHz from the same carrier, and -142 dBc/Hz offset 1 MHz from a 1-GHz carrier.



The RSA7100A wideband signal analyzer is available in versions covering 16 kHz to either 14.0 or 26.5 GHz, with capture bandwidths as wide as 800 MHz.

RF SWITCH MATRICES

DC to 18GHz



USB & Ethernet Control Options models from **\$405^{ea.}**

- 0.25 dB Insertion Loss
- 85 dB Isolation
- 1.2 VSWR
- up to 10W Power Handling
- Extra-Long Switch Life
Up to 100 Million Cycles*
- Switch Cycle Counting Feature
with Automatic Calibration Alerts
- User-Friendly GUI and DLLs Included
- Compatible with Most Third Party Lab Software†
- Small size fits in your Laptop Case!
- Available from Stock

Visit minicircuits.com for detailed model specs, application notes, and more!
Place your order today for delivery as soon as tomorrow!

* Switches protected by US patents 5,272,458; 6,650,210; 6,414,577; 7,843,289; and additional patents pending.
† See data sheet for a full list of compatible software.



For those who don't need the wide frequency range, the RSA7100A also comes in a version covering 16 kHz to 14 GHz, with the same options for real-time analysis bandwidth. Both lower- and higher-frequency versions tune with 0.001-Hz resolution and are available with a front-end preamplifier for increased signal sensitivity from 10 MHz to 3.6 GHz.

The instrument's well-matched input port exhibits VSWR of less than 1.50:1 to 14 GHz and less than 1.70:1 to 26.5 GHz. As much as +30 dBm input power can safely be fed to the input port. Furthermore, several attenuators are built into the analyzer's input signal path for controlling input power levels.

Attenuation of 0 to 100 dB is available in 1-dB steps from 16 kHz to 3.6 GHz, and attenuation from 0 to 75 dB can be set in 5-dB steps from 3.6 to 26.5 GHz. In addition, the analyzer's front end includes a fixed lowpass filter and tunable bandpass preselector filters for image rejection.

Reference levels can be set from -170 to +40 dBm in 0.1-dB steps. For the frequency range of the input preamplifier (10 MHz to 3.6 GHz), the amplitude accuracy (at +25°C) is ± 0.13 dB without the preamplifier and ± 0.14 dB with the preamplifier.

The typical displayed average noise level (DANL) without the preamplifier is -156 dBm/Hz from 100 MHz to 1.7 GHz, -154 dBm/Hz from 1.7 to 2.8 GHz, -151 dBm/Hz from 2.8 to 3.6 GHz, -156 dBm/Hz from 3.6 to 14 GHz, -152 dBm/Hz from 14 to 24 GHz, and -150 dBm/Hz 24 to 26.5 GHz. With the preamp turned on, the typical DANL is -164 dBm/Hz from 50 MHz to 1.7 GHz and -162 dBm/Hz from just beyond 1.7 to 3.6 GHz.

The RSA7100A offers advanced frequency- and time-domain signal recording and playback capabilities and functions with internal or external triggers. It can capture

real-time events as short as 700 ns in the frequency domain and as short as 4 ns in the time domain, with ± 4 -ns delay uncertainty.

Triggering functions include Power Level within Span, to look for signals at specific power levels, and Frequency Mask triggering, when searching for signals within a certain frequency range. Power-based triggering can be performed for levels from -170 to +30 dBm, with the level set with 0.1-dB resolution.

The RSA7100A is a powerful measurement tool for any users who are concerned about broadband measurements or signal activity within a given environment. Together with its controller, the analyzer is meant to operate with a pair of the company's software packages, DataVu-PC and SignalVu-PC.

DataVu-PC provides the capability to mark events of interest, export waveforms to other formats, and perform pulse analysis and export the data into Pulse Descriptor Word (PDW) file format for further analysis. SignalVu-PC orchestrates real-time spectrum and vector signal analysis, with a host of options for full-featured pulse analysis and analysis of signals with 27 different modulation formats. P&A: \$135,000 and up. [mtw](#)

TEKTRONIX INC., 114150 SW Karl Braun Dr., P.O. Box 500, Beaverton, OR 97077; (800) 833-9200, www.tek.com



HF Amplifiers

We stock the complete parts list and PC boards for the Motorola amplifier designs featured in their Application Notes and Engineering Bulletins

AN779L (20W)	AN758 (300W)
AN779H (20W)	AR305 (300W)
AN762 (140W)	AR313 (300W)
EB63A (140W)	EB104 (600W)
EB27A (300W)	AR347 (1000W)

NEW! NEW! NEW!

We stock the new rugged FREESCALE 1KW transistor and parts for the 2M and 88-108MHz amplifier designs



HF Broadband RF Transformers
2 to 30MHz



RF Transformers Type "U"
2 to 300MHz



HF Power
Splitter / Combiners
2 to 30MHz



**Communication
Concepts, Inc.**

www.communication-concepts.com

508 Millstone Drive,
Beavercreek, OH 45434-5840
Email: cci.dayton@pobox.com
Phone (937) 426-8600
FAX (937) 429-3811



2 Port	
PSC-2L	600W PEP
PSC-2H	1000W PEP
4 Port	
PSC-4L	1200W PEP
PSC-4H	2000W PEP
PSC-4H5	5000W PEP

Robust Switch Matrix Eases Multichannel Testing

This rack-mountable, 20 × 6 nonblocking switch matrix provides the performance and flexibility to speed and simplify connections to multiple test systems.

MODERN COMPONENTS AND subsystems—whether in commercial or military applications—must often be tested for a multitude of different characteristics, often requiring disparate test systems to make the required measurements. This can be done by loading a device under test (DUT) into a test fixture and physically moving it from test system to test system.

However, there is an easier way: Use a switch matrix with the capacity and performance to make the connections between the DUT and the different test systems electronically, such as the model ZT-20X6NB 20 × 6 nonblocking switch matrix from Mini-

Circuits (www.minicircuits.com). With a bandwidth of 600 to 6,000 MHz and enough ports to connect a slew of test instruments/systems at one time, it even includes a front-panel touchscreen for easy on-the-spot control.

Better still, the ZT-20X6NB boasts enough digital interfaces for connection to almost any PC. This switch matrix has been built to last, with excellent long-term reliability and minimal degradation in electrical performance.

For those who may have considered Mini-Circuits “only” a supplier of cost-effective RF/microwave components, the ZT-20X6NB (see figure) shows another side of the firm’s engineering capabilities. Housed in a solid aluminum 5U-high, 19-in.-wide rack-mount chassis, this subsystem is designed to take on the everyday punishment of high-volume measurements.

Removing the cover reveals a true high-frequency subsystem design and layout, containing many of the company’s components. Peering into the heart of the unit shows great attention to detail regarding component placement, coaxial interconnections, and thermal management. The fan-cooled switch matrix can handle input-signal power levels to several watts (+36 dBm) to accommodate a wide range of communications components and systems testing through 6 GHz.

The ZT-20X6NB creates bidirectional signal paths, with an almost unlimited number of port-to-port combinations. These can be set from the front panel or programmed using the ActiveX and .NET APIs provided with the switch.

The front panel is well-organized, with RF/microwave interconnections made by means of Type-N female connectors that are all accessible from the front panel. The connectors are organized into “A” and “B” ports. The six B ports can be connected to any combination of the 20 A ports without compromising the

expected switch-matrix performance characteristics, such as isolation and insertion loss.

In fact, all six A ports can be combined to the same B port simultaneously, as might be done for multiple-input, multiple-output (MIMO) system testing. The switch matrix has both USB and Ethernet control interfaces for remote control and programmability via an external PC with internet access.

In terms of performance, the ZT-20X6NB switch matrix is rated for +36 dBm maximum average power into any A port and +26 dBm maximum average power into any B port. The typical return loss is 12 dB across the full frequency range. Typical isolation is 80 dB between any two A ports; 30 dB between any pair of B ports connected to the same A port; and 80 dB for any pair of B ports when connected to different A ports.

The ZT-20X6NB 20 × 6 switch matrix is a well-built signal-routing solution for automated testing of multiple communications channels with a number of test systems. The unit measures 19.00 × 8.73 × 20.18 in. It is designed for 90- to 260-V ac, 47- to 63-Hz supplies. **mw**



The rack-mountable ZT-20X6NB 20 × 6 switch matrix, with a frequency range of 600 to 6,000 MHz, covers the bulk of the world’s telecommunications bands for programmable signal routing in automated test applications.

MINI-CIRCUITS, P.O. Box 350166, Brooklyn, NY 11235-003; (718) 934-4500, www.minicircuits.com.

System Sets Standards for 1/f Noise Measurements

Accurate device noise models and noise-analysis performance start with on-wafer measurements capable of capturing extremely low device noise currents.

NOISE IMPACTS HIGH-FREQUENCY systems in many ways, such as transmission distortion and limiting receiver sensitivity of low-level signals. But to accurately analyze noise via modeling with SPICE and other software simulation programs, it must be measured.

The 9812DX wafer-level 1/f noise characterization system from ProPlus Design Solutions Inc. (www.proplussolutions.com) provides new insights into device-level noise with unparalleled 1/f noise measurement speed, resolution, and accuracy. Such wafer-level measurements are critical in various scenarios—for example, semiconductor foundries may seek to enhance the noise performance of a semiconductor process, especially as device geometries shrink to achieve higher-frequency and higher-data-rate operation.

The 9812DX 1/f noise characterization system (see figure) is actually an enhanced version of the company's widely used 9812D 1/f noise measurement system. It features increased resolution and measurement speed (as much as 10 times greater speed and resolution compared to the older system) to accommodate the growing complexity and shrinking device geometries of advanced integrated-circuit (IC) designs.

Of course, the new system isn't just for foundries: It can also provide invaluable device data for foundry customers looking to improve a process for lower noise levels. In addition, it can give circuit designers more accurate device noise models for evaluating the performance and quality of a foundry process, and for performing accurate noise analysis of their devices.

The noise-measurement system is suitable for process quality monitoring, statistical noise analysis, and studying the effects of process modifications on device and integrated-circuit (IC) noise performance. It speeds and simplifies the collection of device data at different bias points and various other operating conditions, including across multiple die for fast statistical noise data characterization.

The 9812DX offers a 10-MHz bandwidth, starting at 0.03 Hz for analysis of true wafer-level, low-frequency noise. It can measure the noise of dc current as low as 0.1 nA and as high as 200 mA at bias levels up to 200 V. The improvement in noise performance over the older system results in noise measurement resolution of $1 \times 10^{-27} \text{ A}^2/\text{Hz}$.

The enhanced performance results from an improved system architecture, with redesigned critical subsystem



The 9812DX 1/f noise characterization system provides new levels of speed, accuracy, and resolution for on-wafer active and passive device noise measurements.

blocks and carefully selected system components. The test system is designed with stable, high-performance components, including a low-noise-voltage amplifier (LNA) with a frequency range of 0.03 Hz to 10.0 MHz and 0.65-nV noise at 5 kHz. It also features low-noise-current LNAs ranging from 0.03 Hz to 10 MHz, and with various resolution and bandwidth options.

The 9812DX 1/f noise characterization system incorporates programmable bias filters, and a large number of input/output load resistors for different measurement setups. It also has built-in electrostatic-discharge (ESD) protection for a device under test (DUT), and a built-in GPIB card for controlling additional programmable test instruments.

Another feature is its built-in dynamic signal analyzer (DSA) with large on-board memory and multithreaded processing for improved performance and reduced cost. This eliminates the need for expensive external signal-processing equipment and reduces upfront investment and risk.

Finally, the company supports the noise analysis with a number of highly effective modeling and simulation tools, including NanoSpice—a generic parallel SPICE simulator for simulations of extremely dense analog circuits with large numbers of active and passive devices. [mtw](http://www.mtw.com)

ProPLUS DESIGN SOLUTIONS INC., 2025 Gateway Pl., Ste. 130, San Jose, CA 95110; (408) 459-6129, www.proplus-solutions.com.



\$139⁹⁵
from (qty. 1-9)
 Rugged connectorized package
 0.75 x 0.74 x 0.46"

\$11⁹⁵
from (qty. 20)
 3x3mm MMIC

0.5 to 8 GHz

LOW NOISE AMPLIFIERS

IN/OUT Termination Matched!

Low noise, high dynamic range, high output power, and flat gain from 0.5 to 8 GHz, all in a single amplifier! Mini-Circuits' popular ultra-wideband LNAs are now available in both a 3x3mm QFN for your PCB and a rugged connectorized package to facilitate your cable assemblies. Both models are matched over the 0.5 to 8 GHz range*, making them a snap to use for sensitive, high-dynamic-range receivers, instrumentation, defense systems, LTE, WiFi, S-Band and C-Band radar, SatCom and more! They're available off the shelf for a great value, so visit minicircuits.com and place your order today for delivery as soon as tomorrow!

*See datasheet for suggested application circuit for PMA3-83LN+

†Flatness specified over 0.5 to 7 GHz

FEATURES:

- **Low Noise Figure, 1.3 dB**
- **High Gain, 21 dB**
- **Excellent Gain Flatness, ± 0.7 dB[†]**
- **High IP3, +35 dBm**
- **High POUT, +23.2 dBm**



NYU WIRELESS Drives Next-Generation Technology

Students and faculty at NYU WIRELESS are fervently working to create the wireless technology of the future.

THE NEW YORK UNIVERSITY (NYU) WIRELESS (<http://wireless.engineering.nyu.edu>) academic research center in Brooklyn, N.Y., is at the forefront of tomorrow's wireless technology. Led by its founding director, Professor Ted Rappaport, NYU WIRELESS is focused on next-generation 5G wireless networks, with millimeter-wave technology being a major research area. NYU WIRELESS combines NYU's Tandon School of Engineering, School of Medicine, and Courant Institute of Mathematical Sciences. Among its 16 industrial affiliates are Keysight Technologies (www.keysight.com) and National Instruments (NI; www.ni.com).

Although the center is known for its 5G research, a conversation with Rappaport during a recent visit to the NYU WIRELESS facility revealed that he is actually looking beyond that. He said his goal is to have leaders of "where the market will be." Looking into the future, Rappaport said he believes that we will someday have true three-dimensional (3D) video. He explained how NYU WIRELESS is investigating frequencies above 100 GHz into the sub-terahertz region.



2. Here, Professor Rappaport and students are gathered in the channel-sounding lab.



1. This photo shows the transmitter box used for channel-sounding measurements.

The visit included a tour of two of the facility's labs. The first stop was the channel-sounding lab (Figs. 1 and 2). "We have brought our equipment to locations in both Brooklyn and Manhattan to do measurements in the urban environment," said George MacCartney Jr., an engineering Ph.D. candidate. "We elevate the transmitter to a lamppost level, which is expected for millimeter-wave access points in the future."


"Conducting measurements in different environments and scenarios allows us to create an overall physical model," he continued. "Other people can then use our model instead of having to go out into the field and conduct their own measurements. We rotate the antennas along the azimuth and elevation planes at many different angles in order to gain an omnidirectional sense of the environment." Interestingly enough, the antennas can actually be positioned with a PlayStation 3 controller, which is remotely controlled via LabVIEW.

In terms of future goals, MacCartney Jr. added, "We are hoping that future measurement systems utilize phased arrays that can electronically steer the beams. This will allow very fast measurements to be performed." Moreover, new students are examining frequencies above 100 GHz.



VCOs & SYNTHESIZERS

THE INDUSTRY'S SOLID SOURCE



LIFETIME PRODUCT SUPPORT!

State-of-the-Art Design Capability. Thousands of Models In Stock.

Looking for replacement solutions for competitor VCOs & Synthesizers?

Whether you need a second source for end-of-life parts or you're working on a new design, Mini-Circuits is here to support you with thousands of models in stock and decades of design experience. Our VCOs and synthesizers don't just give you industry-leading performance, world-class quality, and fast, easy engineer-to-engineer application support whenever you need it. They also give you the peace of mind that comes with our promise of reliable product supply through the lifetime of your system.

Our engineers will work with you to find a solution from our extensive library of existing designs or develop a custom design to meet your exact requirements. Visit minicircuits.com to explore our catalog, or send your requirements to apps@minicircuits.com today!

- VCOs from 3 to 7000 MHz
- Synthesizers from 56 to 7800 MHz
- Wide Variety of Coaxial and Surface Mount Packages
- Over 5300 Catalog Models and Engineering Designs
- Over 175,000 Units in Stock!
- Custom Designs in 3 to 4 Weeks



According to Rappaport, “Our equipment and our students—past and present—proved that millimeter waves would work. We went out to New York City and proved that you don’t need to have line-of-sight (LOS) for millimeter-waves—everyone thought you did. This was driven by our rotational mechanical systems.

“We take the knowledge of the radio channel and put it into software, which can be used by others,” he continued. “Over 5,000 people in engineering companies around the world are using the NYUSIM channel simulator, which is freely downloadable (<http://wireless.engineering.nyu.edu/5g-millimeter-wave-channel-modeling-software>).”


The NYUSIM channel simulator, an open-source 5G channel model simulator, is a result of measurements along with 5G millimeter-wave channel models that have been developed from 2 to 73 GHz. NYUSIM can be used to generate spatial and temporal wideband channel impulse responses.

The next stop of the tour was the lab that is investigating phased arrays (Fig. 3). According to Aditya Dhananjay, a post-doctoral research fellow, as well as the co-founder and president of MilliLabs (www.millilabs.com), “One of the focal points of our research is tunable millimeter-wave communications. With millimeter-wave systems, highly directional antenna beams are needed to enable communication between a transmitter and a receiver.

“In the lab, steering the beam in different directions can be achieved by rotating mounted antennas,” he continued. “But in reality, that’s not how you steer beams because they need to be steered on the order of microseconds. Steering beams on the order of microseconds requires phased arrays. We are one of the only schools with access to a phased-array system in our lab. We work with equipment from NI and Keysight.

“We also have millimeter-wave systems for data links,” added Dhananjay. “This capability allows us to send real data between a transmitter and a receiver instead of just measuring wireless propagation. We have also developed techniques to do phase-noise correction. At higher frequencies, oscillators tend to behave far worse than oscillators at lower frequencies. The techniques we have developed help to overcome hardware imperfections. We are also building millimeter-wave emulators.”

To summarize, NYU WIRELESS is clearly in the driver’s seat when it comes to 5G and millimeter-wave research. We can expect to see many more developments in the days ahead. On that note, the next Brooklyn 5G Summit (<http://b5gs.com>) will take place April 19-21, 2017. **mw**



3. This photo shows the phased-array system being used.

microwaves&rf DirectConnection

TO ADVERTISE, CONTACT A
SALES REPRESENTATIVE
at <http://mwrf.com/advertising>

**GaN Transistor GP2001
Demo Amp TB256**

20-3000MHz



28VDC

5W

10dB

RF

polyfet rf devices

www.polyfet.com

TEL (805) 484-4210

Your
Power
MOSFET
People

Flexible Cables Test Tight Spots from DC to 18 GHz

Mini-Circuits' ULC-2FT-NMMN+ is an ultra-flexible, 2-ft.-long test cable with stainless-steel male Type N connectors for use from DC to 18 GHz.

It features rugged construction with strain relief for long operating lifetime. The RoHS-compliant cable achieves 0.75-in. static bend radius and 2.0-in. dynamic bend radius to accommodate challenging mating configurations. The test cable features excellent shielding effectiveness (SE) through a triple-shielded design, with low insertion loss of typically 0.7 dB from DC to 6 GHz and 1.6 dB to 18 GHz. The return loss is better than 17 dB across the full frequency range and typically better than 25 dB. The test cable handles operating temperatures from -55 to +85°C.



Coaxial Adapter Mates 40-GHz 2.92-mm Connectors

Mini-Circuits' KF-KM50+ 40-GHz coaxial adapter joins 2.92-mm female to 2.92-mm male coaxial connectors with minimal added loss from DC to 40 GHz and minimal impact on amplitude and phase response with frequency.

The insertion loss is typically 0.09 dB from DC to 40 GHz. The VSWR is typically 1.03:1 from DC to 18 GHz and typically 1.04:1 from DC to 40 GHz. The RoHS-compliant, 50-Ω adapter features a passivated stainless-steel body and is qualified to 500 mating cycles. It is suitable for operating temperatures from -55 to +100°C. The low-cost adapter is available from stock.



Two-Way 0° Splitter/Combiner Handles 10 to 40 GHz

Mini-Circuits' ZN2PD-K44+ two-way 0° splitter/combiner features outstanding control of amplitude from 10 to 40 GHz, with almost negligible amplitude unbalance

of 0.2 dB across the full frequency range. The coaxial splitter/combiner handles as much as 10 W power as a splitter (2 W as a combiner) with only 1.0 dB typical insertion loss (above the nominal 3-dB split point) to 40 GHz. Typical isolation between ports is 20 dB. The broadband splitter/combiner passes as much as 600 mA (300 mA per port). Ideal for satellite and point-to-point microwave radio links as well as in radar and test applications, the component measures 3.5 × 2.0 × 0.5" with female 2.92-mm connectors.



Low-Noise Amplifier Quiets 0.5 to 12.0 GHz

Mini-Circuits' PMA2-123LN+ is a wideband, monolithic low-noise amplifier

(LNA) with low noise, high gain, and high linearity from 0.5 to 12.0 GHz. Based on GaAs pHEMT technology, the MMIC amplifier offers noise figure of typically 3.5 dB at 0.5 GHz, 2.2 dB at 2.0 GHz, and 3.1 dB at 12 GHz. It provides gain of typically 18.6 dB at 0.5 GHz, 19.2 dB at 2.0 GHz, and 15.3 dB at 12.0 GHz. The output power at 1-dB compression (P1dB) is typically +15.2 dBm at 0.5 GHz, +15.3 dBm at 2.0 GHz, and +14.0 dBm at 12.0 GHz, while the output third-order intercept point (OIP3) is typically +27.4 dBm at 0.5 GHz, +28.0 dBm at 2.0 GHz, and +26.3 dBm at 12.0 GHz. The LNA typically draws 68 mA current from a +6-Vdc supply and is supplied in a 2 × 2 mm RoHS-compliant surface-mount housing.



SP4T Switch Promises Long Life to 18 GHz

Mini-Circuits' MSP4TA-18-12D+ is a single-pole, four-throw (SP4T) switch rated for 10 million switching cycles (when switching 0.1 W RF power) and high reliability from DC to 18 GHz. The absorptive, 50-Ω fail-safe switch achieves insertion loss of typically 0.15 dB or less from DC to 8 GHz and typically 0.5 dB from DC to 18 GHz. The isolation is typically 100 dB from DC to 8 GHz and typically 80 dB from DC to 18 GHz. VSWR ranges from typically 1.20:1 from DC to 8 GHz and typically 1.30:1 from DC to 18 GHz. The switch, in a break-before-make configuration, is supplied with SMA RF connectors and 9-pin D-sub connectors. It provides reliable "sleep-time" switching, with typical switching time of 20 ms with +12 V control signals.



Cavity Filter Passes 11.2 to 11.4 GHz

Mini-Circuits' ZVBP-11G3+ cavity bandpass filter features low insertion loss of typically 2 dB throughout a 200-MHz passband from 11.2 to 11.4 GHz, with low VSWR of typically 1.40:1 through the same passband. It offers 48-dB rejection of unwanted signals throughout a lower stopband of DC to 11.03 GHz and an upper stopband of 11.58 to 20.00 GHz. Suitable for satellite communications (satcom) and radar systems, the cavity filter achieves sharp transitions from passband to stopbands. The RoHS-compliant bandpass filter is rated for 10 W maximum RF input power at operating temperatures from -40 to +85°C. It is supplied in a compact housing with female SMA connectors.




New Products

Four-Channel Attenuator Programs 0 to 95 dB to 6 GHz

THE RC4DAT-6G-95 programmable attenuator provides 0- to 95-dB attenuation with 0.25-dB resolution in four independent channels at frequencies from 1 to 6,000 MHz. Suitable for automatic test applications and fading simulators, the attenuator includes USB and Ethernet control ports in a compact shielded metal case measuring just 5.17 × 3.00 × 0.85 in. with female SMA connectors. It achieves 650-ns attenuation transition time with typical attenuation accuracy of ±0.4 dB. The plug-and-play attenuator does not require software drivers and is supplied with easy-to-install and use graphical-user-interface (GUI) software.

MINI-CIRCUITS, P.O. Box 350166, Brooklyn, NY 11235-003; (718) 934-4500; www.minicircuits.com



PAs Boost E- and W-Band Signals

POWER AMPLIFIERS (PAs) based on gallium-nitride (GaN) power transistors provide healthy output-power and efficiency levels at E- and W-band frequencies. These PAs deliver as much as 1 W output power for single-stage designs and as much as 2.5 W saturated output power for two- and four-stage amplifiers. The PAs offer as much as 20% power-added efficiency (PAE) and typical gain ranging from 15 to 40 dB. The amplifiers, which include internal voltage regulation, bias-sequencing circuitry, and reverse-voltage protection, are well-suited for high-frequency radios and test-equipment applications. As an example of an E-band PA, model AMP-12-20010 achieves 15-dB typical gain from 71 to 76 GHz with typical output power of +28.6 dBm at 1-dB compression and typical saturated output power of +31.1 dBm. It is equipped with WR-12 waveguide connectors.


MILLITECH INC., 29 Industrial Dr. E., Northampton, MA 01060; (413) 582-9620; www.millitech.com

Cable Assemblies Work Indoors and Out to 6 GHz

A LINE OF TYPE-N-TO-AMC fixed-length cable assemblies is suited for connections to wireless devices in indoor and outdoor applications, such as automated meter readers. The cable assemblies are usable from dc to 6 GHz and are constructed with Type-N bulkhead jacks and AMC right-angle

plugs terminated to RG-178 cable. The Type-N connectors feature white-bronze-plated bodies with gold-plated contacts. Bulkheads are suitable for panels to 6.5 mm thick and include O-ring protection from moisture. The AMC connectors mate with other industry-standard equivalent connectors. Standard cable assemblies lengths are from 50 to 300 mm, in 50-mm increments; custom lengths are also available.

AMPHENOL RF (HEADQUARTERS), 4 Old Newtown Rd., Danbury, CT 06810; (800) 627-7100, (203) 743-9272; www.amphenolrf.com



Two-Way Divider Channels 2 to 18 GHz


DESIGNED FOR BROADBAND USE, model R2PD-2-18-Sf-10W-w18 is a two-way power divider with low loss from 2 to 18 GHz. It exhibits 1.5-dB typical insertion loss with 14-dB typical return loss across the full frequency range. The power divider features 16-dB minimum isolation and 20-dB maximum isolation and achieves amplitude balance within 0.2 dB and phase balance within 2 deg. The component is supplied with female SMA input and output coaxial connectors and is usable over operating temperatures from -40 to +85°C.

RADITEK INC., 1702L Meridian Ave. Suite 27, San Jose, CA 95125; (408) 266-7404; raditek.com

SPDT Switch Commands Signals from 0.1 to 20.0 GHz

BROADBAND SINGLE-POLE, double-throw (SPDT) absorptive switch model SW2A101 is capable of hot switching 2 W continuous-wave (CW) power from 100 MHz to 20 GHz with low loss and fast switching speed. Supplied in a coaxial package with female SMA connectors, the compact switch exhibits maximum VSWR of 1.80:1 at all ports. The insertion loss is 1.50 dB or less to 500 MHz and 3.8 dB or less to 20 GHz. The minimum isolation is 70 dB from port to port or from input to output. The switch achieves switching speeds of 75 ns from 50% TTL control signal to 90% RF level and 45 ns from 50% TTL control signal to 10% RF signal. It operates on +5 V dc and -120 to -20 V dc supplies, and is designed to maintain rated performance levels at temperatures from -55 to +85°C.

AMPLICAL CORP., 20 Troy Rd., Whippany, NJ 07981; (973) 386-1119;
www.noisewave.com, www.amplical.com



Broadband Attenuator Handles 4 to 18 GHz

SUITABLE FOR EXTREMELY BROADBAND system and test applications, model 5-9844-15 is a rugged coaxial attenuator with 15-dB attenuation from 4 to 18 GHz. It handles power levels to 5 W continuous wave (CW) and 3 kW peak power with low insertion loss of only 1 dB across the frequency range. It exhibits a VSWR of 1.70:1. The compact component measures just 2.5 × 2.0 × 0.56 in., weighs 3 oz., and can be supplied with SMA or Type-N female connectors. It is available with a number of options, including a panel-mount configuration, turn counter, and digital readout.

ARRA INC., 15 Harold Ct., Bay Shore, NY 11706-2296;
(516) 231-8400; www.arra.com

Cavity Filter Passes 4,395 to 4,955 MHz

CAVITY BANDPASS FILTER (BPF) model AB4675B1348 operates with a 560-MHz passband centered at 4,675 MHz. It handles signal power levels as high as 450 W with low passband insertion loss of 1.5 dB or less. The passband VSWR is 1.50:1 or less. The BPF delivers out-of-band attenuation of better than 40 dB at 4,100 MHz and at 5,250 MHz. The robust filter measures 5.73 × 1.50 × 0.99 in. and is equipped with female SMA connectors. It has an operating temperature range of -30 to +75°C.

ANATECH ELECTRONICS INC., 70 Outwater Ln., Garfield, NJ 07026; (973) 772-4242;
www.anatechelectronics.com



Low-Jitter Oscillators Lock Networks to 2.1 GHz

A PAIR of low-jitter oscillators, models NP5032S and NP7050S, provide similar performance levels from 15 MHz to 2.1 GHz, but are supplied in different packages. Suitable for high-speed networking applications, such as SDH and SONET, the NP5032S is housed in an 8-pin ceramic SMD package measuring 5.0 × 3.2 × 1.2 mm. The NP7050S comes in a surface-mount package measuring 7.0 × 5.0 × 1.6 mm. With output types of CMOS, LVPECL, LVDS, CML, and HCSL to choose from, the oscillators achieve typical jitter of 130 fs RMS. The operating temperature range is -40 to +85°C.


NDK AMERICA, 425 N. Martingale Rd., Ste. 1330, Schaumburg, IL 60173;
(847) 852-4165; www.ndk.com

GaN Power Amplifier Pulses 9.0 to 9.9 GHz

BUILT FOR X-BAND radar systems as well as other high-power applications, model BMPC9X89X8-8000 is a solid-state power amplifier (PA) capable of 8 kW peak output power from 9.0 to 9.9 GHz. The PA, which is based on gallium-nitride (GaN) semiconductor technology, works over instantaneous bandwidths as wide as 500 MHz with 69-dB nominal gain and less than 1-dB pulse droop. The pulse rise/fall time is typically 50 ns. The rugged amplifier handles signals with pulse widths from 0.25 to 100 µs at 10% maximum duty cycle. It includes an Ethernet control port and built-in thermal and load protection.

COMTECH PST, 105 Baylis Rd., Melville, NY 11747; (631) 777-8900;
www.comtechpst.com





SPDT PIN Diode Switch Commands 0.1 to 67.0 GHz



DESIGNED FOR BROADBAND applications, the FMSW2026 single-pole, double-throw (SPDT) PIN diode absorptive switch spans 100 MHz to 67 GHz. It handles input power to 0.5 W continuous wave (CW) with 6-dB typical insertion loss. The switch achieves 65-dB typical isolation and boasts 100-ns switching speed. It has a TTL-compatible driver and features an operating-temperature range of -30 to $+60^{\circ}\text{C}$. It runs on $+5$ and -5 V dc, and includes 1.85-mm coaxial connectors.

FAIRVIEW MICROWAVE, 17792 Fitch, Irvine, CA 92614; (978) 682-6936; www.fairviewmicrowave.com

Patch Antennas Direct Body-Worn Systems

DIRECTIONAL PATCH ANTENNAS developed by Southwest Antennas for body-worn wireless applications from 1,350 to 1,390 MHz are now available with sales and design support from RFMW, Ltd. Model 1065-031 operates with left-hand circular polarization (LHCP), while model 1065-032 has right-hand circular polarization (RHCP). The antennas are optimized for multiple-input, multiple-output (MIMO) use and mobile ad hoc network (MANET) radio systems. The antennas, which measure $3.75 \times 3.75 \times 0.51$ in., are specified for 4.2-dBic free-space gain. They are supplied with a stainless-steel female SMA connector and ultraviolet (UV)-stable radome, and can withstand two hours' immersion in salt water.

RFMW LTD. (SOUTHWEST ANTENNA STOCKING DISTRIBUTOR), 188 Martinvale Ln., San Jose, CA 95119; (408) 414-1450; www.rfmw.com



Schottky Diodes Reach 40 GHz

A SERIES OF SILICON Schottky diodes supports circuits through 40 GHz. They boast low $1/f$ noise, low resistance, and small junction capacitance for low-, medium-, and high-barrier applications. The diodes, which can be supplied as chips—or else in glass, ceramic, or beam-lead packages—are candidates for RF/microwave mixers, doublers, and detector circuits. The diodes are rated for breakdown voltages from $+3$ V dc (for low-barrier diodes) to $+6$ V dc (for high-barrier diodes), capacitances from 0.15 to 0.35 pF, and series resistances from 14 to 20 Ω . Diodes in bridge quad and ring quad configurations provide stable performance across operating temperatures from -55 to $+150^{\circ}\text{C}$.

SEMIGEN INC., 3920 Candia Rd., Manchester, NH 03109; (603) 624-8311; www.Semigen.net

Highpass Filter Cuts Off at 57 GHz

HIGHPASS FILTER MODEL HPF-640 is part of a complete filter series covering bandwidth from 10 to 110 GHz. This unit passes signals within the V-band spectrum as low as 57 GHz with worst-case passband insertion loss of 1.5 dB and typical passband insertion loss of 1.0 dB. It features a rejection cutoff at 57 GHz with 20-dB rejection at 55 GHz and 40-dB rejection at 54 GHz and below. The highpass filter is supplied with WR-15 waveguide connectors.

SPACEK LABS INC., 212 E. Gutierrez St., Santa Barbara, CA 93101; (805) 564-4404; www.spaceklabs.com



Ultra-Wideband
10 MHz to 13 GHz



Power Handling
up to 2W

Programmable ATTENUATORS

0 to 120dB 0.25dB Step 1 MHz to 13 GHz* from **\$395**

Features

- Models with attenuation range up to 30, 60, 63, 90, 95, 110 or 120 dB
- Choose from USB, Ethernet, RS232 and SPI control options
- Use our software or yours! User-friendly GUI and DLLs included[†]
- Sweep or hop attenuation levels
- Save and recall customized attenuation patterns
- Pocket-sized package, as small as 3.0 x 2.0 x 0.6"
- **Now** 16 unique models in stock, ready to ship!

* Specs may vary by model. See data sheets for specific model information.

[†] No drivers required. DLL objects for 32/64 bit Windows® environments using ActiveX® and .NET® frameworks.

Perfect for...

- Fading simulators
- Handover system evaluation
- Automated test equipment
- And MORE!

Visit minicircuits.com for detailed model specs, application notes, and more!
Place your order today and have them on your test bench as soon as tomorrow!



[www.minicircuits.com/products/
programmable_attenuators.shtml](http://www.minicircuits.com/products/programmable_attenuators.shtml)



ADVERTISER	PAGE
A	
ARRA INC.....	C3
www.arra.com	
C	
CALIFORNIA EASTERN LAB.....	49
www.cel.com/switches	
CIAO WIRELESS INC.....	17
www.ciaowireless.com	
COILCRAFT.....	c4
www.coilcraft.com	
COMMUNICATION CONCEPTS INC.....	76
www.communication-concepts.com	
D	
DBM CORP.....	18
www.dbmcorp.com	
DELTA SIGMA INC.....	8-9
www.111rfpower.com	
E	
EXODUS ADVANCED COMMUNICATIONS.....	51
www.exoduscomm.com	
F	
FAIRVIEW.....	24, 25
www.fairviewmicrowave.com	
H	
HEROTEK INC.....	13
www.herotek.com	
HOLZWORTH INSTRUMENTATION.....	56
www.holzworth.com	
J	
JFW INDUSTRIES INC.....	34
www.jfwindustries.com	
K	
KOAXIS INC.....	50
www.koaxis.com	
KRYTAR.....	39
www.krytar.com	
L	
L-3 NARDA-MITEQ.....	3
www.nardamiteq.com	

ADVERTISER	PAGE
L	
LINEAR TECHNOLOGY CORPORATION.....	19
www.linear.com/product/LTC5549	
M	
M/A COM TECHNOLOGY SOLUTIONS, INC.....	C2-1
www.macom.com/gan	
MECA ELECTRONICS INC.....	7
www.e-MECA.com	
MINI-CIRCUITS/SCI COMPONENTS.....	12, 14-15, 23, 29, 30-31, 35, 41, 45, 55, 61, 65, 69, 71, 75, 79, 81, 83, 87
www.minicircuits.com	
N	
NI AWR.....	4
www.ni.com/awr	
NI MICROWAVE COMPONENTS.....	26
www.ni-microwavecomponents.com/quicksyn	
P	
PASTERNAK ENTERPRISES.....	36
www.pasternack.com	
PEREGRINE SEMICONDUCTOR CORPORATION.....	11
www.psemi.com	
PLANAR MONOLITHICS INDUSTRIES.....	2
www.pmi-rf.com	
PRONGHORN SOLUTIONS.....	38
www.pronghorn-solutions.com	
S	
SAGE MILLIMETER INC.....	42-43
www.sagemillimeter.com	
SKYWORKS.....	6
www.skyworksinc.com	
STANFORD RESEARCH SYSTEMS (SRS).....	27
www.thinkSRS.com	
SYNERGY MICROWAVE.....	35, 47
www.synergymwave.com	
W	
WAVELINE INC.....	16
www.wavelineinc.com	

This index is provided as an additional service by the publisher, who assumes no responsibility for errors or omissions.


Subscription Assistance and Information:

(ISSN 0745-2993)
Microwaves & RF is published monthly. **Microwaves & RF** is sent free to individuals actively engaged in high-frequency electronics engineering. In addition, paid subscriptions are available. Subscription rates for U.S. are \$95 for 1 year (\$120 in Canada, \$150 for International). Published by Penton Media, Inc., 9800 Metcalf Ave., Overland Park, KS 66212-2216. Periodicals Postage Paid at Kansas City and additional mailing offices. POSTMASTER: Send change of address to *Microwaves & RF* PO Box 2100, Skokie, IL 60076-7800. For paid subscription information, please contact *Microwaves & RF* at PO Box 2100, Skokie IL 60076-7800. Canada Post Publications Mail agreement No. 40612608. Canada return address: IMEX Global Solutions PO Box 25542, London ON N6C 6B2.

Back issues of *MicroWaves* and *Microwaves & RF* are available on microfilm and can be purchased from National Archive Publishing Company (NAPC). For more information, call NAPC at 734-302-6500 or 800-420-NAPC (6272) x 6578. Copying: Permission is granted to users registered with the Copyright Clearance Center, Inc. (CCC) to photocopy any article, with the exception of those for which separate copyright ownership is indicated on the first page of the article, provided that a base fee of \$1.25 per copy of the article plus 60 cents per page is paid directly to the CCC, 222 Rosewood Dr., Danvers, MA 01923. (Code 0745-2993/02 \$1.25 + .60) Copying done for other than personal or internal reference use without the expressed permission of Penton Media, Inc., is prohibited. Requests for special permission or bulk orders should be addressed in writing to the publisher.

Copyright 2017 • Penton • All rights reserved. Printed in the U.S.

We've kept these ARRA Attenuators under our hat long enough...



Low Freq. Variable Attenuators

The "no-nonsense" attenuator...

For Audio, IF, and VHF.

Simple, straight forward, no frills. Not bad when this economy model performs in the same classy manner as other ARRA high precision units.

- SMA connectors, others available
- Off-the-shelf delivery
- 50 ohm impedance, 75 ohms available
- Specs that beat the competition's

Directly calibrated models

Freq Range (MHz)	Atten Range (dB)	Atten vs Freq (dB)	Model No.
DC-60	40	± 1.0	0682-40F
DC-100	15	± 0.3	0682-15F
DC-100	30	± 0.5	0682-30F
DC-250	10	± 0.5	0682-10F

Uncalibrated models

DC-60	40	± 1.0	0682-40
DC-100	20	± 0.6	0682-20
DC-100	30	± 0.5	0682-30
DC-200	30	± 2.0	0682-30A
DC-250	15	± 1.2	0682-15
DC-500	10	± 0.25	0682-10

Phaseless Variable Attenuators

The "incredible" attenuator...

Elegant, classic, exceptional. With all the extras you'd expect at the top of the ARRA line. So uniquely new in its approach, it's one of a kind. Nothing else like it on the market. It's got everything...

- Low phase
- High RF Power
- Low VSWR & Insertion loss
- Extremely flat frequency response
- 0-3 dB & high attenuation models
- Bands from 350-5000 MHz

...the last word in variable attenuators

ARRA INC.


15 Harold Court • Bay Shore NY 11706-2296

Tel 631-231-8400

Fax 631-434-1116

E-Mail: sales@arra.com

Visit our website at www.arra.com



Ideal for use in Bias Tees, Coilcraft conical inductors offer flat bandwidth and high impedance to 40 GHz

Coilcraft BCL/BCR Series conical inductors operate across a frequency range of 10 MHz to 40 GHz, letting you replace a series of narrow band inductors with one part.

Both series provide excellent return loss and insertion loss. Their unique conical shape optimizes the effects of capacitance, maintaining high impedance across your frequency spectrum.

Choose from a rugged, surface mount package or our flying lead configuration. And for applications below 6 GHz, try our high current 4310LC wideband bias choke.

Learn more and order your free evaluation samples by visiting us online at: coilcraft.com/conicals.

